

MasterProtect C TMB 350 Pepper Spice 877

Version **Revision Date:** SDS Number: Date of last issue: 12/01/2020 03/26/2021 000000874700 Date of first issue: 12/01/2020 2.0

SECTION 1. IDENTIFICATION

Product name MasterProtect C TMB 350 Pepper Spice 877

Product code 00000000050568196 00000000050568196

Manufacturer or supplier's details

Company name of supplier Master Builders-Construction Systems

US, LLC

Address 23700 CHAGRIN BLVD

Beachwood OH 44122

ChemTel: +1-813-248-0585 Emergency telephone

Recommended use of the chemical and restrictions on use

Recommended use Product for construction chemicals

Restrictions on use Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Skin sensitization Category 1

Carcinogenicity (Inhalation) Category 1A

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 1 (Lungs)

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 2 (Kidney, Immune system)

Short-term (acute) aquatic

hazard

Category 3

Long-term (chronic) aquatic

hazard

Category 3

GHS label elements

Hazard pictograms





Signal Word Danger

Hazard Statements H317 May cause an allergic skin reaction.



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/01/2020

 2.0
 03/26/2021
 000000874700
 Date of first issue: 12/01/2020

H350 May cause cancer by inhalation.

H372 Causes damage to organs (Lungs) through prolonged or

repeated exposure if inhaled.

H373 May cause damage to organs (Kidney, Immune system)

through prolonged or repeated exposure if inhaled. H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing must not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P308 + P313 IF exposed or concerned: Get medical advice/attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No applicable information available.

Components

-		
Chemical name	CAS-No.	Concentration (% w/w)
Quartz (SiO2)	14808-60-7	>= 5 - < 10
cristobalite	14464-46-1	>= 1 - < 5
Titanium dioxide	13463-67-7	>= 1 - < 5
talc	14807-96-6	>= 0.1 - < 1
1,3,5-Triazine-1,3,5(2H,4H,6H)-	4719-04-4	>= 0.1 - < 1
triethanol		
diuron	330-54-1	< 0.1
3-iodo-2-propynyl butylcarbamate	55406-53-6	< 0.1

Actual concentration is withheld as a trade secret



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/01/2020

 2.0
 03/26/2021
 000000874700
 Date of first issue: 12/01/2020

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.

Immediately remove contaminated clothing.

If inhaled : If difficulties occur after vapour/aerosol has been inhaled,

remove to fresh air and seek medical attention.

In case of skin contact : After contact with skin, wash immediately with plenty of water

and soap.

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact : Hold eyes open and rinse slowly and gently with water for 15

to 20 minutes. Remove contact lenses, if present, after first 5

minutes, then continue rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention. Do NOT induce vomiting.

Most important symptoms

and effects, both acute and delayed

May cause an allergic skin reaction.

May cause cancer.

Causes damage to organs through prolonged or repeated

exposure.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam

Dry powder Water spray

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

See SDS section 10 - Stability and reactivity.

Hazardous combustion prod-

ucts

harmful vapours nitrogen oxides

fumes/smoke carbon black carbon oxides

Further information : The degree of risk is governed by the burning substance and

the fire conditions.

If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not

allow to reach sewage or effluent systems.

Contaminated extinguishing water must be disposed of in



Version **Revision Date:** SDS Number: Date of last issue: 12/01/2020 03/26/2021 000000874700 Date of first issue: 12/01/2020 2.0

accordance with official regulations.

for fire-fighters

Special protective equipment : Wear a self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emergency procedures

Do not breathe vapour/aerosol/spray mists.

Wear eye/face protection.

If exposed to high vapour concentration, leave area immedi-

ately.

Use personal protective clothing.

Handle in accordance with good building materials hygiene

and safety practice.

Environmental precautions Contain contaminated water/firefighting water.

Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up Large spills should be collected mechanically (remove by

pumping) for disposal.

Pick up with inert absorbent material (e.g. sand, earth etc.). Spilled product should be disposed in accordance with all

applicable government regulations.

SECTION 7. HANDLING AND STORAGE

Avoid aerosol formation. Advice on safe handling

Avoid inhalation of mists/vapours.

Avoid skin contact. Avoid contact with eyes.

Further information on stor-

age conditions

Keep only in the original container in a cool, dry, well-

ventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

Materials to avoid No applicable information available.

Further information on stor-

age stability

No data available

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
		(Form of	ters / Permissible	
		exposure)	concentration	
diuron	330-54-1	TWA value	10 mg/m3	ACGIHTLV
		REL value	10 mg/m3	NIOSH
		TWA value	10 mg/m3	29 CFR
				1910.1000
				(Table Z-1-A)



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/01/2020

 2.0
 03/26/2021
 000000874700
 Date of first issue: 12/01/2020

		TWA	10 mg/m3	ACGIH
		TWA	10 mg/m3	NIOSH REL
		TWA	10 mg/m3	OSHA P0
Titanium dioxide	13463-67-7	TWA value	10 mg/m3	ACGIHTLV
Thailiaili dioxide	10400 07 7	PEL (Total	15 mg/m3	29 CFR
		dust)	10 1119/1110	1910.1000
		auot,		(Table Z-1)
		TWA value	10 mg/m3	29 CFR
		(Total dust)		1910.1000
		(10000)		(Table Z-1-A)
		TWA (total	15 mg/m3	OSHA Z-1
		dust)	3. 3.	
		TWA (Total	10 mg/m3	OSHA P0
		dust) `		
		TWÁ	10 mg/m3	ACGIH
			(Titanium dioxide)	
cristobalite	14464-46-1	TWA value	0.025 mg/m3	ACGIHTLV
		(Respirable		
		fraction)		
		TWA (Res-	0.05 mg/m3	OSHA Z-1
		pirable dust)		
		TWA (respir-	0.05 mg/m3	OSHA P0
		able dust		
		fraction)		
		TWA (Res-	0.025 mg/m3	ACGIH
		pirable par-	(Silica)	
		ticulate mat-		
		ter)		
		PEL (respir-	0.05 mg/m3	OSHA CARC
		able)		
		TWA (Res-	0.05 mg/m3	NIOSH REL
(0:00)	1,1000,00,7	pirable dust)	(Silica)	A COULTLY
Quartz (SiO2)	14808-60-7	TWA value	0.025 mg/m3	ACGIHTLV
		(Respirable		
		fraction) TWA value	0.05 mg/m3	29 CFR
		I WA Value	(Respirable dust)	1910.1001-
			(IXespirable dust)	1050
		OSHA Action	0.025 mg/m3	29 CFR
		level	(Respirable dust)	1910.1001-
		10 01	(respirable dust)	1050
		REL value	0.05 mg/m3	NIOSH
		(Respirable	0.00 mg/mo	1110011
		dust)		
		TWA (Res-	0.05 mg/m3	OSHA Z-1
		pirable dust)		
		TWA (respir-	10 mg/m3 /	OSHA Z-3
		able)	%SiO2+2	
		TWA (respir-	250 mppcf /	OSHA Z-3
		able)	%SiO2+5	
		TWA (respir-	0.1 mg/m3	OSHA P0
		able dust		
		1	Ĭ	I
		fraction)		



MasterProtect C TMB 350 Pepper Spice 877

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/01/2020

 2.0
 03/26/2021
 000000874700
 Date of first issue: 12/01/2020

pirable par- ticulate mat- ter)	(Silica)	
PEL (respir- able)	0.05 mg/m3	OSHA CARC
TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL

Engineering measures : No applicable information available.

Personal protective equipment

Respiratory protection : Wear respiratory protection if ventilation is inadequate.

Wear a NIOSH-certified (or equivalent) organic va-

pour/particulate respirator.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's

directions for use should be observed because of great di-

versity of types.

Eye protection : Safety glasses with side-shields.

Skin and body protection : light protective clothing

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.

Hands and/or face should be washed before breaks and at

the end of the shift.

At the end of the shift the skin should be cleaned and skin-

care agents applied.

Remove contaminated clothing immediately and clean before

re-use or dispose it if necessary.

Gloves must be inspected regularly and prior to each use.

Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : No applicable information available.

Odor : mild

Odor Threshold : No data available



MasterProtect C TMB 350 Pepper Spice 877

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/01/2020

 2.0
 03/26/2021
 000000874700
 Date of first issue: 12/01/2020

pH : 9 - 10

Melting point : No applicable information available.

Boiling point : No applicable information available.

Flash point : 200.12 °F / 93.40 °C

Method: closed cup

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not flammable

Self-ignition : not self-igniting

Upper explosion limit / Upper

flammability limit

No applicable information available.

Lower explosion limit / Lower

flammability limit

No applicable information available.

Vapor pressure : No applicable information available.

Relative vapor density : No applicable information available.

Relative density : No applicable information available.

Density : 1.3660 g/cm3 (73.40 °F / 23.00 °C)

Solubility(ies)

Water solubility : partly miscible (73.40 °F / 23.00 °C)

Solubility in other solvents : No applicable information available.

Partition coefficient: n-

octanol/water

No applicable information available.

Autoignition temperature : Based on the water content the product does not ignite.

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : 5,600.000 mPa.s (73.40 °F / 23.00 °C)

Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive

Oxidizing properties : Not an oxidizer.

Sublimation point : No applicable information available.



MasterProtect C TMB 350 Pepper Spice 877

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/01/2020

 2.0
 03/26/2021
 000000874700
 Date of first issue: 12/01/2020

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as pre-

scribed/indicated.

Chemical stability : The product is stable if stored and handled as pre-

scribed/indicated.

Possibility of hazardous reac-

tions

The product is stable if stored and handled as pre-

scribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute toxicity estimate: > 200 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/01/2020

 2.0
 03/26/2021
 000000874700
 Date of first issue: 12/01/2020

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer by inhalation.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Lung) through prolonged or repeated exposure if inhaled. May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use.

The product has not been tested. The statements on toxicology have been derived from the properties of the individual

components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Components:

diuron:

M-Factor (Acute aquatic tox- : 10

icity)

M-Factor (Chronic aquatic

toxicity)

: 10

3-iodo-2-propynyl butylcarbamate:

M-Factor (Acute aquatic tox-

•

icity)

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/01/2020

 2.0
 03/26/2021
 000000874700
 Date of first issue: 12/01/2020

: 1

M-Factor (Chronic aquatic

toxicity)

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regula-

tions.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/01/2020

 2.0
 03/26/2021
 000000874700
 Date of first issue: 12/01/2020

SECTION 15. REGULATORY INFORMATION

US State Regulations

Pennsylvania Right To Know

 Titanium dioxide
 13463-67-7

 cristobalite
 14464-46-1

 Quartz (SiO2)
 14808-60-7

New Jersey Right To Know

 Titanium dioxide
 13463-67-7

 cristobalite
 14464-46-1

 Carbon black
 1333-86-4

 talc
 14807-96-6

California Prop. 65

WARNING: This product can expose you to chemicals including Quartz (SiO2), cristobalite, Titanium dioxide, Carbon black, diuron, benzophenone, Quartz (SiO2), which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this product are either listed as

active on the TSCA Inventory or are in compliance with a

TSCA Inventory exemption.


SECTION 16. OTHER INFORMATION

Further information

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/01/2020


 2.0
 03/26/2021
 000000874700
 Date of first issue: 12/01/2020

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1910.1000

29 CFR 1910.1001-1050 : OSHA - Specifically Regulated Substances (29 CFR

1910.1001-1050)

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

29 CFR 1910.1000 (Table Z- :

1-A) / TWA value

: Time Weighted Average (TWA):

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

29 CFR 1910.1001-1050 /

OSHA Action level

: OSHA Action level:

29 CFR 1910.1001-1050 / : Time Weighted Average (TWA):

TWA value

ACGIH / TWA : 8-hour, time-weighted average
ACGIHTLV / TWA value : Time Weighted Average (TWA):
NIOSH / REL value : Recommended exposure limit (REL):

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA P0 / TWA : 8-hour time weighted average



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/01/2020

 2.0
 03/26/2021
 000000874700
 Date of first issue: 12/01/2020

OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

Revision Date : 03/26/2021

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING



MasterProtect C TMB 350 Pepper Spice 877

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 12/01/2020

 2.0
 03/26/2021
 000000874700
 Date of first issue: 12/01/2020

WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN