

MasterProtect EL 750 FN Ser U

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/15/2020

 2.0
 06/18/2021
 000000261440
 Date of first issue: 10/15/2020

SECTION 1. IDENTIFICATION

Product name : MasterProtect EL 750 FN Ser U

Product code : 00000000051719031 00000000051719031

Manufacturer or supplier's details

Company name of supplier : Master Builders-Construction Systems

US, LLC

Address : 23700 CHAGRIN BLVD

Beachwood OH 44122

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Waterproof coating

Restrictions on use : Reserved for industrial and professional use.

National Emergency Telephone Number USA: +1-800-255-3924 ChemTel contract no. MIS9240420

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity

- repeated exposure

Category 2 (Kidney)

Short-term (acute) aquatic

hazard

Category 3

Long-term (chronic) aquatic

hazard

Category 3

GHS label elements

Hazard pictograms :

Signal Word : Danger

Hazard Statements : H350 May cause cancer by inhalation.

H373 May cause damage to organs (Kidney) through prolonged

or repeated exposure. H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.



MasterProtect EL 750 FN Ser U

Version Revision Date: SDS Number: Date of last issue: 10/15/2020 2.0 06/18/2021 000000261440 Date of first issue: 10/15/2020

Precautionary Statements : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Aqueous solution

Components

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	>= 30 - < 50
Titanium dioxide	13463-67-7	>= 1 - < 5
Perlite, expanded	93763-70-3	>= 1 - < 5
ethylene glycol	107-21-1	>= 1 - < 5
zinc oxide	1314-13-2	>= 0.1 - < 1
Distillates (petroleum), solvent- dewaxed heavy paraffinic	64742-65-0	>= 0.1 - < 1
Quartz (SiO2)	14808-60-7	>= 0.1 - < 1
diuron	330-54-1	< 0.1
3-iodo-2-propynyl butylcarbamate	55406-53-6	< 0.1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.

Immediately remove contaminated clothing.

If inhaled : If difficulties occur after vapour/aerosol has been inhaled,

remove to fresh air and seek medical attention.

In case of skin contact : After contact with skin, wash immediately with plenty of water

and soap.



Version **Revision Date:** SDS Number: Date of last issue: 10/15/2020 06/18/2021 000000261440 Date of first issue: 10/15/2020 2.0

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact Hold eyes open and rinse slowly and gently with water for 15

to 20 minutes. Remove contact lenses, if present, after first 5

minutes, then continue rinsing.

If eye irritation persists, consult a specialist.

If swallowed Immediately rinse mouth and then drink 200-300 ml of water,

> seek medical attention. Do NOT induce vomiting.

Most important symptoms and effects, both acute and

delayed

May cause cancer by inhalation.

May cause damage to organs through prolonged or repeated

exposure.

Notes to physician Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam

> Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

water jet

Specific hazards during fire

fighting

See SDS section 10 - Stability and reactivity.

Hazardous combustion prod-

ucts

harmful vapours nitrogen oxides fumes/smoke carbon black carbon oxides

Further information The degree of risk is governed by the burning substance and

the fire conditions.

If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not

allow to reach sewage or effluent systems.

Contaminated extinguishing water must be disposed of in

accordance with official regulations.

for fire-fighters

Special protective equipment : Wear a self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer-

gency procedures

Do not breathe vapour/aerosol/spray mists.

Wear eye/face protection.

If exposed to high vapour concentration, leave area immedi-

Version **Revision Date:** SDS Number: Date of last issue: 10/15/2020 06/18/2021 000000261440 Date of first issue: 10/15/2020 2.0

ately.

Use personal protective clothing.

Handle in accordance with good building materials hygiene

and safety practice.

Contain contaminated water/firefighting water. **Environmental precautions**

Do not discharge into drains/surface waters/groundwater.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Dispose of rinse water in accordance with local and national

regulations.

Keep container tightly closed in a dry and well-ventilated Conditions for safe storage

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Keep only in the original container in a cool, dry, well-

ventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

Recommended storage tem: :

perature

> 39 °F / > 4 °C

Further information on stor-

age stability

PROTECT FROM FREEZING DURING THE COLD-SEASON

(BELOW 40°F / 5°C).

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Limestone	1317-65-3	REL value (Respirable)	5 mg/m3	NIOSH



MasterProtect EL 750 FN Ser U

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/15/2020

 2.0
 06/18/2021
 000000261440
 Date of first issue: 10/15/2020

		REL value	10 mg/m3	NIOSH
		(Total) PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium car- bonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH REL
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
Perlite, expanded	93763-70-3	REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
ethylene glycol	107-21-1	TWA value	25 ppm	ACGIHTLV



MasterProtect EL 750 FN Ser U

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/15/2020

 2.0
 06/18/2021
 000000261440
 Date of first issue: 10/15/2020

		(Vapor fraction)		
		STEL value (Vapor frac- tion)	50 ppm	ACGIHTLV
		STEL value (Aerosol, inhalable.)	10 mg/m3	ACGIHTLV
		TWA (Vapor)	25 ppm	ACGIH
		STEL (Va- por)	50 ppm	ACGIH
		STEL (Inhal- able fraction, Aerosol only)	10 mg/m3	ACGIH
		С	50 ppm 125 mg/m3	OSHA P0
zinc oxide	1314-13-2	TWA value (Respirable fraction)	2 mg/m3	ACGIHTLV
		STEL value (Respirable fraction)	10 mg/m3	ACGIHTLV
		REL value (fumes/smok e)	5 mg/m3	NIOSH
		REL value (dust)	5 mg/m3	NIOSH
		STEL value (fumes/smok e)	10 mg/m3	NIOSH
		Ceil_Time (dust)	15 mg/m3	NIOSH
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (fumes/smok e)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (fumes/smok e)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		STEL value (fumes/smok e)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Res-	2 mg/m3	ACGIH



MasterProtect EL 750 FN Ser U

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/15/2020

 2.0
 06/18/2021
 000000261440
 Date of first issue: 10/15/2020

		pirable par- ticulate mat- ter)		
		STEL (Respirable particulate matter)	10 mg/m3	ACGIH
		TWA (Dust)	5 mg/m3	NIOSH REL
		TWA	5 mg/m3	NIOSH REL
		(Fumes)	o mg/me	
		ST (Fumes)	10 mg/m3	NIOSH REL
		C (Dust)	15 mg/m3	NIOSH REL
		TWA (Fumes)	5 mg/m3	OSHA Z-1
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Fumes)	5 mg/m3	OSHA P0
		STEL (Fumes)	10 mg/m3	OSHA P0
Distillates (petroleum), solvent- dewaxed heavy paraffinic	64742-65-0	TWA value (Inhalable fraction)	5 mg/m3	ACGIHTLV
		STEL value (Mist)	10 mg/m3	NIOSH
		REL value (Mist)	5 mg/m3	NIOSH
		REL value	350 mg/m3	NIOSH
		Ceil_Time	1,800 mg/m3	NIOSH
		PEL (Mist)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Mist)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particu-	5 mg/m3	ACGIH
		late matter)	5/ C	00114 50
		TWA (Mist)	5 mg/m3	OSHA P0 NIOSH REL
		TWA (Mist) ST (Mist)	5 mg/m3 10 mg/m3	NIOSH REL
Quartz (SiO2)	14808-60-7	TWA value	0.025 mg/m3	ACGIHTLV
Qualte (SIO2)	14000-00-7	(Respirable fraction)	0.020 mg/m3	AGGIIILV
		TWA value	0.05 mg/m3	29 CFR



MasterProtect EL 750 FN Ser U

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/15/2020

 2.0
 06/18/2021
 000000261440
 Date of first issue: 10/15/2020

			(Respirable dust)	1910.1001- 1050
		OSHA Action level	0.025 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
		REL value (Respirable dust)	0.05 mg/m3	NIOSH
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
		TWA (Res- pirable par- ticulate mat- ter)	0.025 mg/m3 (Silica)	ACGIH
		PEL (respirable)	0.05 mg/m3	OSHA CARC
		TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL
diuron	330-54-1	TWA value	10 mg/m3	ACGIHTLV
		REL value	10 mg/m3	NIOSH
		TWA value	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	10 mg/m3	ACGIH
		TWA	10 mg/m3	NIOSH REL
		TWA	10 mg/m3	OSHA P0

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits

may be exceeded.

Use NIOSH approved respiratory protection.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's

directions for use should be observed because of great di-

versity of types.

Eye protection : Safety glasses with side-shields.

Skin and body protection : Impermeable protective clothing

Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective

boots, chemical-protection suit.



MasterProtect EL 750 FN Ser U

Version Revision Date: SDS Number: Date of last issue: 10/15/2020 2.0 06/18/2021 000000261440 Date of first issue: 10/15/2020

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.

Hands and/or face should be washed before breaks and at

the end of the shift.

At the end of the shift the skin should be cleaned and skin-

care agents applied.

Remove contaminated clothing immediately and clean before

re-use or dispose it if necessary.

Gloves must be inspected regularly and prior to each use.

Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : pigmented

Odor : slight odour, sweetish

Odor Threshold : not determined

pH : approx. 9.2 - 10.0

Melting point : No data available

Boiling point : 379 - 401 °F / 193 - 205 °C

Flash point : 199 °F / 93 °C

Evaporation rate : No data available

Flammability (liquids) : The product is not flammable.

Upper explosion limit / Upper

flammability limit

15.3 %(V)

Lower explosion limit / Lower

flammability limit

3.2 %(V)

Vapor pressure : No data available

Relative vapor density : Heavier than air.



MasterProtect EL 750 FN Ser U

Version Revision Date: SDS Number: Date of last issue: 10/15/2020 2.0 06/18/2021 000000261440 Date of first issue: 10/15/2020

Relative density : 1.2 - 1.4

Density : approx. 1.00 g/cm3 (68 °F / 20 °C)

Solubility(ies)

Water solubility : soluble (68 °F / 20 °C)

Solubility in other solvents : soluble

Partition coefficient: n-

octanol/water

No data available

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : Based on its structural properties the product is not classified

as oxidizing.

Sublimation point : No data available

Molecular weight : No data available

Metal corrosion rate : Corrosive effects to metal are not anticipated.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as pre-

scribed/indicated.

Chemical stability : The product is stable if stored and handled as pre-

scribed/indicated.

Possibility of hazardous reac-

tions

The product is stable if stored and handled as pre-

scribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

. See 353 section 7 - Hariding and storage

: Strong acids Strong bases

> Strong oxidizing agents Strong reducing agents

Hazardous decomposition

Incompatible materials

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/15/2020

 2.0
 06/18/2021
 000000261440
 Date of first issue: 10/15/2020

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

May cause cancer by inhalation.

IARC Group 1: Carcinogenic to humans

Quartz (SiO2) 14808-60-7

(Silica dust, crystalline)

Group 2A: Probably carcinogenic to humans

Perlite, expanded 93763-70-3

(glass)

Group 2B: Possibly carcinogenic to humans

Titanium dioxide 13463-67-7

OSHA OSHA specifically regulated carcinogen

Quartz (SiO2) 14808-60-7

(crystalline silica)

NTP Known to be human carcinogen

Quartz (SiO2) 14808-60-7

(Silica, Crystalline (Respirable Size))

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

May cause damage to organs (Kidney) through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.



MasterProtect EL 750 FN Ser U

Version Revision Date: SDS Number: Date of last issue: 10/15/2020 2.0 06/18/2021 000000261440 Date of first issue: 10/15/2020

Further information

Product:

Remarks : Health injuries are not known or expected under normal use.

The product has not been tested. The statements on toxicology have been derived from the properties of the individual

components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Components:

zinc oxide:

M-Factor (Acute aquatic tox- : 1

icity)

M-Factor (Chronic aquatic

toxicity)

tic : 1

diuron:

M-Factor (Acute aquatic tox- :

icity)

M-Factor (Chronic aquatic

toxicity)

10

10

3-iodo-2-propynyl butylcarbamate:

M-Factor (Acute aquatic tox- : 10

icity)

M-Factor (Chronic aquatic

toxicity)

: 1

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available



MasterProtect EL 750 FN Ser U

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/15/2020

 2.0
 06/18/2021
 000000261440
 Date of first issue: 10/15/2020

Other adverse effects

Product:

Additional ecological infor-

mation

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regula-

tions

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

ethylene glycol 107-21-1 >= 1 - < 5 %

US State Regulations

Pennsylvania Right To Know

Limestone 1317-65-3



Version 2.0	Revision Date: 06/18/2021	SDS Number: 000000261440	Date of last issue: 10/15/2020 Date of first issue: 10/15/2020	
	Titanium dioxide Perlite, expanded ethylene glycol zinc oxide diuron ammonia ammonia, aqueous	s solution	13463-67-7 93763-70-3 107-21-1 1314-13-2 330-54-1 7664-41-7 1336-21-6	
New 、	Jersey Right To Know Limestone Titanium dioxide Perlite, expanded		1317-65-3 13463-67-7 93763-70-3	
	ethylene glycol Distillates (petrolet Quartz (SiO2)	um), solvent-dewaxed	107-21-1 heavy paraffinic 64742-65-0 14808-60-7	

California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer, and

ethylene glycol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All chemical substances in this product are either listed as

active on the TSCA Inventory or are in compliance with a

TSCA Inventory exemption.

DSL : This product contains one or more components not listed on

the Canadian DSL or NDSL. All other components are on the

Canadian DSL.


SECTION 16. OTHER INFORMATION

Further information

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/15/2020

 2.0
 06/18/2021
 000000261440
 Date of first issue: 10/15/2020

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1910.1000

29 CFR 1910.1001-1050 : OSHA - Specifically Regulated Substances (29 CFR

1910.1001-1050)

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens
OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

29 CFR 1910.1000 (Table Z- : Short Term Exposure Limit (STEL):

1-A) / STEL value

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

1-A) / TWA value

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

29 CFR 1910.1001-1050 / : OSHA Action level:

OSHA Action level

29 CFR 1910.1001-1050 / : Time Weighted Average (TWA):

TWA value

ACGIH / TWA : 8-hour, time-weighted average

ACGIH / STEL : Short-term exposure limit

ACGIHTLV / STEL value : Short Term Exposure Limit (STEL): ACGIHTLV / TWA value : Time Weighted Average (TWA):

NIOSH / Ceil_Time : Ceiling Limit Value and Time Period (if specified):



Version Revision Date: SDS Number: Date of last issue: 10/15/2020 2.0 06/18/2021 000000261440 Date of first issue: 10/15/2020

NIOSH / REL value : Recommended exposure limit (REL): NIOSH / STEL value : Short Term Exposure Limit (STEL):

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

NIOSH REL / C : Ceiling value not be exceeded at any time.

OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA P0 / TWA : 8-hour time weighted average
OSHA P0 / STEL : Short-term exposure limit

OSHA P0 / C : Ceiling limit

OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System: IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

Revision Date : 06/18/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific



MasterProtect EL 750 FN Ser U

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/15/2020

 2.0
 06/18/2021
 000000261440
 Date of first issue: 10/15/2020

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN