

MasterProtect H 440HZ

Version 2.0 Revision Date: 08/30/2023 SDS Number: 000000259849 Date of last issue: 07/30/2020
Date of first issue: 07/30/2020

SECTION 1. IDENTIFICATION

Product name : MasterProtect H 440HZ
Product code : 000000000051678062 000000000051678062

Manufacturer or supplier's details

Company name of supplier : Master Builders-Construction Systems
US, LLC
Address : 889 VALLEY PARK DR
Shakopee MN 55379-1854
Emergency telephone : ChemTel: +1-813-248-0585
National Emergency Tele-
phone Number : USA: +1-800-255-3924 ChemTel contract no. MIS9240420

Recommended use of the chemical and restrictions on use

Recommended use : Functional surface coating
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Flammable liquids : Category 2
Skin irritation : Category 2
Eye irritation : Category 2A
Specific target organ toxicity : Category 3 (Central nervous system)
- single exposure
Long-term (chronic) aquatic : Category 2
hazard

GHS label elements

Hazard pictograms : 

Signal Word : Danger
Hazard Statements : H225 Highly flammable liquid and vapor.

MasterProtect H 440HZ

Version 2.0 Revision Date: 08/30/2023 SDS Number: 000000259849 Date of last issue: 07/30/2020
Date of first issue: 07/30/2020

H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements

:

Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing mist or vapors.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P391 Collect spillage.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
P233 Keep container tightly closed.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Mixture

MasterProtect H 440HZ

Version 2.0 Revision Date: 08/30/2023 SDS Number: 000000259849 Date of last issue: 07/30/2020
 Date of first issue: 07/30/2020

Components

Chemical name	CAS-No.	Concentration (% w/w)
propan-2-ol	67-63-0	>= 50 - < 70
triethoxyoctylsilane	2943-75-1	>= 30 - < 50

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.
- If inhaled : If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.
- In case of skin contact : After contact with skin, wash immediately with plenty of water and soap.
Under no circumstances should organic solvent be used.
If irritation develops, seek medical attention.
- In case of eye contact : Remove contact lenses, if present.
Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.
Do NOT induce vomiting.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
Causes serious eye irritation.
May cause drowsiness or dizziness.
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam
Water spray
Dry powder
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : water jet
- Specific hazards during fire fighting : See SDS section 10 - Stability and reactivity.
- Hazardous combustion products : harmful vapours
nitrogen oxides
fumes/smoke
carbon black
carbon oxides
- Further information : The degree of risk is governed by the burning substance and

MasterProtect H 440HZ

Version	Revision Date:	SDS Number:	Date of last issue: 07/30/2020
2.0	08/30/2023	000000259849	Date of first issue: 07/30/2020

the fire conditions.
Containers may rocket or explode in heat of fire.
Keep containers cool by spraying with water if exposed to fire.
Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.
Contaminated extinguishing water must be disposed of in accordance with official regulations.

Special protective equipment : Wear a self-contained breathing apparatus.
for fire-fighters

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Can release flammable vapours.
Avoid all sources of ignition: heat, sparks, open flame.
Use antistatic tools.
Do not breathe vapour/aerosol/spray mists.
Use personal protective clothing.

Environmental precautions : Contain contaminated water/firefighting water.
Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
See user defined text.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Keep away from open flames, hot surfaces and sources of ignition.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).
Substance/product can form explosive mixture with air.
Use only explosion-proof equipment.

Advice on safe handling : Take precautionary measures against static discharges.
Keep away from sources of ignition - No smoking.
Provide good room ventilation even at ground level (vapours are heavier than air).

Conditions for safe storage : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
Keep tightly closed.
Protect from direct sunlight.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of	Control parameters / Permissible	Basis
------------	---------	------------------------	----------------------------------	-------

MasterProtect H 440HZ

Version 2.0 Revision Date: 08/30/2023 SDS Number: 000000259849 Date of last issue: 07/30/2020
 Date of first issue: 07/30/2020

		exposure)	concentration	
propan-2-ol	67-63-0	TWA	200 ppm	ACGIH
		STEL	400 ppm	ACGIH
		TWA	400 ppm 980 mg/m ³	NIOSH REL
		ST	500 ppm 1,225 mg/m ³	NIOSH REL
		TWA	400 ppm 980 mg/m ³	OSHA Z-1
		TWA	400 ppm 980 mg/m ³	OSHA P0
		STEL	500 ppm 1,225 mg/m ³	OSHA P0

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits may be exceeded.
 Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Body protection must be chosen based on level of activity and exposure.

Protective measures : Do not inhale gases/vapours/aerosols.
 Avoid contact with the skin, eyes and clothing.
 Avoid exposure - obtain special instructions before use.
 Handle in accordance with good building materials hygiene and safety practice.
 Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.
 Hands and/or face should be washed before breaks and at the end of the shift.
 At the end of the shift the skin should be cleaned and skin-care agents applied.
 Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.
 Gloves must be inspected regularly and prior to each use.
 Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

MasterProtect H 440HZ

Version 2.0 Revision Date: 08/30/2023 SDS Number: 000000259849 Date of last issue: 07/30/2020
Date of first issue: 07/30/2020

Color : clear

Odor : alcohol-like

Odor Threshold : not determined

pH : Not applicable

Melting point : No data available

Boiling point : 180 °F / 82 °C

Flash point : 54 °F / 12 °C

Evaporation rate : No data available

Flammability (liquids) : Highly flammable liquid and vapor.

Upper explosion limit / Upper flammability limit : 12.0 %(V)

Lower explosion limit / Lower flammability limit : 2.5 %(V)

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : No data available

Density : approx. 1.0 g/cm³ (68 °F / 20 °C)

Bulk density : Not applicable

Solubility(ies)
Water solubility : partly soluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : not applicable for mixtures

Autoignition temperature : 750 °F / 399 °C

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity
Viscosity, dynamic : No data available

MasterProtect H 440HZ

Version	Revision Date:	SDS Number:	Date of last issue: 07/30/2020
2.0	08/30/2023	000000259849	Date of first issue: 07/30/2020

Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	Based on its structural properties the product is not classified as oxidizing.
Sublimation point	:	No data available
Molecular weight	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No hazardous reactions if stored and handled as prescribed/indicated.
Chemical stability	:	The product is stable if stored and handled as prescribed/indicated.
Possibility of hazardous reactions	:	Vapors may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks. Electrostatic discharge
Incompatible materials	:	Strong acids Strong bases Strong oxidizing agents Strong reducing agents
Hazardous decomposition products	:	No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

MasterProtect H 440HZ

Version	Revision Date:	SDS Number:	Date of last issue: 07/30/2020
2.0	08/30/2023	000000259849	Date of first issue: 07/30/2020

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

MasterProtect H 440HZ

Version Revision Date: SDS Number: Date of last issue: 07/30/2020
2.0 08/30/2023 000000259849 Date of first issue: 07/30/2020

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

- Waste from residues : Dispose of in accordance with national, state and local regulations.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Do not discharge into drains/surface waters/groundwater.
- Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.
-

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

- UN number : UN 1219
Proper shipping name : ISOPROPANOL
Class : 3
Packing group : II
Labels : 3

IATA-DGR

- UN/ID No. : UN 1219
Proper shipping name : Isopropanol
Class : 3
Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

- UN number : UN 1219
Proper shipping name : ISOPROPANOL
- Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-D
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

- UN/ID/NA number : UN 1219
Proper shipping name : Isopropanol
-

MasterProtect H 440HZ

Version 2.0 Revision Date: 08/30/2023 SDS Number: 000000259849 Date of last issue: 07/30/2020
 Date of first issue: 07/30/2020

Class : 3
 Packing group : II
 Labels : FLAMMABLE LIQUID
 ERG Code : 129
 Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
propan-2-ol	67-63-0	100	193

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

propan-2-ol 67-63-0 >= 50 - < 70 %

US State Regulations

Pennsylvania Right To Know

propan-2-ol	67-63-0
triethoxyoctylsilane	2943-75-1

New Jersey Right To Know

propan-2-ol	67-63-0
-------------	---------

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL


SECTION 16. OTHER INFORMATION

Further information

MasterProtect H 440HZ

Version 2.0 Revision Date: 08/30/2023 SDS Number: 000000259849 Date of last issue: 07/30/2020
 Date of first issue: 07/30/2020

NFPA 704:



HMIS® IV:

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / STEL	:	Short-term exposure limit
OSHA Z-1 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International

MasterProtect H 440HZ

Version	Revision Date:	SDS Number:	Date of last issue: 07/30/2020
2.0	08/30/2023	000000259849	Date of first issue: 07/30/2020

Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 08/30/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN