

## MasterProtect HB 200 neutral

Version 1.0      Revision Date: 08/20/2020      SDS Number: 000000261293      Date of last issue: -  
Date of first issue: 08/20/2020

---

**SECTION 1. IDENTIFICATION**

Product name : MasterProtect HB 200 neutral  
Product code : 000000000051713731 000000000051713731

**Manufacturer or supplier's details**

Company name of supplier : Master Builders-Construction Systems  
US, LLC  
Address : 23700 CHAGRIN BLVD  
Beachwood OH 44122  
Emergency telephone : ChemTel: +1-813-248-0585

**Recommended use of the chemical and restrictions on use**

Recommended use : Product for construction chemicals  
Restrictions on use : Reserved for industrial and professional use.

---


**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200**

Specific target organ toxicity : 2 (Kidney)  
- repeated exposure (Oral)

Carcinogenicity (Inhalation) : 1A

Short-term (acute) aquatic hazard : 3

**GHS label elements**

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H350 May cause cancer.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H402 Harmful to aquatic life.

Precautionary Statements : **Prevention:**  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read

## MasterProtect HB 200 neutral

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/20/2020	000000261293	Date of first issue: 08/20/2020

and understood.  
P260 Do not breathe dust or mist.  
P273 Avoid release to the environment.

**Response:**

P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.  
P314 Get medical advice/ attention if you feel unwell.

**Storage:**

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/container to appropriate hazardous waste collection point.

**Other hazards**

No data available.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS****Components**

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	>= 15 - < 50
ethyleneglycol	107-21-1	>= 1 - < 3
Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol	25265-77-4	>= 0 - < 3
Mica-group minerals	12001-26-2	>= 1 - < 3
Quartz (SiO <sub>2</sub> )	14808-60-7	>= 0.1 - < 1
Poly(oxy-1,2-ethanediyl), .alpha.-[(1,1,3,3-tetramethylbutyl)phenyl]-.omega.-hydroxy-	9036-19-5	>= 0.1 - < 0.2
diuron	330-54-1	>= 0 - < 0.2
3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate	55406-53-6	>= 0 - < 0.1

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Show this material safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : After contact with skin, wash immediately with plenty of water and soap.  
Under no circumstances should organic solvent be used.  
If irritation develops, seek medical attention.
- In case of eye contact : Flush eyes with water as a precaution.

## MasterProtect HB 200 neutral

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/20/2020	000000261293	Date of first issue: 08/20/2020

---

- Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Induce vomiting immediately and call a physician.  
Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : May cause cancer.  
May cause damage to organs through prolonged or repeated exposure.
- Notes to physician : Treat symptomatically.

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Water spray  
Foam  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

## MasterProtect HB 200 neutral

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/20/2020	000000261293	Date of first issue: 08/20/2020

## SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapors/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.  
Protect from direct sunlight.
- Materials to avoid : No applicable information available.
- Further information on storage stability : No data available

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethyleneglycol	107-21-1	TWA value (Vapor fraction)	25 ppm	ACGIHTLV
		STEL value (Vapor fraction)	50 ppm	ACGIHTLV
		STEL value (Aerosol, inhalable.)	10 mg/m3	ACGIHTLV
		TWA (Vapor)	25 ppm	ACGIH
		STEL (Vapor)	50 ppm	ACGIH
		STEL (Inhalable fraction,	10 mg/m3	ACGIH

## MasterProtect HB 200 neutral

Version 1.0      Revision Date: 08/20/2020      SDS Number: 000000261293      Date of last issue: -  
 Date of first issue: 08/20/2020

		Aerosol only)		
		C	50 ppm 125 mg/m <sup>3</sup>	OSHA P0
diuron	330-54-1	TWA value	10 mg/m <sup>3</sup>	ACGIHTLV
		REL value	10 mg/m <sup>3</sup>	NIOSH
		TWA value	10 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		TWA	10 mg/m <sup>3</sup>	ACGIH
		TWA	10 mg/m <sup>3</sup>	NIOSH REL
		TWA	10 mg/m <sup>3</sup>	OSHA P0
Limestone	1317-65-3	REL value (Respirable)	5 mg/m <sup>3</sup>	NIOSH
		REL value (Total)	10 mg/m <sup>3</sup>	NIOSH
		PEL (Respirable fraction)	5 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respirable fraction)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Total dust)	15 mg/m <sup>3</sup>	OSHA P0
		TWA (respirable dust fraction)	5 mg/m <sup>3</sup>	OSHA P0
		TWA (Respirable)	5 mg/m <sup>3</sup> (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m <sup>3</sup> (Calcium carbonate)	NIOSH REL
Mica-group minerals	12001-26-2	TWA value (Respirable fraction)	3 mg/m <sup>3</sup>	ACGIHTLV
		REL value (Respirable)	3 mg/m <sup>3</sup>	NIOSH
		TWA value (Respirable dust)	3 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		TWA value	20 millions of particles per cubic foot of air	29 CFR 1910.1000 (Table Z-3)
		TWA (Res-	3 mg/m <sup>3</sup>	ACGIH

## MasterProtect HB 200 neutral

Version 1.0      Revision Date: 08/20/2020      SDS Number: 000000261293      Date of last issue: -  
 Date of first issue: 08/20/2020

		pirable particulate matter)		
		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	3 mg/m <sup>3</sup>	NIOSH REL
		TWA (respirable dust fraction)	3 mg/m <sup>3</sup>	OSHA P0
Quartz (SiO <sub>2</sub> )	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m <sup>3</sup>	ACGIHTLV
		TWA value	0.05 mg/m <sup>3</sup> (Respirable dust)	29 CFR 1910.1001-1050
		OSHA Action level	0.025 mg/m <sup>3</sup> (Respirable dust)	29 CFR 1910.1001-1050
		REL value (Respirable dust)	0.05 mg/m <sup>3</sup>	NIOSH
		TWA (Respirable dust)	0.05 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respirable)	10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO <sub>2</sub> +5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m <sup>3</sup>	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH
		PEL (respirable)	0.05 mg/m <sup>3</sup>	OSHA CARC
		TWA (Respirable dust)	0.05 mg/m <sup>3</sup> (Silica)	NIOSH REL

**Engineering measures** : No applicable information available.

**Personal protective equipment**

Respiratory protection : When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles

## MasterProtect HB 200 neutral

Version 1.0      Revision Date: 08/20/2020      SDS Number: 000000261293      Date of last issue: -  
Date of first issue: 08/20/2020

---

- Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Protective measures : Do not inhale gases/vapours/aerosols.  
Avoid contact with the skin, eyes and clothing.  
Avoid exposure - obtain special instructions before use.  
Handle in accordance with good building materials hygiene and safety practice.  
Wearing of closed work clothing is recommended.
- Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.
- 

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : liquid
- Color : various colours
- Odor : sweetish, slight odour
- Odor Threshold : No data available
- pH : neutral to slightly alkaline
- Melting point : No applicable information available.
- Boiling point : 379.00 - 401.00 °F / 192.78 - 205.00 °C
- Flash point : 200.01 °F / 93.34 °C
- Evaporation rate : No applicable information available.
- Flammability (solid, gas) : not highly flammable  
Method: derived from flash point
- Upper explosion limit / Upper flammability limit : 15.3 %(V)
- Lower explosion limit / Lower flammability limit : 3.2 %(V)
- Vapor pressure : No applicable information available.
- Relative vapor density : Heavier than air.
- Relative density : No applicable information available.
-

## MasterProtect HB 200 neutral

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/20/2020	000000261293	Date of first issue: 08/20/2020

---

Density : 1.35 - 1.47 g/cm<sup>3</sup> (68 °F / 20 °C)

Solubility(ies)  
Water solubility : partly soluble

Solubility in other solvents : No applicable information available.

Partition coefficient: n-octanol/water : No data available.

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity  
Viscosity, dynamic : No applicable information available.

Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive  
Not explosive

Oxidizing properties : Based on its structural properties the product is not classified as oxidizing.

Sublimation point : No applicable information available.

Molecular weight : No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids  
Strong bases  
Strong oxidizing agents  
Strong reducing agents

Hazardous decomposition products : irritant gases/vapours  
carbon oxides



## MasterProtect HB 200 neutral

Version            Revision Date:            SDS Number:            Date of last issue: -  
1.0                08/20/2020                000000261293            Date of first issue: 08/20/2020

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified based on available information.

**Product:**

Acute oral toxicity                                :    Remarks: No applicable information available.

Acute inhalation toxicity                        :    Remarks: No applicable information available.

Acute dermal toxicity                             :    Remarks: No applicable information available.

**Skin corrosion/irritation**

Not classified based on available information.

**Serious eye damage/eye irritation**

Not classified based on available information.

**Respiratory or skin sensitization****Skin sensitization**

Not classified based on available information.

**Respiratory sensitization**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

May cause cancer.

**Reproductive toxicity**

Not classified based on available information.

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

**Aspiration toxicity**

Not classified based on available information.

**Product:**

No aspiration hazard expected.

**Further information****Product:**

Remarks    :    No data available

## MasterProtect HB 200 neutral

Version 1.0      Revision Date: 08/20/2020      SDS Number: 000000261293      Date of last issue: -  
Date of first issue: 08/20/2020

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability****Components:****Poly(oxy-1,2-ethanediyl), .alpha.-[(1,1,3,3-tetramethylbutyl)phenyl]- .omega.-hydroxy-:**

Biodegradability : aerobic  
Inoculum: activated sludge, domestic, non-adapted  
Result: Readily biodegradable.  
Biodegradation: 90 %  
Exposure time: 28 d  
Method: Modified OECD-Screening-Test.

**Bioaccumulative potential****Components:****ethyleneglycol:**

Partition coefficient: n-octanol/water : log Pow: approx. -1.36 (73 °F / 23 °C)  
Method: Calculation Hansch/Leo  
GLP: no data  
Remarks: Information taken from reference works and the literature.

**Isobutyric acid, monoester with 2,2,4-trimethylpentane-1,3-diol:**

Partition coefficient: n-octanol/water : log Pow: 3.2 (77 °F / 25 °C)  
pH: 7  
Method: Partition coefficient (n-octanol/water), HPLC method.  
GLP: no

**Quartz (SiO<sub>2</sub>):**

Partition coefficient: n-octanol/water : Remarks: not applicable

**Poly(oxy-1,2-ethanediyl), .alpha.-[(1,1,3,3-tetramethylbutyl)phenyl]- .omega.-hydroxy-:**

Bioaccumulation : Remarks: Accumulation in organisms is not to be expected.

**3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate:**

Partition coefficient: n-octanol/water : log Pow: 2.81 (77 °F / 25 °C)  
Method: Partition coefficient (n-octanol/water), Shake-flask method  
GLP: yes

**Mobility in soil**

No data available

## MasterProtect HB 200 neutral

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/20/2020	000000261293	Date of first issue: 08/20/2020

---

**Other adverse effects****Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life.

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with national, state and local regulations. Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****49 CFR**

Not regulated as a dangerous good

**SECTION 15. REGULATORY INFORMATION**

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

ethyleneglycol	107-21-1
----------------	----------

**US State Regulations****Pennsylvania Right To Know**

ethyleneglycol	107-21-1
Limestone	1317-65-3

---

**MasterProtect HB 200 neutral**

Version 1.0	Revision Date: 08/20/2020	SDS Number: 000000261293	Date of last issue: - Date of first issue: 08/20/2020
----------------	------------------------------	-----------------------------	--

Mica-group minerals 12001-26-2

**New Jersey Right To Know**

ethyleneglycol	107-21-1
Limestone	1317-65-3
Mica-group minerals	12001-26-2
Quartz (SiO2)	14808-60-7
Quartz (SiO2)	14808-60-7
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5

**California Prop. 65**

WARNING: This product can expose you to chemicals including diuron, which is/are known to the State of California to cause cancer, and ethyleneglycol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).


**The ingredients of this product are reported in the following inventories:**

TSCA : On the inventory, or in compliance with the inventory

**SECTION 16. OTHER INFORMATION**

**Further information**

**NFPA 704:**



**HMIS® IV:**

<b>HEALTH</b>		
<b>FLAMMABILITY</b>		
<b>PHYSICAL HAZARD</b>		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

**Full text of other abbreviations**

- 29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
- 29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
- 29 CFR 1910.1000 (Table Z-3) : OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000
- 29 CFR 1910.1001-1050 : OSHA - Specifically Regulated Substances (29 CFR

## MasterProtect HB 200 neutral

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/20/2020	000000261293	Date of first issue: 08/20/2020

	1910.1001-1050)
ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV	: American Conference of Governmental Industrial Hygienists - threshold limit values (US)
NIOSH	: NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA CARC	: OSHA Specifically Regulated Chemicals/Carcinogens
OSHA P0	: USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	: USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
29 CFR 1910.1000 (Table Z-1-A) / TWA value	: Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-1) / PEL	: Permissible exposure limit
29 CFR 1910.1000 (Table Z-3) / TWA value	: Time Weighted Average (TWA):
29 CFR 1910.1001-1050 / OSHA Action level	: OSHA Action level:
29 CFR 1910.1001-1050 / TWA value	: Time Weighted Average (TWA):
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
ACGIHTLV / STEL value	: Short Term Exposure Limit (STEL):
ACGIHTLV / TWA value	: Time Weighted Average (TWA):
NIOSH / REL value	: Recommended exposure limit (REL):
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA CARC / PEL	: Permissible exposure limit (PEL)
OSHA P0 / TWA	: 8-hour time weighted average
OSHA P0 / C	: Ceiling limit
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-3 / TWA	: 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC

## MasterProtect HB 200 neutral

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	08/20/2020	000000261293	Date of first issue: 08/20/2020

---

- No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 08/20/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN