

## MasterProtect HB 400 CS Med TB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/15/2020

 2.0
 09/03/2021
 000000261305
 Date of first issue: 10/15/2020

**SECTION 1. IDENTIFICATION** 

Product name : MasterProtect HB 400 CS Med TB

Product code : 00000000051715056 00000000051715056

Manufacturer or supplier's details

Company name of supplier : Master Builders-Construction Systems

US, LLC

Address : 23700 CHAGRIN BLVD

Beachwood OH 44122

Emergency telephone : ChemTel: +1-813-248-0585

National Emergency Tele-

phone Number

USA: +1-800-255-3924 ChemTel contract no. MIS9240420

Recommended use of the chemical and restrictions on use

Recommended use : Waterproof coating

Restrictions on use : Reserved for industrial and professional use.

## **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 1 (Lungs)

Specific target organ toxicity

- repeated exposure

Category 2 (Kidney)

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 2 (Kidney, Immune system)

Short-term (acute) aquatic

hazard

Category 3

Long-term (chronic) aquatic

hazard

Category 3

**GHS label elements** 

Version Revision Date: SDS Number: Date of last issue: 10/15/2020 2.0 09/03/2021 000000261305 Date of first issue: 10/15/2020

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H350 May cause cancer by inhalation.

H372 Causes damage to organs (Lungs) through prolonged or

repeated exposure if inhaled.

H373 May cause damage to organs (Kidney) through prolonged

or repeated exposure.

H373 May cause damage to organs (Kidney, Immune system)

through prolonged or repeated exposure if inhaled.

H402 Harmful to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary Statements** 

### Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P260 Do not breathe mist or vapors. P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

### Response:

P308 + P313 IF exposed or concerned: Get medical advice/

attention.

### Storage:

P405 Store locked up.

### Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

#### Other hazards

None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : Aqueous solution

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	>= 15 - < 50
crystalline silica	14808-60-7	>= 15 - < 20
Titanium dioxide	13463-67-7	>= 3 - < 10
Propanoic acid, 2-methyl-, monoester	25265-77-4	>= 0 - < 3
with 2,2,4-trimethyl-1,3- pentanediol		



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/15/2020

 2.0
 09/03/2021
 000000261305
 Date of first issue: 10/15/2020

ethylene glycol	107-21-1	>= 0.3 - < 3
Isooctylphenol ethoxylate	9036-19-5	>= 0 - < 0.2
diuron	330-54-1	>= 0 - < 0.1
3-iodo-2-propynyl butylcarbamate	55406-53-6	>= 0 - < 0.1

#### **SECTION 4. FIRST AID MEASURES**

General advice : First aid personnel should pay attention to their own safety.

Immediately remove contaminated clothing.

If inhaled : If difficulties occur after vapour/aerosol has been inhaled,

remove to fresh air and seek medical attention.

In case of skin contact : After contact with skin, wash immediately with plenty of water

and soap.

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

In case of eye contact : Hold eyes open and rinse slowly and gently with water for 15

to 20 minutes. Remove contact lenses, if present, after first 5

minutes, then continue rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention.

Do NOT induce vomiting.

Most important symptoms

and effects, both acute and

delayed

May cause cancer by inhalation.

Causes damage to organs through prolonged or repeated

exposure if inhaled.

May cause damage to organs through prolonged or repeated

exposure.

Prolonged or repeated inhalation of respirable crystalline silica

(quartz) may result in silicosis.

Notes to physician : Treat symptomatically.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Foam

Water spray Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

water jet

Specific hazards during fire

fighting

See SDS section 10 - Stability and reactivity.

Hazardous combustion prod-

ucts

harmful vapours nitrogen oxides fumes/smoke

Version **Revision Date:** SDS Number: Date of last issue: 10/15/2020 09/03/2021 000000261305 Date of first issue: 10/15/2020 2.0

> carbon black carbon oxides

Further information The degree of risk is governed by the burning substance and

the fire conditions.

If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not

allow to reach sewage or effluent systems.

Contaminated extinguishing water must be disposed of in

accordance with official regulations.

for fire-fighters

Special protective equipment : Wear a self-contained breathing apparatus.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec- :

tive equipment and emergency procedures

Do not breathe vapour/aerosol/spray mists.

Wear eye/face protection.

If exposed to high vapour concentration, leave area immedi-

ately.

Use personal protective clothing.

Handle in accordance with good building materials hygiene

and safety practice.

**Environmental precautions** Contain contaminated water/firefighting water.

Do not discharge into drains/surface waters/groundwater.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling Avoid aerosol formation.

Avoid inhalation of mists/vapours.

Avoid skin contact. Avoid contact with eyes.

Conditions for safe storage Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Keep only in the original container in a cool, dry, well-

ventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.



# MasterProtect HB 400 CS Med TB

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/15/2020

 2.0
 09/03/2021
 000000261305
 Date of first issue: 10/15/2020

Further information on storage stability

PROTECT FROM FREEZING DURING THE COLD-SEASON

(BELOW 40°F / 5°C).

## **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethylene glycol	107-21-1	TWA (Vapor)	25 ppm	ACGIH
		STEL (Va- por)	50 ppm	ACGIH
		STEL (Inhalable fraction, Aerosol only)	10 mg/m3	ACGIH
		С	50 ppm 125 mg/m3	OSHA P0
diuron	330-54-1	TWA value	10 mg/m3	ACGIHTLV
		REL value	10 mg/m3	NIOSH
		TWA value	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	10 mg/m3	ACGIH
		TWA	10 mg/m3	NIOSH REL
		TWA	10 mg/m3	OSHA P0
Limestone	1317-65-3	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium car- bonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH REL
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
Quartz (SiO2)	14808-60-7	TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/15/2020

 2.0
 09/03/2021
 000000261305
 Date of first issue: 10/15/2020

TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
PEL (respir- able)	0.05 mg/m3	OSHA CARC
TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL

**Engineering measures** : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits

may be exceeded.

Use NIOSH approved respiratory protection.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's

directions for use should be observed because of great di-

versity of types.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Impermeable protective clothing

Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective

boots, chemical-protection suit.

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.

Hands and/or face should be washed before breaks and at

the end of the shift.

At the end of the shift the skin should be cleaned and skin-

care agents applied.

Remove contaminated clothing immediately and clean before

re-use or dispose it if necessary.

Gloves must be inspected regularly and prior to each use.

Replace if necessary (e.g. pinhole leaks).

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES** 

Appearance : liquid



## MasterProtect HB 400 CS Med TB

Version Revision Date: SDS Number: Date of last issue: 10/15/2020 2.0 09/03/2021 000000261305 Date of first issue: 10/15/2020

Color : pigmented

Odor : sweetish, slight odour

Odor Threshold : not determined

pH : 9.5 - 10

Melting point : No data available

Boiling point : 379 - 401 °F / 193 - 205 °C

Flash point :  $> 199 \,^{\circ}\text{F} / > 93 \,^{\circ}\text{C}$ 

Evaporation rate : No data available

Flammability (liquids) : not highly flammable

Method: derived from flash point

Upper explosion limit / Upper

flammability limit

15.3 %(V)

Lower explosion limit / Lower

flammability limit

3.2 %(V)

Vapor pressure : No data available

Relative vapor density : Heavier than air.

Relative density : 1.57 - 1.70

Density : 1.57 - 1.70 g/cm3 (68 °F / 20 °C)

Bulk density : Not applicable

Solubility(ies)

Water solubility : partly soluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

not applicable for mixtures

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No data available



## MasterProtect HB 400 CS Med TB

Version Revision Date: SDS Number: Date of last issue: 10/15/2020 2.0 09/03/2021 000000261305 Date of first issue: 10/15/2020

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : Based on its structural properties the product is not classified

as oxidizing.

Sublimation point : No data available

Molecular weight : No data available

**SECTION 10. STABILITY AND REACTIVITY** 

Reactivity : No hazardous reactions if stored and handled as pre-

scribed/indicated.

Chemical stability : The product is stable if stored and handled as pre-

scribed/indicated.

Possibility of hazardous reac-

tions

The product is stable if stored and handled as pre-

scribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong oxidizing agents

Strong bases Strong acids

Hazardous decomposition

products

irritant gases/vapours

carbon oxides

## **SECTION 11. TOXICOLOGICAL INFORMATION**

## **Acute toxicity**

Not classified based on available information.

#### Skin corrosion/irritation

Not classified based on available information.

### Serious eye damage/eye irritation

Not classified based on available information.

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

### Respiratory sensitization

Not classified based on available information.

## Germ cell mutagenicity

Not classified based on available information.



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/15/2020

 2.0
 09/03/2021
 000000261305
 Date of first issue: 10/15/2020

Carcinogenicity

May cause cancer by inhalation.

IARC Group 1: Carcinogenic to humans

crystalline silica 14808-60-7

(Silica dust, crystalline)

Group 2B: Possibly carcinogenic to humans

Titanium dioxide 13463-67-7

OSHA specifically regulated carcinogen

crystalline silica 14808-60-7

(crystalline silica)

NTP Known to be human carcinogen

crystalline silica 14808-60-7

(Silica, Crystalline (Respirable Size))

### Reproductive toxicity

Not classified based on available information.

## STOT-single exposure

Not classified based on available information.

### STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

May cause damage to organs (Kidney) through prolonged or repeated exposure.

May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure if inhaled.

### **Aspiration toxicity**

Not classified based on available information.

### **Further information**

**Product:** 

Remarks : Health injuries are not known or expected under normal use.

The product has not been tested. The statements on toxicology have been derived from the properties of the individual

components.

### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

#### **Product:**

#### **Ecotoxicology Assessment**

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

#### Components:

#### diuron:



## MasterProtect HB 400 CS Med TB

Version **Revision Date:** SDS Number: Date of last issue: 10/15/2020 09/03/2021 000000261305 Date of first issue: 10/15/2020 2.0

M-Factor (Acute aquatic tox-

icity)

M-Factor (Chronic aquatic

toxicity)

10

10

3-iodo-2-propynyl butylcarbamate:

M-Factor (Acute aquatic tox- : 10

icity)

M-Factor (Chronic aquatic

toxicity)

: 1

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

**Product:** 

Additional ecological infor-

mation

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

components.

**SECTION 13. DISPOSAL CONSIDERATIONS** 

**Disposal methods** 

Waste from residues Dispose of in accordance with national, state and local regula-

tions.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging should be emptied as far as possible Contaminated packaging

and disposed of in the same manner as the sub-

stance/product.

**SECTION 14. TRANSPORT INFORMATION** 

International Regulations

**UNRTDG** 

Not regulated as a dangerous good

**IATA-DGR** 

Not regulated as a dangerous good

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/15/2020

 2.0
 09/03/2021
 000000261305
 Date of first issue: 10/15/2020

#### **IMDG-Code**

Not regulated as a dangerous good

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### **Domestic regulation**

#### **49 CFR**

Not regulated as a dangerous good

### Special precautions for user

Not applicable

#### **SECTION 15. REGULATORY INFORMATION**

### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ	Calculated product RQ	
		(lbs)	(lbs)	
carbendazim	10605-21-7	10	27777	

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

ethylene glycol 107-21-1 >= 1 - < 5 %

## **US State Regulations**

### Pennsylvania Right To Know

Limestone	1317-65-3
crystalline silica	14808-60-7
Titanium dioxide	13463-67-7
Wollastonite (Ca(SiO3))	13983-17-0
ethylene glycol	107-21-1
diuron	330-54-1
1,4-dioxane	123-91-1

#### **New Jersey Right To Know**

Limestone	1317-65-3
crystalline silica	14808-60-7
Titanium dioxide	13463-67-7
ethylene glycol	107-21-1
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0

### California Prop. 65

WARNING: This product can expose you to chemicals including crystalline silica, which is/are known to the State of California to cause cancer, and

ethylene glycol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

### The ingredients of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this product are either listed as

active on the TSCA Inventory or are in compliance with a



 Version
 Revision Date:
 SDS Number:
 Date of last issue: 10/15/2020


 2.0
 09/03/2021
 000000261305
 Date of first issue: 10/15/2020

TSCA Inventory exemption.

#### **SECTION 16. OTHER INFORMATION**


#### **Further information**

#### NFPA 704:



Special hazard

#### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1-A)

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV : American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens
OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

29 CFR 1910.1000 (Table Z- :

Time Weighted Average (TWA):

1-A) / TWA value

ACGIH / TWA : 8-hour, time-weighted average
ACGIH / STEL : Short-term exposure limit
ACGIHTLV / TWA value : Time Weighted Average (TWA):
NIOSH / REL value : Recommended exposure limit (REL):

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA P0 / TWA : 8-hour time weighted average

OSHA P0 / C : Ceiling limit

OSHA Z-1 / TWA : 8-hour time weighted average



Version Revision Date: SDS Number: Date of last issue: 10/15/2020 2.0 09/03/2021 000000261305 Date of first issue: 10/15/2020

OSHA Z-3 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 09/03/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN