

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

MBCC GROUP

MasterSeal HLM 5000 LOW VOC

Version 3.0 Revision Date: 10/18/2023 SDS Number: 960000012261 Date of last issue: 10/02/2023
Date of first issue: 10/26/2021

SECTION 1. IDENTIFICATION

Product name : MasterSeal HLM 5000 LOW VOC
Product code : 000000000055590866 000000000055590866

Manufacturer or supplier's details

Company name of supplier : Master Builders-Construction Systems
US, LLC
Address : 889 VALLEY PARK DR
Shakopee MN 55379-1854
Emergency telephone : ChemTel: +1-813-248-0585
National Emergency Telephone Number : USA: +1-800-255-3924 ChemTel contract no. MIS9240420

Recommended use of the chemical and restrictions on use

Recommended use : Adhesives and/or sealants
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 3
Skin irritation : Category 2
Serious eye damage : Category 1
Reproductive toxicity : Category 1B
Specific target organ toxicity - repeated exposure (Inhalation) : Category 1 (Central nervous system)
Short-term (acute) aquatic hazard : Category 3

GHS label elements

Hazard pictograms : 

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

MBCC GROUP

MasterSeal HLM 5000 LOW VOC

Version 3.0 Revision Date: 10/18/2023 SDS Number: 960000012261 Date of last issue: 10/02/2023
Date of first issue: 10/26/2021

Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H360 May damage fertility or the unborn child.
H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.
H402 Harmful to aquatic life.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

MBCC GROUP

MasterSeal HLM 5000 LOW VOC

Version 3.0 Revision Date: 10/18/2023 SDS Number: 960000012261 Date of last issue: 10/02/2023
Date of first issue: 10/26/2021

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : polyurethane

Components

Chemical name	CAS-No.	Concentration (% w/w)
talc	14807-96-6	$\geq 20 - < 30$
Asphalt	8052-42-4	$\geq 5 - < 10$
4-Chloro- α,α,α -trifluorotoluene	98-56-6	$\geq 5 - < 10$
calcium oxide	1305-78-8	$\geq 5 - < 10$
Stoddard solvent	8052-41-3	$\geq 5 - < 10$
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	$\geq 1 - < 5$
dibutyltin dilaurate	77-58-7	$\geq 0.1 - < 1$
Carbon black	1333-86-4	$\geq 0.1 - < 1$

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

If inhaled : Keep patient calm, remove to fresh air. If symptoms persist, seek medical advice.

In case of skin contact : After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

In case of eye contact : Wash affected eyes for at least 15 minutes under running water with eyelids held open. Remove contact lenses, if present. If eye irritation persists, consult a specialist.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

Most important symptoms and effects, both acute and delayed : Causes skin irritation. Causes serious eye damage. May damage fertility or the unborn child.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

MBCC GROUP

MasterSeal HLM 5000 LOW VOC

Version	Revision Date:	SDS Number:	Date of last issue: 10/02/2023
3.0	10/18/2023	960000012261	Date of first issue: 10/26/2021

Causes damage to organs through prolonged or repeated exposure if inhaled.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Dry powder
Alcohol-resistant foam

Unsuitable extinguishing media : water jet

Specific hazards during fire fighting : Evolution of fumes/fog.

Hazardous combustion products : harmful vapours

Further information : The degree of risk is governed by the burning substance and the fire conditions.
Containers may rocket or explode in heat of fire.
Keep containers cool by spraying with water if exposed to fire.
Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.
Contaminated extinguishing water must be disposed of in accordance with official regulations.

Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Can release flammable vapours.
Wind direction should be noted.
Avoid all sources of ignition: heat, sparks, open flame.
Use antistatic tools.
Breathing protection required.
Use personal protective clothing.

Environmental precautions : Prevent spread over a wide area (e.g. by containment or oil barriers).
Contain contaminated water/firefighting water.
Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up : Pick up with suitable absorbent material.
Dispose of in accordance with national, state and local regulations.
Large spills should be collected mechanically (remove by pumping) for disposal.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

MBCC GROUP

MasterSeal HLM 5000 LOW VOC

Version 3.0 Revision Date: 10/18/2023 SDS Number: 960000012261 Date of last issue: 10/02/2023
Date of first issue: 10/26/2021

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Sources of ignition should be kept well clear.
Take precautionary measures against static discharges.
Substance/product can form explosive mixture with air.
Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.
- Advice on safe handling : Take precautionary measures against static discharges.
Keep away from sources of ignition - No smoking.
Provide good room ventilation even at ground level (vapours are heavier than air).
- Further information on storage conditions : Keep container tightly closed and in a cool place.
- Materials to avoid : Segregate from foods and animal feeds.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
talc	14807-96-6	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (respirable dust fraction)	2 mg/m ³	OSHA P0
		TWA (Respirable)	2 mg/m ³	NIOSH REL
		TWA	0.1 fibres per cubic centimeter	ACGIH
		TWA (Respirable particulate matter)	2 mg/m ³	ACGIH
Asphalt	8052-42-4	TWA (Fume, inhalable fraction)	0.5 mg/m ³ (benzene soluble aerosol)	ACGIH
		C (Fumes)	5 mg/m ³	NIOSH REL
calcium oxide	1305-78-8	TWA	2 mg/m ³	ACGIH
		TWA	2 mg/m ³	NIOSH REL
		TWA	5 mg/m ³	OSHA Z-1
		TWA	5 mg/m ³	OSHA P0
Stoddard solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	350 mg/m ³	NIOSH REL
		C	1,800 mg/m ³	NIOSH REL
		TWA	500 ppm 2,900 mg/m ³	OSHA Z-1

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

MBCC GROUP

MasterSeal HLM 5000 LOW VOC

Version 3.0 Revision Date: 10/18/2023 SDS Number: 960000012261 Date of last issue: 10/02/2023
Date of first issue: 10/26/2021

		TWA	100 ppm 525 mg/m3	OSHA P0
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
dibutyltin dilaurate	77-58-7	TWA	0.1 mg/m3 (Tin)	OSHA Z-1
		TWA	0.1 mg/m3 (Tin)	ACGIH
		STEL	0.2 mg/m3 (Tin)	ACGIH
		TWA	0.1 mg/m3 (Tin)	OSHA P0
		TWA	0.1 mg/m3 (Tin)	NIOSH REL
Carbon black	1333-86-4	TWA (Inhalable particulate matter)	3 mg/m3	ACGIH
		TWA	3.5 mg/m3	NIOSH REL
		TWA	3.5 mg/m3	OSHA Z-1
		TWA	3.5 mg/m3	OSHA P0
		TWA	0.1 mg/m3 (PAHs)	NIOSH REL

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits may be exceeded.
Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Body protection must be chosen based on level of activity and exposure.

Protective measures : Do not inhale dust/fumes/aerosols.
Avoid contact with the skin, eyes and clothing.
Avoid exposure.
Handle in accordance with good building materials hygiene and safety practice.
Wearing of closed work clothing is recommended.

Hygiene measures : No eating, drinking, smoking or tobacco use at the place of work.
Handle in accordance with good industrial hygiene and safety

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

MBCC GROUP

MasterSeal HLM 5000 LOW VOC

Version	Revision Date:	SDS Number:	Date of last issue: 10/02/2023
3.0	10/18/2023	960000012261	Date of first issue: 10/26/2021

practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid, slightly viscous
Color	:	brown-black
Odor	:	slight, aromatic
Odor Threshold	:	not determined
pH	:	Not applicable
Melting point	:	Not applicable
Boiling point/boiling range	:	307 °F / 153 °C
Flash point	:	129 °F / 54 °C
Evaporation rate	:	No data available
Flammability (liquids)	:	Flammable liquid and vapor.
Self-ignition	:	not self-igniting
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	Heavier than air.
Relative density	:	No data available
Density	:	1.28 g/ml
Solubility(ies)		
Water solubility	:	sparingly soluble (59 °F / 15 °C)
Solubility in other solvents	:	No data available
Partition coefficient: n-	:	not applicable for mixtures

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

MBCC GROUP

MasterSeal HLM 5000 LOW VOC

Version	Revision Date:	SDS Number:	Date of last issue: 10/02/2023
3.0	10/18/2023	960000012261	Date of first issue: 10/26/2021

octanol/water

Autoignition temperature : No data available

Decomposition temperature : Vapors may form explosive mixture with air.

No decomposition if stored and handled as prescribed/indicated.

Viscosity

Viscosity, dynamic : 470 poise

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : Not an oxidizer.

Sublimation point : No data available

Molecular weight : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability : The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions : The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid : Avoid all sources of ignition: heat, sparks, open flame.
Avoid electro-static discharge.
Avoid heat.

See SDS section 7 - Handling and storage.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

MBCC GROUP

MasterSeal HLM 5000 LOW VOC

Version 3.0 Revision Date: 10/18/2023 SDS Number: 960000012261 Date of last issue: 10/02/2023
Date of first issue: 10/26/2021

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC	Group 2B: Possibly carcinogenic to humans	
	Asphalt	8052-42-4
	(Bitumens, occupational exposure to straight-run bitumens and their emissions during road paving)	
	Group 2B: Possibly carcinogenic to humans	
	4-Chloro- α,α,α -trifluorotoluene	98-56-6
	Group 2B: Possibly carcinogenic to humans	
	Carbon black	1333-86-4

Reproductive toxicity

May damage fertility or the unborn child.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

MBCC GROUP

MasterSeal HLM 5000 LOW VOC

Version	Revision Date:	SDS Number:	Date of last issue: 10/02/2023
3.0	10/18/2023	960000012261	Date of first issue: 10/26/2021

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Observe national and local legal requirements. Disposal requirements are dependent on the hazard classification and will vary by location and the type of disposal selected. The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous waste. Residues should be disposed of in the same manner as the substance/product.

Contaminated packaging : Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned. Packs that cannot be cleaned should be disposed of in the same manner as the contents.

SECTION 14. TRANSPORT INFORMATION

International Regulations

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

MBCC GROUP

MasterSeal HLM 5000 LOW VOC

Version 3.0 Revision Date: 10/18/2023 SDS Number: 960000012261 Date of last issue: 10/02/2023
Date of first issue: 10/26/2021

UNRTDG

UN number : UN 1866
Proper shipping name : RESIN SOLUTION
Class : 3
Packing group : III
Labels : 3
Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 1866
Proper shipping name : Resin solution
Class : 3
Packing group : III
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 366
Packing instruction (passenger aircraft) : 355

IMDG-Code

UN number : UN 1866
Proper shipping name : RESIN SOLUTION

Class : 3
Packing group : III
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : NA 1993
Proper shipping name : Combustible liquid, n.o.s.

Class : CBL
Packing group : III
Labels : NONE
ERG Code : 128
Marine pollutant : no
Remarks : Above applies only to containers over 119 gallons or 450 liters. Not regulated if shipped in packages less than or equal to 119 gallons (450 liters). If transporting by vessel or aircraft, unless other means of transportation is impracticable, then the product must be shipped as a flammable liquid.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
------------	---------	--------------------	-----------------------------

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

MBCC GROUP

MasterSeal HLM 5000 LOW VOC

Version	Revision Date:	SDS Number:	Date of last issue: 10/02/2023
3.0	10/18/2023	960000012261	Date of first issue: 10/26/2021

Asphalt	8052-42-4	100	1176
---------	-----------	-----	------

US State Regulations

Pennsylvania Right To Know

talc	14807-96-6
Asphalt	8052-42-4
calcium oxide	1305-78-8
Stoddard solvent	8052-41-3
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
toluene-2,6-diisocyanate	91-08-7

New Jersey Right To Know

talc	14807-96-6
Asphalt	8052-42-4
4-Chloro- α,α,α -trifluorotoluene	98-56-6
calcium oxide	1305-78-8
Stoddard solvent	8052-41-3
Carbon black	1333-86-4

California Prop. 65

WARNING: This product can expose you to chemicals including Asphalt, which is/are known to the State of California to cause cancer, and Diisodecyl phthalate, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL

TSCA list

The following substance(s) is/are subject to a Significant New Use Rule:

toluene-2,6-diisocyanate	91-08-7	See 40 CFR § 721.10789; Proposed Rule
--------------------------	---------	---------------------------------------

4-methyl-m-phenylene diisocyanate	584-84-9	See 40 CFR § 721.10789; Proposed Rule
-----------------------------------	----------	---------------------------------------

The following substance(s) is/are subject to TSCA 12(b) export notification requirements:

4-Chloro- α,α,α -trifluorotoluene	98-56-6
--	---------

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

MBCC GROUP

MasterSeal HLM 5000 LOW VOC


Version
3.0

Revision Date:
10/18/2023

SDS Number:
960000012261

Date of last issue: 10/02/2023
Date of first issue: 10/26/2021

NFPA 704:



HMIS® IV:

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard

MBCC GROUP

MasterSeal HLM 5000 LOW VOC

Version	Revision Date:	SDS Number:	Date of last issue: 10/02/2023
3.0	10/18/2023	960000012261	Date of first issue: 10/26/2021

Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 10/18/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN