

**MasterSeal M 200 flash SLP**

Version 1.0      Revision Date: 10/15/2020      SDS Number: 000000261546      Date of last issue: -  
Date of first issue: 10/15/2020

---

**SECTION 1. IDENTIFICATION**

Product name : MasterSeal M 200 flash SLP  
Product code : 000000000055517276 000000000055517276

**Manufacturer or supplier's details**

Company name of supplier : Master Builders-Construction Systems  
US, LLC  
Address : 23700 CHAGRIN BLVD  
Beachwood OH 44122  
Emergency telephone : ChemTel: +1-813-248-0585

**Recommended use of the chemical and restrictions on use**

Recommended use : Product for construction chemicals  
Restrictions on use : Reserved for industrial and professional use.

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200**

FLAMMABLE LIQUIDS : Category 3  
Acute toxicity (Inhalation - vapour) : Category 3  
Respiratory sensitization : Category 1  
Skin sensitization : Category 1  
Carcinogenicity : Category 2  
Reproductive toxicity : Category 1B  
Reproductive toxicity : Category 1B  
Specific target organ toxicity - repeated exposure : Category 1 (Central nervous system)

**GHS label elements**

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapour.

---

## MasterSeal M 200 flash SLP

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/15/2020	000000261546	Date of first issue: 10/15/2020

---

H331 Toxic if inhaled.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer.  
H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.  
H360 May damage fertility or the unborn child.

## Precautionary Statements :

**Prevention:**

P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P260 Do not breathe dust or mist.  
P201 Obtain special instructions before use.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P202 Do not handle until all safety precautions have been read and understood.  
P243 Take action to prevent static discharges.  
P284 In case of inadequate ventilation wear respiratory protection.  
P241 Use explosion-proof [electrical/ ventilating/ lighting/ .?] equipment.  
P264 Wash face, hands and any exposed skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P242 Use only non-sparking tools.  
P240 Ground and bond container and receiving equipment.

**Response:**

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.  
P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.  
P233 Keep container tightly closed.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents/container to appropriate hazardous waste collection point.

## MasterSeal M 200 flash SLP

Version 1.0      Revision Date: 10/15/2020      SDS Number: 000000261546      Date of last issue: -  
 Date of first issue: 10/15/2020

**Other hazards**

CONTAINS ISOCYANATES. INHALATION OF ISOCYANATE MISTS OR VAPORS MAY CAUSE RESPIRATORY IRRITATION, BREATHLESSNESS, CHEST DISCOMFORT AND REDUCED PULMONARY FUNCTION. OVEREXPOSURE WELL ABOVE THE PEL MAY RESULT IN BRONCHITIS, BRONCHIAL SPASMS AND PULMONARY EDEMA. LONG-TERM EXPOSURE TO ISOCYANATES HAS BEEN REPORTED TO CAUSE LUNG DAMAGE, INCLUDING REDUCED LUNG FUNCTION WHICH MAY BE PERMANENT. ACUTE OR CHRONIC OVEREXPOSURE TO ISOCYANATES MAY CAUSE SENSITIZATION IN SOME INDIVIDUALS, RESULTING IN ALLERGIC RESPIRATORY REACTIONS INCLUDING WHEEZING, SHORTNESS OF BREATH AND DIFFICULTY BREATHING. ANIMAL TESTS INDICATE THAT SKIN CONTACT MAY PLAY A ROLE IN CAUSING RESPIRATORY SENSITIZATION.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : No data available.

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Limestone	1317-65-3	>= 10 - < 50
talc	14807-96-6	>= 10 - < 15
Stoddard solvent	8052-41-3	>= 3 - < 5
4-methyl-m-phenylene diisocyanate	584-84-9	>= 3 - < 5
Calcium sulphate	7778-18-9	>= 0 - < 5
Titanium dioxide	13463-67-7	>= 0 - < 3
trimethoxy(3-(oxiranylmethoxy)propyl)silane	2530-83-8	>= 0.3 - < 1
toluene-2,6-diisocyanate	91-08-7	>= 0.3 - < 1
dibutyltin dilaurate	77-58-7	>= 0.1 - < 0.2

**SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.  
 Consult a physician.  
 Show this material safety data sheet to the doctor in attendance.  
 Symptoms of poisoning may appear several hours later.  
 Do not leave the victim unattended.

If inhaled : Remove the affected individual into fresh air and keep the person calm.  
 Assist in breathing if necessary.  
 Immediate medical attention required.

Call a physician or poison control center immediately.  
 If unconscious, place in recovery position and seek medical advice.

In case of skin contact : Wash affected areas thoroughly with soap and water.  
 If irritation develops, seek medical attention.

If skin irritation persists, call a physician.  
 If on skin, rinse well with water.

## MasterSeal M 200 flash SLP

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/15/2020	000000261546	Date of first issue: 10/15/2020

---

- If on clothes, remove clothes.
- In case of eye contact : In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Immediate medical attention required.
- Flush eyes with water as a precaution.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Rinse mouth and then drink 200-300 ml of water. Do NOT induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required.
- Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction. Toxic if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of causing cancer. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.
- Notes to physician : Treat symptomatically.

---

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Water spray  
Foam  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : nitrous gases  
fumes/smoke  
isocyanate  
vapor
- Further information : Keep containers cool by spraying with water if exposed to fire.

## MasterSeal M 200 flash SLP

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/15/2020	000000261546	Date of first issue: 10/15/2020

---

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

Special protective equipment for fire-fighters : Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

Wear self-contained breathing apparatus for firefighting if necessary.

---

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Clear area.  
Ensure adequate ventilation.  
Wear suitable personal protective clothing and equipment.  
Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Dike spillage.

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

---

## SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Product is not explosive.

Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).  
Keep away from open flames, hot surfaces and sources of ignition.

## MasterSeal M 200 flash SLP

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/15/2020	000000261546	Date of first issue: 10/15/2020

- Advice on safe handling : Provide suitable exhaust ventilation at the processing machines.  
Ensure thorough ventilation of stores and work areas.  
Avoid aerosol formation.  
When handling heated product, vapours of the product should be ventilated, and respiratory protection used.  
Wear respiratory protection when spraying.  
Danger of bursting when sealed gastight.  
Protect against moisture.  
If bulging of drum occurs, transfer to well ventilated area, puncture to relieve pressure, open vent and let stand for 48 hours before resealing.
- Avoid formation of aerosol.  
Do not breathe vapors/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Prevent unauthorized access.  
no smoking  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.  
Protect from direct sunlight.
- Materials to avoid : Observe VCI storage rules.
- Further information on storage stability : No data available

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
------------	---------	------------	-----------------	-------

## MasterSeal M 200 flash SLP

Version  
1.0Revision Date:  
10/15/2020SDS Number:  
000000261546Date of last issue: -  
Date of first issue: 10/15/2020

		(Form of exposure)	ters / Permissible concentration	
dibutyltin dilaurate	77-58-7	TWA value	0.1 mg/m <sup>3</sup> (tin (Sn))	ACGIHTLV
		STEL value	0.2 mg/m <sup>3</sup> (tin (Sn))	ACGIHTLV
		REL value	0.1 mg/m <sup>3</sup> (tin (Sn))	NIOSH
		PEL	0.1 mg/m <sup>3</sup> (tin (Sn))	29 CFR 1910.1000 (Table Z-1)
		TWA value	0.1 mg/m <sup>3</sup> (tin (Sn))	29 CFR 1910.1000 (Table Z-1-A)
		TWA	0.1 mg/m <sup>3</sup> (Tin)	OSHA Z-1
		TWA	0.1 mg/m <sup>3</sup> (Tin)	ACGIH
		STEL	0.2 mg/m <sup>3</sup> (Tin)	ACGIH
		TWA	0.1 mg/m <sup>3</sup> (Tin)	OSHA P0
		TWA	0.1 mg/m <sup>3</sup> (Tin)	NIOSH REL
toluene-2,6-diisocyanate	91-08-7	STEL value (Inhalable fraction and vapor)	0.005 ppm	ACGIHTLV
		Skin Designation (Inhalable fraction and vapor)		ACGIHTLV
		TWA value (Inhalable fraction and vapor)	0.001 ppm	ACGIHTLV
		C	0.02 ppm 0.14 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Inhalable fraction and vapor)	0.001 ppm	ACGIH
		STEL (Inhalable fraction and vapor)	0.005 ppm	ACGIH
		TWA	0.005 ppm 0.04 mg/m <sup>3</sup>	OSHA P0
		STEL	0.02 ppm 0.15 mg/m <sup>3</sup>	OSHA P0
4-methyl-m-phenylene diisocyanate	584-84-9	TWA value (Inhalable fraction and vapor)	0.001 ppm	ACGIHTLV
		Skin Designation		ACGIHTLV

## MasterSeal M 200 flash SLP

Version 1.0      Revision Date: 10/15/2020      SDS Number: 000000261546      Date of last issue: -  
 Date of first issue: 10/15/2020

		nation (Inhalable fraction and vapor)		
		STEL value (Inhalable fraction and vapor)	0.005 ppm	ACGIHTLV
		CLV	0.02 ppm 0.14 mg/m3	29 CFR 1910.1000 (Table Z-1)
		C	0.02 ppm 0.14 mg/m3	OSHA Z-1
		TWA (Inhalable fraction and vapor)	0.001 ppm	ACGIH
		STEL (Inhalable fraction and vapor)	0.005 ppm	ACGIH
		TWA	0.005 ppm 0.04 mg/m3	OSHA P0
		STEL	0.02 ppm 0.15 mg/m3	OSHA P0
Limestone	1317-65-3	REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium carbonate)	NIOSH REL



## MasterSeal M 200 flash SLP

Version  
1.0Revision Date:  
10/15/2020SDS Number:  
000000261546Date of last issue: -  
Date of first issue: 10/15/2020

Silicon dioxide	7631-86-9	REL value	6 mg/m <sup>3</sup>	NIOSH
		TWA value	6 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		TWA value	20 millions of particles per cubic foot of air	29 CFR 1910.1000 (Table Z-3)
		TWA value	0.8 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-3)
		TWA (Dust)	20 Million parti- cles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m <sup>3</sup> / %SiO <sub>2</sub> (Silica)	OSHA Z-3
		TWA (Res- pirable dust)	0.05 mg/m <sup>3</sup> (Silica)	NIOSH REL
		TWA	6 mg/m <sup>3</sup> (Silica)	NIOSH REL
Calcium sulphate	7778-18-9	TWA value (Inhalable fraction)	10 mg/m <sup>3</sup>	ACGIHTLV
		REL value (Respirable)	5 mg/m <sup>3</sup>	NIOSH
		REL value (Total)	10 mg/m <sup>3</sup>	NIOSH
		PEL (Respir- able fraction)	5 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Res- pirable)	5 mg/m <sup>3</sup>	NIOSH REL
		TWA (total)	10 mg/m <sup>3</sup>	NIOSH REL
		TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respir- able fraction)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Total dust)	15 mg/m <sup>3</sup>	OSHA P0
		TWA (respir- able dust fraction)	5 mg/m <sup>3</sup>	OSHA P0
		TWA (Inhal- able particu- late matter)	10 mg/m <sup>3</sup> (Calcium)	ACGIH

## MasterSeal M 200 flash SLP

Version 1.0      Revision Date: 10/15/2020      SDS Number: 000000261546      Date of last issue: -  
 Date of first issue: 10/15/2020

Titanium dioxide	13463-67-7	TWA value	10 mg/m3	ACGIHTLV
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
talc	14807-96-6	TWA value (Respirable fraction)	2 mg/m3	ACGIHTLV
		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (respirable dust fraction)	2 mg/m3	OSHA P0
		TWA (Respirable)	2 mg/m3	NIOSH REL
		TWA	0.1 fibres per cubic centimeter	ACGIH
		TWA (Respirable particulate matter)	2 mg/m3	ACGIH
Stoddard solvent	8052-41-3	TWA value	100 ppm	ACGIHTLV
		REL value	350 mg/m3	NIOSH
		Ceil_Time	1,800 mg/m3	NIOSH
		PEL	500 ppm 2,900 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	100 ppm 525 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	100 ppm	ACGIH
		TWA	350 mg/m3	NIOSH REL
		C	1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,900 mg/m3	OSHA Z-1
		TWA	100 ppm 525 mg/m3	OSHA P0

**Engineering measures** : Provide adequate exhaust ventilation to control work place concentrations.

**Personal protective equipment**

Respiratory protection : When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.

## MasterSeal M 200 flash SLP

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/15/2020	000000261546	Date of first issue: 10/15/2020

---

When atmospheric levels may exceed the occupational exposure limit (PEL or TLV) NIOSH-certified air-purifying respirators equipped with an organic vapor sorbent and particulate filter can be used as long as appropriate precautions and change out schedules are in place.

For emergency or non-routine, high exposure situations, including confined space entry, use a NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied-air respirator (SAR) with escape provisions.

## Hand protection

Remarks : Chemical resistant protective gloves should be worn to prevent all skin contact. Suitable materials may include chloroprene rubber (Neoprene) nitrile rubber (Buna N) chlorinated polyethylene polyvinylchloride (Pylox) butyl rubber fluoroelastomer (Viton) depending upon conditions of use. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Tightly fitting safety goggles (chemical goggles).  
Wear face shield if splashing hazard exists.  
Eye wash bottle with pure water  
Tightly fitting safety goggles

Skin and body protection : Cover as much of the exposed skin as possible to prevent all skin contact.  
Suitable materials may include saran-coated material depending upon conditions of use.  
Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Wear protective clothing as necessary to prevent contact.  
Eye wash fountains and safety showers must be easily accessible.  
Observe the appropriate PEL or TLV value.

Hygiene measures : Wash soiled clothing immediately.  
Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.  
Avoid contact with skin, eyes and clothing.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and immediately after handling the product.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

## MasterSeal M 200 flash SLP

Version 1.0      Revision Date: 10/15/2020      SDS Number: 000000261546      Date of last issue: -  
Date of first issue: 10/15/2020

---

Color : off-white

Odor : solvent

Odor Threshold : No data available

pH : neutral to slightly alkaline

Melting point : No applicable information available.

Boiling point : 354 °F / 179 °C  
Method: Estimation

Flash point : 109.99 °F / 43.33 °C  
  
Method: Standard Method of Test for Flash Point by Setaflash  
Closed Tester

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not determined

Upper explosion limit / Upper flammability limit : 7.0 %(V)

Lower explosion limit / Lower flammability limit : 1.0 %(V)

Vapor pressure : No data available

Relative vapor density : Heavier than air.

Relative density : 1.16

Density : 9.6807 lb/USg (68 °F / 20 °C)

Bulk density : not applicable

Solubility(ies)  
Water solubility : slightly soluble

Solubility in other solvents : No applicable information available.

Partition coefficient: n-octanol/water : No data available.

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity

## MasterSeal M 200 flash SLP

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/15/2020	000000261546	Date of first issue: 10/15/2020

---

Viscosity, dynamic	:	No applicable information available.
Explosive properties	:	Not explosive Not explosive
Oxidizing properties	:	Based on its structural properties the product is not classified as oxidizing.
Sublimation point	:	No applicable information available.
Molecular weight	:	No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapors may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Strong acids Strong bases Strong oxidizing agents Strong reducing agents
Hazardous decomposition products	:	No hazardous decomposition products if stored and handled as prescribed/indicated.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Toxic if inhaled.

**Product:**

Acute oral toxicity	:	Remarks: No data available.
Acute inhalation toxicity	:	ATE: 2.15 mg/l Remarks: Determined for vapor
Acute dermal toxicity	:	Remarks: No data available.

**Skin corrosion/irritation**

Not classified based on available information.

**Product:**

Remarks	:	May cause skin irritation and/or dermatitis.
---------	---	--

## MasterSeal M 200 flash SLP

Version 1.0      Revision Date: 10/15/2020      SDS Number: 000000261546      Date of last issue: -  
Date of first issue: 10/15/2020

---

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Remarks : Vapors may cause irritation to the eyes, respiratory system and the skin.

**Respiratory or skin sensitization****Skin sensitization**

May cause an allergic skin reaction.

**Respiratory sensitization**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Product:**

Remarks : Causes sensitization.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Suspected of causing cancer.

**Reproductive toxicity**

May damage fertility or the unborn child.

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

**Aspiration toxicity**

Not classified based on available information.

**Further information****Product:**

Remarks : Solvents may degrease the skin.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential****Components:****talc:**

Partition coefficient: n- : Remarks: not applicable

---

## MasterSeal M 200 flash SLP

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/15/2020	000000261546	Date of first issue: 10/15/2020

---

octanol/water

**Stoddard solvent:**

Partition coefficient: n-octanol/water : log Pow: 3.5 - 6.4 (68 °F / 20 °C)  
Method: Partition coefficient (n-octanol/water), HPLC method.

**Calcium sulphate:**

Partition coefficient: n-octanol/water : GLP: no  
Remarks: The value has not been determined because the substance is inorganic.

**Titanium dioxide:**

Partition coefficient: n-octanol/water : Remarks: not applicable

**toluene-2,6-diisocyanate:**

Partition coefficient: n-octanol/water : log Pow: 3.74  
Method: other (calculated)

**dibutyltin dilaurate:**

Partition coefficient: n-octanol/water : log Pow: 3.17 (69.4 °F / 20.8 °C)  
pH: 6.1 - 6.3  
Method: Partition coefficient (n-octanol/water), Shake-flask method  
GLP: yes

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Additional ecological information : There is a high probability that the product is not acutely harmful to aquatic organisms.  
The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Do not contaminate ponds, waterways or ditches with chemical or used container.  
Dispose of in accordance with national, state and local regulations.  
Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the sub-

## MasterSeal M 200 flash SLP

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/15/2020	000000261546	Date of first issue: 10/15/2020

---

stance/product.

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

UN number : UN 1263  
Proper shipping name : PAINT  
Class : 3  
Packing group : III  
Labels : 3

**IATA-DGR**

UN/ID No. : UN 1263  
Proper shipping name : PAINT  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

**IMDG-Code**

UN number : UN 1263  
Proper shipping name : PAINT  
  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****49 CFR**

UN/ID/NA number : UN 1263  
Proper shipping name : PAINT, COMBUSTIBLE LIQUID  
  
Class : C  
Packing group : III  
Labels : Combustible Liquid  
ERG Code : 128  
Marine pollutant : no

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

**SECTION 15. REGULATORY INFORMATION**



## MasterSeal M 200 flash SLP

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/15/2020	000000261546	Date of first issue: 10/15/2020

---

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

toluene-2,6-diisocyanate 91-08-7

4-methyl-m-phenylene diisocyanate 584-84-9

**US State Regulations****Pennsylvania Right To Know**

4-methyl-m-phenylene diisocyanate	584-84-9
Limestone	1317-65-3
Calcium sulphate	7778-18-9
Titanium dioxide	13463-67-7
talc	14807-96-6
Silica, amorphous, fumed, cryst.-free	112945-52-5
Stoddard solvent	8052-41-3

**New Jersey Right To Know**

4-methyl-m-phenylene diisocyanate	584-84-9
Limestone	1317-65-3
Calcium sulphate	7778-18-9
Titanium dioxide	13463-67-7
talc	14807-96-6
Stoddard solvent	8052-41-3
toluene-2,6-diisocyanate	91-08-7
Quartz (SiO <sub>2</sub> )	14808-60-7

**California Prop. 65**

WARNING: This product can expose you to chemicals including ethylene oxide, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**The ingredients of this product are reported in the following inventories:**


TSCA : On the inventory, or in compliance with the inventory

**SECTION 16. OTHER INFORMATION****Further information**

## MasterSeal M 200 flash SLP

Version 1.0      Revision Date: 10/15/2020      SDS Number: 000000261546      Date of last issue: -  
Date of first issue: 10/15/2020

## NFPA 704:



## HMIS® IV:

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

## Full text of other abbreviations

29 CFR 1910.1000 (Table Z-1-A)	: OSHA - Table Z-1-A (29 CFR 1910.1000)
29 CFR 1910.1000 (Table Z-1)	: OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
29 CFR 1910.1000 (Table Z-3)	: OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000
ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV	: American Conference of Governmental Industrial Hygienists - threshold limit values (US)
NIOSH	: NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA P0	: USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	: USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
29 CFR 1910.1000 (Table Z-1-A) / TWA value	: Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-1) / CLV	: Ceiling Limit Value:
29 CFR 1910.1000 (Table Z-1) / PEL	: Permissible exposure limit
29 CFR 1910.1000 (Table Z-3) / TWA value	: Time Weighted Average (TWA):
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
ACGIHTLV / Skin Designation	: Skin Designation:
ACGIHTLV / STEL value	: Short Term Exposure Limit (STEL):
ACGIHTLV / TWA value	: Time Weighted Average (TWA):
NIOSH / Ceil_Time	: Ceiling Limit Value and Time Period (if specified):
NIOSH / REL value	: Recommended exposure limit (REL):

## MasterSeal M 200 flash SLP

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/15/2020	000000261546	Date of first issue: 10/15/2020

NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / STEL	:	Short-term exposure limit
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-1 / C	:	Ceiling
OSHA Z-3 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 10/15/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

**MasterSeal M 200 flash SLP**

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/15/2020	000000261546	Date of first issue: 10/15/2020

---

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN