

MasterSeal NP 150 Ist

Version 2.0 Revision Date: 06/09/2023 SDS Number: 000000260958 Date of last issue: 07/16/2020
Date of first issue: 07/16/2020

SECTION 1. IDENTIFICATION

Product name : MasterSeal NP 150 Ist
Product code : 000000000051704032 000000000051704032

Manufacturer or supplier's details

Company name of supplier : Master Builders-Construction Systems
US, LLC
Address : 23700 CHAGRIN BLVD
Beachwood OH 44122
Emergency telephone : ChemTel: +1-813-248-0585
National Emergency Tele-
phone Number : USA: +1-800-255-3924 ChemTel contract no. MIS9240420


Recommended use of the chemical and restrictions on use

Recommended use : Sealant
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Skin sensitization : Category 1
Reproductive toxicity : Category 1B
Short-term (acute) aquatic hazard : Category 3
Long-term (chronic) aquatic hazard : Category 3

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.
H360 May damage fertility or the unborn child.
H402 Harmful to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

MasterSeal NP 150 Ist

Version 2.0 Revision Date: 06/09/2023 SDS Number: 000000260958 Date of last issue: 07/16/2020
 Date of first issue: 07/16/2020

Precautionary Statements : **Prevention:**
 P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P261 Avoid breathing dust.
 P272 Contaminated work clothing must not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P363 Wash contaminated clothing before reuse.

Storage:
 P405 Store locked up.

Disposal:
 P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Mixture based on:
 polymers
 inorganic compounds

Components

Chemical name	CAS-No.	Concentration (% w/w)
calcium carbonate	471-34-1	>= 30 - < 50
Limestone	1317-65-3	>= 5 - < 10
Titanium dioxide	13463-67-7	>= 1 - < 5
Octadecanoic acid, monoester with 1,2,3-propanetriol	31566-31-1	>= 1 - < 5
Calcium distearate	1592-23-0	>= 1 - < 5
bis(2,2,6,6-tetramethyl-4-piperidyl)sebacate	52829-07-9	>= 0.1 - < 1
Aminoethyl aminopropyl trimethoxy silane	1760-24-3	>= 0.1 - < 1
Proprietary amide wax	Proprietary	>= 0.1 - < 1
Dibutyltin diacetyldiacetate	22673-19-4	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

MasterSeal NP 150 Ist

Version Revision Date: SDS Number: Date of last issue: 07/16/2020
2.0 06/09/2023 000000260958 Date of first issue: 07/16/2020

SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety.
Remove contaminated clothing.
- If inhaled : If generated vapours are inhaled, move to fresh air.
Seek medical attention.
- In case of skin contact : Wash thoroughly with soap and water
Under no circumstances should organic solvent be used.
If irritation develops, seek medical attention.
- In case of eye contact : Wash affected eyes for at least 15 minutes under running
water with eyelids held open, consult an eye specialist.
Remove contact lenses, if present, after first 5 minutes, then
continue rinsing for an additional 15 minutes.
- If swallowed : Rinse mouth and then drink 200-300 ml of water.
DO NOT induce vomiting unless directed to do so by a physi-
cian or poison control center.
- Most important symptoms : May cause an allergic skin reaction.
and effects, both acute and : May damage fertility or the unborn child.
delayed
- Notes to physician : Treat symptomatically.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam
Water spray
Dry powder
Carbon dioxide (CO₂)
- Unsuitable extinguishing : water jet
media
- Hazardous combustion prod- : harmful vapours
ucts : nitrogen oxides
 : fumes/smoke
 : carbon black
- Further information : The degree of risk is governed by the burning substance and
the fire conditions.
Contaminated extinguishing water must be disposed of in
accordance with official regulations.
- Special protective equipment : Wear a self-contained breathing apparatus.
for fire-fighters
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protec- : Use personal protective clothing.

MasterSeal NP 150 Ist

Version 2.0 Revision Date: 06/09/2023 SDS Number: 000000260958 Date of last issue: 07/16/2020
 Date of first issue: 07/16/2020

tive equipment and emergency procedures Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions : Contain contaminated water/firefighting water.
 Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up : Sweep/shovel up.
 Dispose of absorbed material in accordance with regulations.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Keep away from sources of ignition - No smoking.
 The relevant fire protection measures should be noted.

Advice on safe handling : Avoid contact with the skin, eyes and clothing.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Protect from direct sunlight.
 Store protected against freezing.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
calcium carbonate	471-34-1	TWA (Respirable)	5 mg/m ³ (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m ³ (Calcium carbonate)	NIOSH REL
Limestone	1317-65-3	TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (respirable fraction)	5 mg/m ³	OSHA Z-1
		TWA (Total dust)	15 mg/m ³	OSHA P0
		TWA (respirable dust fraction)	5 mg/m ³	OSHA P0
		TWA (Respirable)	5 mg/m ³ (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m ³ (Calcium carbonate)	NIOSH REL
Titanium dioxide	13463-67-7	TWA (total dust)	15 mg/m ³	OSHA Z-1

MasterSeal NP 150 Ist

Version 2.0 Revision Date: 06/09/2023 SDS Number: 000000260958 Date of last issue: 07/16/2020
 Date of first issue: 07/16/2020

		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA (Respirable particulate matter)	0.2 mg/m3 (Titanium dioxide)	ACGIH
		TWA (Respirable particulate matter)	2.5 mg/m3 (Titanium dioxide)	ACGIH
Octadecanoic acid, monoester with 1,2,3-propanetriol	31566-31-1	TWA value (Inhalable fraction)	10 mg/m3	ACGIHTLV
		TWA value (Respirable fraction)	3 mg/m3	ACGIHTLV
		TWA (Inhalable particulate matter)	10 mg/m3	ACGIH
		TWA (Respirable particulate matter)	3 mg/m3	ACGIH
Calcium distearate	1592-23-0	TWA (Inhalable particulate matter)	10 mg/m3	ACGIH
		TWA (Respirable particulate matter)	3 mg/m3	ACGIH
Dibutyltin diacetyldiacetate	22673-19-4	TWA value	0.1 mg/m3 (tin (Sn))	ACGIHTLV
		STEL value	0.2 mg/m3 (tin (Sn))	ACGIHTLV
		REL value	0.1 mg/m3 (tin (Sn))	NIOSH
		PEL	0.1 mg/m3 (tin (Sn))	29 CFR 1910.1000 (Table Z-1)
		TWA value	0.1 mg/m3 (tin (Sn))	29 CFR 1910.1000 (Table Z-1-A)
		TWA	0.1 mg/m3 (Tin)	OSHA Z-1
		TWA	0.1 mg/m3 (Tin)	ACGIH
		STEL	0.2 mg/m3 (Tin)	ACGIH
		TWA	0.1 mg/m3 (Tin)	OSHA P0
		TWA	0.1 mg/m3 (Tin)	NIOSH REL

Engineering measures : Ensure adequate ventilation.

MasterSeal NP 150 Ist

Version 2.0 Revision Date: 06/09/2023 SDS Number: 000000260958 Date of last issue: 07/16/2020
Date of first issue: 07/16/2020

Personal protective equipment

- Respiratory protection : Wear appropriate certified respirator when exposure limits may be exceeded.
Use NIOSH approved respiratory protection.
- Hand protection
- Remarks : Chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.
- Eye protection : Wear safety glasses with side shields or goggles.
- Skin and body protection : Body protection must be chosen based on level of activity and exposure.
- Protective measures : Avoid contact with the skin, eyes and clothing.
No special measures necessary if stored and handled correctly.
Handle in accordance with good building materials hygiene and safety practice.
Wearing of closed work clothing is recommended.
- Hygiene measures : When using, do not eat, drink or smoke.
Hands and/or face should be washed before breaks and at the end of the shift.
At the end of the shift the skin should be cleaned and skin-care agents applied.
Gloves must be inspected regularly and prior to each use.
Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : paste
- Color : pigmented
- Odor : odorless
- Odor Threshold : Not applicable
- pH : neutral to slightly alkaline
- Melting point : No data available
- Boiling point : No data available
- Flash point : does not flash

MasterSeal NP 150 Ist

Version 2.0 Revision Date: 06/09/2023 SDS Number: 000000260958 Date of last issue: 07/16/2020
Date of first issue: 07/16/2020

Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not classified as a flammability hazard
Self-ignition	:	not self-igniting
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	Heavier than air.
Relative density	:	No data available
Density	:	12.2 lb/USg (73 - 77 °F / 23 - 25 °C)
Bulk density	:	approx. 1.5 g/cm ³
Solubility(ies)		
Water solubility	:	slightly soluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	not applicable for mixtures
Autoignition temperature	:	No data available
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, dynamic	:	Not applicable
Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	Based on its structural properties the product is not classified as oxidizing.
Self-heating substances	:	No data available
Sublimation point	:	No data available
Molecular weight	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

MasterSeal NP 150 Ist

Version	Revision Date:	SDS Number:	Date of last issue: 07/16/2020
2.0	06/09/2023	000000260958	Date of first issue: 07/16/2020

Reactivity	:	No hazardous reactions if stored and handled as prescribed/indicated.
Chemical stability	:	The product is stable if stored and handled as prescribed/indicated.
Possibility of hazardous reactions	:	The product is stable if stored and handled as prescribed/indicated.
Conditions to avoid	:	See SDS section 7 - Handling and storage.
Incompatible materials	:	Strong acids Strong bases Strong oxidizing agents Strong reducing agents
Hazardous decomposition products	:	No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION
Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC Group 2B: Possibly carcinogenic to humans
Titanium dioxide

13463-67-7

Reproductive toxicity

May damage fertility or the unborn child.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

MasterSeal NP 150 Ist

Version 2.0 Revision Date: 06/09/2023 SDS Number: 000000260958 Date of last issue: 07/16/2020
Date of first issue: 07/16/2020

Aspiration toxicity

Not classified based on available information.

Further information**Product:**

Remarks : Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:****Ecotoxicology Assessment**

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential**Components:****Calcium distearate:**

Partition coefficient: n-octanol/water : log Pow: 0.8
Method: OECD Test Guideline 107

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with national, state and local regulations.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Do not discharge into drains/surface waters/groundwater.

MasterSeal NP 150 Ist

Version	Revision Date:	SDS Number:	Date of last issue: 07/16/2020
2.0	06/09/2023	000000260958	Date of first issue: 07/16/2020

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

US State Regulations

Pennsylvania Right To Know

calcium carbonate	471-34-1
Di-isononylphthalate	28553-12-0
Diisononyl phthalate (DINP)	68515-48-0
Limestone	1317-65-3
Titanium dioxide	13463-67-7
methanol	67-56-1

New Jersey Right To Know

calcium carbonate	471-34-1
Limestone	1317-65-3
Titanium dioxide	13463-67-7

California Prop. 65

WARNING: This product can expose you to chemicals including Di-isononylphthalate, which is/are known to the State of California to cause cancer, and Di-isodecyl phthalate, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL


MasterSeal NP 150 Ist

Version 2.0 Revision Date: 06/09/2023 SDS Number: 000000260958 Date of last issue: 07/16/2020
 Date of first issue: 07/16/2020

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z-1-A)	: OSHA - Table Z-1-A (29 CFR 1910.1000)
29 CFR 1910.1000 (Table Z-1)	: OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV	: American Conference of Governmental Industrial Hygienists - threshold limit values (US)
NIOSH	: NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA P0	: USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
29 CFR 1910.1000 (Table Z-1-A) / TWA value	: Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-1) / PEL	: Permissible exposure limit
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
ACGIHTLV / STEL value	: Short Term Exposure Limit (STEL):
ACGIHTLV / TWA value	: Time Weighted Average (TWA):
NIOSH / REL value	: Recommended exposure limit (REL):
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA P0 / TWA	: 8-hour time weighted average
OSHA Z-1 / TWA	: 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensa-

MasterSeal NP 150 Ist

Version	Revision Date:	SDS Number:	Date of last issue: 07/16/2020
2.0	06/09/2023	000000260958	Date of first issue: 07/16/2020

tion, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 06/09/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN