



## MasterSeal TC 225HT TB INTNL

Version	Revision Date:	SDS Number:	Date of last issue: 07/20/2020
1.1	11/25/2020	000000261212	Date of first issue: 07/20/2020

---

**GHS label elements**

Hazard pictograms



Signal Word

: Danger

Hazard Statements

: H226 Flammable liquid and vapour.  
 H319 Causes serious eye irritation.  
 H315 Causes skin irritation.  
 H331 Toxic if inhaled.  
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
 H317 May cause an allergic skin reaction.  
 H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.  
 H360 May damage fertility or the unborn child.  
 H402 Harmful to aquatic life.  
 H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

: **Prevention:**  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
 P260 Do not breathe dust or mist.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P273 Avoid release to the environment.  
 P243 Take action to prevent static discharges.  
 P201 Obtain special instructions before use.  
 P284 In case of inadequate ventilation wear respiratory protection.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
 P264 Wash face, hands and any exposed skin thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P242 Use only non-sparking tools.  
 P240 Ground and bond container and receiving equipment.

**Response:**  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

## MasterSeal TC 225HT TB INTNL

Version	Revision Date:	SDS Number:	Date of last issue: 07/20/2020
1.1	11/25/2020	000000261212	Date of first issue: 07/20/2020

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.

P233 Keep container tightly closed.

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/container to appropriate hazardous waste collection point.

**Other hazards**

No data available.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : isocyanate  
organic solvents

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Stoddard solvent	8052-41-3	>= 10 - < 15
4,4'-methylenedicyclohexyl diisoncyanate	5124-30-1	>= 10 - < 15
bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	41556-26-7	>= 0.3 - < 1
dibutyltin dilaurate	77-58-7	>= 0.3 - < 1
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	82919-37-7	>= 0.1 - < 0.2
talc	14807-96-6	>= 10 - < 15
Titanium dioxide	13463-67-7	>= 0 - < 5
Calcium sulphate	7778-18-9	>= 3 - < 7

**SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.

If inhaled : If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

In case of skin contact : After contact with skin, wash immediately with plenty of water and soap.  
Under no circumstances should organic solvent be used.

## MasterSeal TC 225HT TB INTNL

Version	Revision Date:	SDS Number:	Date of last issue: 07/20/2020
1.1	11/25/2020	000000261212	Date of first issue: 07/20/2020

---

- If irritation develops, seek medical attention.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,  
seek medical attention.  
Do NOT induce vomiting.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Toxic if inhaled.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May damage fertility or the unborn child.  
Causes damage to organs through prolonged or repeated exposure.
- Notes to physician : Treat symptomatically.
- 

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Foam  
Water spray  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.
- 

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.

## MasterSeal TC 225HT TB INTNL

Version	Revision Date:	SDS Number:	Date of last issue: 07/20/2020
1.1	11/25/2020	000000261212	Date of first issue: 07/20/2020

---

Evacuate personnel to safe areas.  
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

- Environmental precautions : Contain contaminated water/firefighting water.  
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

---

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Product is not explosive.

Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).  
Keep away from open flames, hot surfaces and sources of ignition.

- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapors/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

- Conditions for safe storage : Prevent unauthorized access.  
no smoking  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.

- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.  
Protect from direct sunlight.

## MasterSeal TC 225HT TB INTNL

Version 1.1      Revision Date: 11/25/2020      SDS Number: 000000261212      Date of last issue: 07/20/2020  
 Date of first issue: 07/20/2020

Materials to avoid : Observe VCI storage rules.

Further information on storage stability : No decomposition if stored and applied as directed.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
dibutyltin dilaurate	77-58-7	TWA value	0.1 mg/m <sup>3</sup> (tin (Sn))	ACGIHTLV
		STEL value	0.2 mg/m <sup>3</sup> (tin (Sn))	ACGIHTLV
		REL value	0.1 mg/m <sup>3</sup> (tin (Sn))	NIOSH
		PEL	0.1 mg/m <sup>3</sup> (tin (Sn))	29 CFR 1910.1000 (Table Z-1)
		TWA value	0.1 mg/m <sup>3</sup> (tin (Sn))	29 CFR 1910.1000 (Table Z-1-A)
		TWA	0.1 mg/m <sup>3</sup> (Tin)	OSHA Z-1
		TWA	0.1 mg/m <sup>3</sup> (Tin)	ACGIH
		STEL	0.2 mg/m <sup>3</sup> (Tin)	ACGIH
		TWA	0.1 mg/m <sup>3</sup> (Tin)	OSHA P0
		TWA	0.1 mg/m <sup>3</sup> (Tin)	NIOSH REL
Limestone	1317-65-3	REL value (Respirable)	5 mg/m <sup>3</sup>	NIOSH
		REL value (Total)	10 mg/m <sup>3</sup>	NIOSH
		PEL (Respirable fraction)	5 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respir-	5 mg/m <sup>3</sup>	OSHA Z-1

## MasterSeal TC 225HT TB INTNL

Version 1.1      Revision Date: 11/25/2020      SDS Number: 000000261212      Date of last issue: 07/20/2020  
 Date of first issue: 07/20/2020

		able fraction)		
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium carbonate)	NIOSH REL
4,4'-methylenedicyclohexyl diisoncyanate	5124-30-1	TWA value	0.005 ppm	ACGIHTLV
		Ceil_Time	0.01 ppm 0.11 mg/m3	NIOSH
		CLV	0.01 ppm 0.11 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	0.005 ppm	ACGIH
		C	0.01 ppm 0.11 mg/m3	NIOSH REL
		C	0.01 ppm 0.11 mg/m3	OSHA P0
Silicon dioxide	7631-86-9	REL value	6 mg/m3	NIOSH
		TWA value	6 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value	20 millions of particles per cubic foot of air	29 CFR 1910.1000 (Table Z-3)
		TWA value	0.8 mg/m3	29 CFR 1910.1000 (Table Z-3)
		TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
		TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL
		TWA	6 mg/m3 (Silica)	NIOSH REL
Calcium sulphate	7778-18-9	TWA value (Inhalable fraction)	10 mg/m3	ACGIHTLV
		REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)

## MasterSeal TC 225HT TB INTNL

Version 1.1      Revision Date: 11/25/2020      SDS Number: 000000261212      Date of last issue: 07/20/2020  
 Date of first issue: 07/20/2020

		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (Respirable)	5 mg/m3	NIOSH REL
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Inhalable particulate matter)	10 mg/m3 (Calcium)	ACGIH
Titanium dioxide	13463-67-7	TWA value	10 mg/m3	ACGIHTLV
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
talc	14807-96-6	TWA value (Respirable fraction)	2 mg/m3	ACGIHTLV
		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (respirable dust fraction)	2 mg/m3	OSHA P0
		TWA (Respirable)	2 mg/m3	NIOSH REL
		TWA	0.1 fibres per cubic centimeter	ACGIH
		TWA (Respirable particulate matter)	2 mg/m3	ACGIH
Stoddard solvent	8052-41-3	TWA value	100 ppm	ACGIHTLV



## MasterSeal TC 225HT TB INTNL

Version 1.1      Revision Date: 11/25/2020      SDS Number: 000000261212      Date of last issue: 07/20/2020  
 Date of first issue: 07/20/2020

		REL value	350 mg/m3	NIOSH
		Ceil_Time	1,800 mg/m3	NIOSH
		PEL	500 ppm 2,900 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	100 ppm 525 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	100 ppm	ACGIH
		TWA	350 mg/m3	NIOSH REL
		C	1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,900 mg/m3	OSHA Z-1
		TWA	100 ppm 525 mg/m3	OSHA P0

**Engineering measures** : Ensure adequate ventilation.

**Personal protective equipment**

Respiratory protection : Wear appropriate certified respirator when exposure limits may be exceeded.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Safety glasses with side-shields.

Skin and body protection : Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

Protective measures : Do not inhale gases/vapours/aerosols.  
 Avoid contact with the skin, eyes and clothing.  
 Avoid exposure - obtain special instructions before use.  
 Handle in accordance with good building materials hygiene and safety practice.  
 Wearing of closed work clothing is recommended.

Hygiene measures : Avoid contact with skin, eyes and clothing.  
 When using do not eat or drink.  
 When using do not smoke.  
 Wash hands before breaks and immediately after handling the product.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

## MasterSeal TC 225HT TB INTNL

Version 1.1      Revision Date: 11/25/2020      SDS Number: 000000261212      Date of last issue: 07/20/2020  
Date of first issue: 07/20/2020

---

Color : various colours

Odor : of polyol

Odor Threshold : not determined

pH : Not applicable

Melting point : No applicable information available.

Boiling point : 222.01 - 500 °F / 105.56 - 260 °C

Flash point : 105 °F / 41 °C

Method: Standard Method of Test for Flash Point by Setaflash Closed Tester

Evaporation rate : No applicable information available.

Flammability (solid, gas) : Flammable.

Upper explosion limit / Upper flammability limit : 7.0 %(V)

Lower explosion limit / Lower flammability limit : 1.0 %(V)

Vapor pressure : No data available

Relative vapor density : Heavier than air.

Relative density : No applicable information available.

Density : approx. 1.13 g/cm<sup>3</sup> (68 °F / 20 °C)

Solubility(ies)

    Water solubility : slightly soluble (68 °F / 20 °C)

    Solubility in other solvents : No applicable information available.

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity

    Viscosity, dynamic : 29 mPa.s (104 °F / 40 °C)

    Viscosity, kinematic : 2566 mm<sup>2</sup>/s (104 °F / 40 °C)

Explosive properties : Not explosive

## MasterSeal TC 225HT TB INTNL

Version	Revision Date:	SDS Number:	Date of last issue: 07/20/2020
1.1	11/25/2020	000000261212	Date of first issue: 07/20/2020

---

Oxidizing properties	:	Based on its structural properties the product is not classified as oxidizing.
Sublimation point	:	No applicable information available.
Molecular weight	:	No data available
Metal corrosion rate	:	Corrosive effects to metal are not anticipated.

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	No hazardous reactions if stored and handled as prescribed/indicated.
Chemical stability	:	The product is stable if stored and handled as prescribed/indicated.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapors may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Strong acids Strong bases Strong oxidizing agents Strong reducing agents
Hazardous decomposition products	:	No hazardous decomposition products if stored and handled as prescribed/indicated.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Toxic if inhaled.

**Product:**

Acute inhalation toxicity	:	ATE: 2.19 mg/l Remarks: Determined for vapor
---------------------------	---	---

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Respiratory or skin sensitization****Skin sensitization**

May cause an allergic skin reaction.

**Respiratory sensitization**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.



## MasterSeal TC 225HT TB INTNL

Version 1.1      Revision Date: 11/25/2020      SDS Number: 000000261212      Date of last issue: 07/20/2020  
Date of first issue: 07/20/2020

---

**Bioaccumulative potential****Components:****Stoddard solvent:**

Partition coefficient: n-octanol/water : log Pow: 3.5 - 6.4 (68 °F / 20 °C)  
Method: Partition coefficient (n-octanol/water), HPLC method.

**4,4'-methylenedicyclohexyl diisoncyanate:**

Partition coefficient: n-octanol/water : Remarks: Study technically not feasible.

**bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate:**

Partition coefficient: n-octanol/water : Remarks: No data available.

**dibutyltin dilaurate:**

Partition coefficient: n-octanol/water : log Pow: 3.17 (69.4 °F / 20.8 °C)  
pH: 6.1 - 6.3  
Method: Partition coefficient (n-octanol/water), Shake-flask method  
GLP: yes

**Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:**

Partition coefficient: n-octanol/water : Remarks: No data available.

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Additional ecological information : There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with national, state and local regulations. Residues should be disposed of in the same manner as the substance/product. Do not discharge into drains/surface waters/groundwater.

## MasterSeal TC 225HT TB INTNL

Version	Revision Date:	SDS Number:	Date of last issue: 07/20/2020
1.1	11/25/2020	000000261212	Date of first issue: 07/20/2020

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

UN number : UN 1263  
 Proper shipping name : PAINT  
 Class : 3  
 Packing group : III  
 Labels : 3

**IATA-DGR**

UN/ID No. : UN 1263  
 Proper shipping name : PAINT  
 Class : 3  
 Packing group : III  
 Labels : Flammable Liquids  
 Packing instruction (cargo aircraft) : 366  
 Packing instruction (passenger aircraft) : 355

**IMDG-Code**

UN number : UN 1263  
 Proper shipping name : PAINT  
  
 Class : 3  
 Packing group : III  
 Labels : 3  
 EmS Code : F-E, S-E  
 Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****49 CFR**

UN/ID/NA number : UN 1263  
 Proper shipping name : PAINT, COMBUSTIBLE LIQUID  
  
 Class : C  
 Packing group : III  
 Labels : Combustible Liquid  
 ERG Code : 128  
 Marine pollutant : no

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## MasterSeal TC 225HT TB INTNL

Version	Revision Date:	SDS Number:	Date of last issue: 07/20/2020
1.1	11/25/2020	000000261212	Date of first issue: 07/20/2020

## SECTION 15. REGULATORY INFORMATION

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

4,4'-methylenedicyclohexyl diisoncyanate	5124-30-1
--	-----------

## US State Regulations

## Pennsylvania Right To Know

Titanium dioxide	13463-67-7
4,4'-methylenedicyclohexyl diisoncyanate	5124-30-1
Calcium sulphate	7778-18-9
Limestone	1317-65-3
talc	14807-96-6
Silica, amorphous, fumed, cryst.-free	112945-52-5
Stoddard solvent	8052-41-3

## New Jersey Right To Know

Titanium dioxide	13463-67-7
4,4'-methylenedicyclohexyl diisoncyanate	5124-30-1
talc	14807-96-6
Stoddard solvent	8052-41-3
Limestone	1317-65-3
Calcium sulphate	7778-18-9

## California Prop. 65

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer, and toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : This product contains the following components listed on the Canadian NDSL. All other components are on the Canadian DSL.

Fatty acids, C14-18 and C16-18-unsatd., maleated


## SECTION 16. OTHER INFORMATION

## Further information

## MasterSeal TC 225HT TB INTNL

Version 1.1      Revision Date: 11/25/2020      SDS Number: 000000261212      Date of last issue: 07/20/2020  
 Date of first issue: 07/20/2020

## NFPA 704:



## HMIS® IV:

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

## Full text of other abbreviations

29 CFR 1910.1000 (Table Z-1-A)	: OSHA - Table Z-1-A (29 CFR 1910.1000)
29 CFR 1910.1000 (Table Z-1)	: OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
29 CFR 1910.1000 (Table Z-3)	: OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000
ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV	: American Conference of Governmental Industrial Hygienists - threshold limit values (US)
NIOSH	: NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA P0	: USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	: USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
29 CFR 1910.1000 (Table Z-1-A) / CLV	: Ceiling Limit Value:
29 CFR 1910.1000 (Table Z-1-A) / TWA value	: Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-1) / PEL	: Permissible exposure limit
29 CFR 1910.1000 (Table Z-3) / TWA value	: Time Weighted Average (TWA):
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
ACGIHTLV / STEL value	: Short Term Exposure Limit (STEL):
ACGIHTLV / TWA value	: Time Weighted Average (TWA):
NIOSH / Ceil_Time	: Ceiling Limit Value and Time Period (if specified):
NIOSH / REL value	: Recommended exposure limit (REL):
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek



## MasterSeal TC 225HT TB INTNL

Version	Revision Date:	SDS Number:	Date of last issue: 07/20/2020
1.1	11/25/2020	000000261212	Date of first issue: 07/20/2020

NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / C	:	Ceiling limit
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 11/25/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT

**MasterSeal TC 225HT TB INTNL**

Version	Revision Date:	SDS Number:	Date of last issue: 07/20/2020
1.1	11/25/2020	000000261212	Date of first issue: 07/20/2020

---

PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN