

MasterSeal TC 275 PART B

Version 2.0 Revision Date: 04/26/2021 SDS Number: 000000534220 Date of last issue: 07/27/2020
Date of first issue: 04/27/2020

SECTION 1. IDENTIFICATION

Product name : MasterSeal TC 275 PART B
Product code : 000000000055352976 000000000055352976

Manufacturer or supplier's details

Company name of supplier : Master Builders-Construction Systems
US, LLC

Address : 23700 CHAGRIN BLVD
Beachwood OH 44122

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use



Recommended use : Product for construction chemicals
Restrictions on use : Reserved for industrial and professional use.

National Emergency Telephone Number : USA: +1-800-255-3924 ChemTel contract no. MIS9240420

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Acute toxicity (Inhalation) : Category 4
Skin corrosion/irritation : Category 2
Serious eye damage/eye irritation : Category 2A
Respiratory sensitization : Category 1
Skin sensitization : Category 1
Specific target organ toxicity - single exposure : Category 3 (Respiratory system)
Specific target organ toxicity - repeated exposure : Category 2 (Olfactory organs)

GHS label elements

Hazard pictograms :  

Signal Word : Danger

MasterSeal TC 275 PART B

Version	Revision Date:	SDS Number:	Date of last issue: 07/27/2020
2.0	04/26/2021	000000534220	Date of first issue: 04/27/2020

- Hazard Statements : H319 Causes serious eye irritation.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H373 May cause damage to organs (Olfactory organs) through prolonged or repeated exposure.
- Precautionary Statements : **Prevention:**
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P271 Use only outdoors or in a well-ventilated area.
P260 Do not breathe dusts or mists.
P261 Avoid breathing mist.
P284 In case of inadequate ventilation wear respiratory protection.
P272 Contaminated work clothing should not be allowed out of the workplace.
P264 Wash face, hands and any exposed skin thoroughly after handling.
- Response:**
P312 Call a POISON CENTER or doctor/ physician if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P314 Get medical advice/ attention if you feel unwell.
P302 + P352 IF ON SKIN: Wash with plenty of water.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
- Storage:**
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
- Disposal:**
P501 Dispose of contents/container to appropriate hazardous waste collection point.

MasterSeal TC 275 PART B

Version Revision Date: SDS Number: Date of last issue: 07/27/2020
2.0 04/26/2021 000000534220 Date of first issue: 04/27/2020

Other hazards

CONTAINS ISOCYANATES. INHALATION OF ISOCYANATE MISTS OR VAPORS MAY CAUSE RESPIRATORY IRRITATION, BREATHLESSNESS, CHEST DISCOMFORT AND REDUCED PULMONARY FUNCTION. OVEREXPOSURE WELL ABOVE THE PEL MAY RESULT IN BRONCHITIS, BRONCHIAL SPASMS AND PULMONARY EDEMA. LONG-TERM EXPOSURE TO ISOCYANATES HAS BEEN REPORTED TO CAUSE LUNG DAMAGE, INCLUDING REDUCED LUNG FUNCTION WHICH MAY BE PERMANENT. ACUTE OR CHRONIC OVEREXPOSURE TO ISOCYANATES MAY CAUSE SENSITIZATION IN SOME INDIVIDUALS, RESULTING IN ALLERGIC RESPIRATORY REACTIONS INCLUDING WHEEZING, SHORTNESS OF BREATH AND DIFFICULTY BREATHING. ANIMAL TESTS INDICATE THAT SKIN CONTACT MAY PLAY A ROLE IN CAUSING RESPIRATORY SENSITIZATION.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : isocyanate

Components

Chemical name	CAS-No.	Concentration (% w/w)
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8	>= 50 - < 75
Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)	9016-87-9	>= 25 - < 50
Methylenediphenyl diisocyanate	26447-40-5	>= 7 - < 15
Polymethylene polyphenylisocyanate, polyethylene glycol polymer	57636-09-6	>= 1 - < 3
1,3-Diazetidone-2,4-dione, 1,3-bis[4-[(4-isocyanatophenyl)methyl]phenyl]-	17589-24-1	>= 0.3 - < 1

SECTION 4. FIRST AID MEASURES

- General advice : Immediately remove contaminated clothing.
First aid personnel should pay attention to their own safety.
If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).
- If inhaled : Remove the affected individual into fresh air and keep the person calm.
Assist in breathing if necessary.
Seek medical attention.
- In case of skin contact : Wash affected areas thoroughly with soap and water.
Remove contaminated clothing. If irritation develops, get medical attention.
- In case of eye contact : In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
Immediate medical attention required.
- If swallowed : Rinse mouth and then drink 200-300 ml of water.

MasterSeal TC 275 PART B

Version	Revision Date:	SDS Number:	Date of last issue: 07/27/2020
2.0	04/26/2021	000000534220	Date of first issue: 04/27/2020

Do NOT induce vomiting.
Immediate medical attention required.

Most important symptoms and effects, both acute and delayed : Causes serious eye irritation.
Causes skin irritation.
Harmful if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
May cause respiratory irritation.
May cause damage to organs through prolonged or repeated exposure.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam
Water spray
Dry powder
Carbon dioxide (CO₂)

Unsuitable extinguishing media : water jet

Specific hazards during fire fighting : Reacts with water, with formation of carbon dioxide.

Hazardous combustion products : nitrogen oxides
isocyanate
fumes/smoke

Further information : Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Special protective equipment for fire-fighters : Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Clear area.
Ensure adequate ventilation.
Wear suitable personal protective clothing and equipment.
Clean up spills immediately.

Environmental precautions : Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up : Dike spillage.
If temporary control of isocyanate vapor is required, a blanket of protein foam or other suitable foam (available from most fire departments) may be placed over the spill. Transfer as much liquid as possible via pump or vacuum device into closed but

MasterSeal TC 275 PART B

Version	Revision Date:	SDS Number:	Date of last issue: 07/27/2020
2.0	04/26/2021	000000534220	Date of first issue: 04/27/2020

not sealed containers for disposal.
 Absorb isocyanate with suitable absorbent material (see § 40 CFR, sections 260, 264 and 265 for further information).
 Shovel into open container.
 Spill area can be decontaminated with the following recommended decontamination solution:
 Mixture of 90 % water, 5-8 % household ammonia, 2-5 % detergent.
 Wash down spill area with decontamination solution.
 Allow solution to stand for at least 10 minutes.
 Pick up with suitable absorbent material.
 Place into appropriately labeled waste containers.
 Do not make container pressure tight.
 Move container to a well-ventilated area (outside).
 Allow to stand for at least 48 hours to allow escape of evolved carbon dioxide.
 Dispose of absorbed material in accordance with regulations.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Mix thoroughly before use.
 Avoid aerosol formation.
 Ensure thorough ventilation of stores and work areas.
 Danger of bursting when sealed gastight.
 Protect against moisture.
 If bulging of drum occurs, transfer to well ventilated area, puncture to relieve pressure, open vent and let stand for 48 hours before resealing.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
 Observe label precautions.
 Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep container tightly closed in a cool, well-ventilated place.
 Protect against moisture.
 Formation of CO₂ and build up of pressure possible.
 Danger of bursting when sealed gastight.
- Materials to avoid : Keep away from water.
 Segregate from foods and animal feeds.
 Segregate from acids and bases.
- Recommended storage temperature : 61 - 81 °F / 16 - 27 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

MasterSeal TC 275 PART B

Version 2.0 Revision Date: 04/26/2021 SDS Number: 000000534220 Date of last issue: 07/27/2020
 Date of first issue: 04/27/2020

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8	TWA value	0.005 ppm	ACGIHTLV
		REL value	0.005 ppm 0.05 mg/m ³	NIOSH
		Ceil_Time	0.020 ppm 0.2 mg/m ³	NIOSH
		CLV	0.02 ppm 0.2 mg/m ³	29 CFR 1910.1000 (Table Z-1)
		CLV	0.02 ppm 0.2 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		TWA	0.005 ppm	ACGIH
		C	0.02 ppm 0.2 mg/m ³	OSHA Z-1
		C	0.02 ppm 0.2 mg/m ³	OSHA P0
		TWA	0.005 ppm 0.05 mg/m ³	NIOSH REL
		C	0.02 ppm 0.2 mg/m ³	NIOSH REL
Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)	9016-87-9	C	0.02 ppm 0.2 mg/m ³	OSHA Z-1
		C	0.02 ppm 0.2 mg/m ³	OSHA P0
		TWA	0.005 ppm 0.05 mg/m ³	NIOSH REL
		C	0.02 ppm 0.2 mg/m ³	NIOSH REL

Engineering measures : Provide local exhaust ventilation to maintain recommended P.E.L.

Personal protective equipment

Respiratory protection : When atmospheric levels may exceed the occupational exposure limit (PEL or TLV) NIOSH-certified air-purifying respirators equipped with an organic vapor sorbent and particulate filter can be used as long as appropriate precautions and change out schedules are in place.
 For emergency or non-routine, high exposure situations, including confined space entry, use a NIOSH-certified full face-piece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied-air respirator (SAR) with escape provisions.

Hand protection

Remarks : Chemical resistant protective gloves Suitable materials chloroprene rubber (Neoprene) chlorinated polyethylene polyvinylchloride (Pylox) butyl rubber fluoroelastomer (Viton) nitrile

MasterSeal TC 275 PART B

Version 2.0 Revision Date: 04/26/2021 SDS Number: 000000534220 Date of last issue: 07/27/2020
Date of first issue: 04/27/2020

- rubber (Buna N)
- Eye protection : Tightly fitting safety goggles (chemical goggles).
Wear face shield if splashing hazard exists.
- Skin and body protection : Cover as much of the exposed skin as possible to prevent all skin contact.
Suitable materials may include saran-coated material
Chemical resistant protective boots
- Protective measures : Wear protective clothing as necessary to prevent contact.
Do not breathe vapour/spray.
Eye wash fountains and safety showers must be easily accessible.
Observe the appropriate PEL value.
- Hygiene measures : No eating, drinking, smoking or tobacco use at the place of work.
Wash hands before breaks and at the end of workday.
Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.
-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : black
- Odor : faintly aromatic
- Odor Threshold : not determined
- pH : Not applicable
- Freezing point : approx. 35.6 °F / 2.0 °C
- Boiling point : 392 °F / 200 °C
(6.666 hPa)
- Flash point : > 392 °F / > 200 °C
Method: open cup
- Evaporation rate : No data available
- Flammability (liquids) : Not classified as a flammability hazard
- Self-ignition : Based on its structural properties the product is not classified as self-igniting.

MasterSeal TC 275 PART B

Version	Revision Date:	SDS Number:	Date of last issue: 07/27/2020
2.0	04/26/2021	000000534220	Date of first issue: 04/27/2020

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : 0.00010 mmHg (77.00 °F / 25.00 °C)

Relative vapor density : No data available

Relative density : No data available

Density : 10.1 lb/USg (77.00 °F / 25.00 °C)

Solubility(ies)

 Water solubility : hydrolyzes

 Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Autoignition temperature : > 878 °F / > 470 °C

Viscosity

 Viscosity, dynamic : No data available

 Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : Not an oxidizer.

Sublimation point : No data available

Molecular weight : No data available

Metal corrosion rate : No corrosive effect on metal.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions : Reacts with water, with formation of carbon dioxide.
Risk of bursting.
Reacts with alcohols.
Reacts with acids.
Reacts with alkalis.
Reacts with amines.
Risk of exothermic reaction.

MasterSeal TC 275 PART B

Version	Revision Date:	SDS Number:	Date of last issue: 07/27/2020
2.0	04/26/2021	000000534220	Date of first issue: 04/27/2020

Risk of violent reaction.
 Risk of polymerization.
 Contact with certain rubbers and plastics can cause brittleness of the substance/product with subsequent loss in strength.

Conditions to avoid : Avoid moisture.

Incompatible materials : Water
 Alcohols
 Strong bases
 Substances/products that react with isocyanates.

Hazardous decomposition products : Carbon monoxide
 Hydrogen cyanide (hydrocyanic acid)
 Nitrogen oxides (NOx)
 Aromatic isocyanates
 gases/vapours

SECTION 11. TOXICOLOGICAL INFORMATION
Acute toxicity

Harmful if inhaled.

Product:

Acute inhalation toxicity : Acute toxicity estimate: 1.01 mg/l

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

Respiratory sensitization

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs (Olfactory organs) through prolonged or repeated exposure.

MasterSeal TC 275 PART B

Version 2.0 Revision Date: 04/26/2021 SDS Number: 000000534220 Date of last issue: 07/27/2020
Date of first issue: 04/27/2020

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regulations. Do not discharge into drains/surface waters/groundwater. Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

MasterSeal TC 275 PART B

Version	Revision Date:	SDS Number:	Date of last issue: 07/27/2020
2.0	04/26/2021	000000534220	Date of first issue: 04/27/2020

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8	>= 50 - < 70 %
Isocyanic acid, polymethylene-polyphenylene ester (P-MDI)	9016-87-9	>= 30 - < 50 %

US State Regulations**Pennsylvania Right To Know**

Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8
Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)	9016-87-9

New Jersey Right To Know

Methylenediphenyl diisocyanate	26447-40-5
Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)	9016-87-9
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8

The ingredients of this product are reported in the following inventories:

TSCA : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.


DSL : This product contains one or more components listed on the Canadian NDSL. All other components are on the Canadian DSL.

SECTION 16. OTHER INFORMATION**Further information**

MasterSeal TC 275 PART B

Version 2.0 Revision Date: 04/26/2021 SDS Number: 000000534220 Date of last issue: 07/27/2020
 Date of first issue: 04/27/2020

NFPA 704:



HMIS® IV:

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z-1-A)	: OSHA - Table Z-1-A (29 CFR 1910.1000)
29 CFR 1910.1000 (Table Z-1)	: OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV	: American Conference of Governmental Industrial Hygienists - threshold limit values (US)
NIOSH	: NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA P0	: USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
29 CFR 1910.1000 (Table Z-1-A) / CLV	: Ceiling Limit Value:
29 CFR 1910.1000 (Table Z-1) / CLV	: Ceiling Limit Value:
ACGIH / TWA	: 8-hour, time-weighted average
ACGIHTLV / TWA value	: Time Weighted Average (TWA):
NIOSH / Ceil_Time	: Ceiling Limit Value and Time Period (if specified):
NIOSH / REL value	: Recommended exposure limit (REL):
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / C	: Ceiling value not be exceeded at any time.
OSHA P0 / C	: Ceiling limit
OSHA Z-1 / C	: Ceiling

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency

MasterSeal TC 275 PART B

Version	Revision Date:	SDS Number:	Date of last issue: 07/27/2020
2.0	04/26/2021	000000534220	Date of first issue: 04/27/2020

Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 04/26/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN