

**MasterSeal TC 295 charcoal gre PART A**

Version 1.1      Revision Date: 01/08/2021      SDS Number: 000000894666      Date of last issue: 06/10/2020  
Date of first issue: 06/10/2020

---

**SECTION 1. IDENTIFICATION**

Product name : MasterSeal TC 295 charcoal gre PART A  
Product code : 000000000050583720 000000000050583720

**Manufacturer or supplier's details**

Company name of supplier : Master Builders-Construction Systems  
US, LLC  
Address : 23700 CHAGRIN BLVD  
Beachwood OH 44122  
Emergency telephone : ChemTel: +1-813-248-0585

**Recommended use of the chemical and restrictions on use**


Recommended use : Product for construction chemicals  
Restrictions on use : Reserved for industrial and professional use.

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200**

Skin corrosion/irritation : Category 2  
Serious eye damage/eye irritation : Category 1  
Skin sensitization : Category 1A  
Short-term (acute) aquatic hazard : Category 3  
Long-term (chronic) aquatic hazard : Category 3

**GHS label elements**

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H318 Causes serious eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H402 Harmful to aquatic life.  
H412 Harmful to aquatic life with long lasting effects.

## MasterSeal TC 295 charcoal gre PART A

Version 1.1      Revision Date: 01/08/2021      SDS Number: 000000894666      Date of last issue: 06/10/2020  
 Date of first issue: 06/10/2020

Precautionary Statements : **Prevention:**  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
 P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
 P273 Avoid release to the environment.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P264 Wash face, hands and any exposed skin thoroughly after handling.

**Response:**  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P302 + P352 IF ON SKIN: Wash with plenty of water.  
 P362 + P364 Take off contaminated clothing and wash it before reuse.  
 P310 Immediately call a POISON CENTER or doctor/ physician.

**Disposal:**  
 P501 Dispose of contents/container to appropriate hazardous waste collection point.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : No applicable information available.

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Aspartic acid, N,N'-(methylenedi-4,1-cyclohexanediyl)bis-, 1,1',4,4'-tetraethyl ester	136210-30-5	>= 25 - < 50
calcium oxide	1305-78-8	>= 5 - < 7
Diethyl fumarate	623-91-6	>= 0 - < 3
bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	41556-26-7	>= 0.3 - < 1
Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	82919-37-7	>= 0.2 - < 0.3
talc	14807-96-6	>= 25 - < 50
Titanium dioxide	13463-67-7	>= 3 - < 5
Limestone	1317-65-3	>= 1 - < 5

**SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.  
 Consult a physician.  
 Show this material safety data sheet to the doctor in attendance.  
 Do not leave the victim unattended.

## MasterSeal TC 295 charcoal gre PART A

Version	Revision Date:	SDS Number:	Date of last issue: 06/10/2020
1.1	01/08/2021	000000894666	Date of first issue: 06/10/2020

---

- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye damage.
- Notes to physician : Treat symptomatically.

---

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Foam  
Water spray  
Dry powder  
Carbon dioxide (CO<sub>2</sub>)
- Unsuitable extinguishing media : water jet
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

**MasterSeal TC 295 charcoal gre PART A**

Version	Revision Date:	SDS Number:	Date of last issue: 06/10/2020
1.1	01/08/2021	000000894666	Date of first issue: 06/10/2020

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapors/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
To avoid spills during handling keep bottle on a metal tray.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.  
Protect from direct sunlight.
- Materials to avoid : No applicable information available.
- Further information on storage stability : No decomposition if stored and applied as directed.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Ingredients with workplace control parameters**

## MasterSeal TC 295 charcoal gre PART A

Version  
1.1Revision Date:  
01/08/2021SDS Number:  
000000894666Date of last issue: 06/10/2020  
Date of first issue: 06/10/2020

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
calcium oxide	1305-78-8	TWA value	2 mg/m <sup>3</sup>	ACGIHTLV
		REL value	2 mg/m <sup>3</sup>	NIOSH
		PEL	5 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		TWA value	5 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		TWA	2 mg/m <sup>3</sup>	ACGIH
		TWA	2 mg/m <sup>3</sup>	NIOSH REL
		TWA	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA	5 mg/m <sup>3</sup>	OSHA P0
Limestone	1317-65-3	REL value (Respirable)	5 mg/m <sup>3</sup>	NIOSH
		REL value (Total)	10 mg/m <sup>3</sup>	NIOSH
		PEL (Respirable fraction)	5 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respirable fraction)	5 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Total dust)	15 mg/m <sup>3</sup>	OSHA P0
		TWA (respirable dust fraction)	5 mg/m <sup>3</sup>	OSHA P0
		TWA (Respirable)	5 mg/m <sup>3</sup> (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m <sup>3</sup> (Calcium carbonate)	NIOSH REL
Titanium dioxide	13463-67-7	TWA value	10 mg/m <sup>3</sup>	ACGIHTLV
		PEL (Total dust)	15 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m <sup>3</sup>	29 CFR 1910.1000 (Table Z-1-A)

## MasterSeal TC 295 charcoal gre PART A

Version 1.1      Revision Date: 01/08/2021      SDS Number: 000000894666      Date of last issue: 06/10/2020  
 Date of first issue: 06/10/2020

		TWA (total dust)	15 mg/m <sup>3</sup>	OSHA Z-1
		TWA (Total dust)	10 mg/m <sup>3</sup>	OSHA P0
		TWA	10 mg/m <sup>3</sup> (Titanium dioxide)	ACGIH
talc	14807-96-6	TWA value (Respirable fraction)	2 mg/m <sup>3</sup>	ACGIHTLV
		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (respirable dust fraction)	2 mg/m <sup>3</sup>	OSHA P0
		TWA (Respirable)	2 mg/m <sup>3</sup>	NIOSH REL
		TWA	0.1 fibres per cubic centimeter	ACGIH
		TWA (Respirable particulate matter)	2 mg/m <sup>3</sup>	ACGIH

**Engineering measures** : No applicable information available.

**Personal protective equipment**

Respiratory protection : When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Do not inhale gases/vapours/aerosols.  
Avoid contact with the skin, eyes and clothing.  
Avoid exposure - obtain special instructions before use.  
Handle in accordance with good building materials hygiene and safety practice.  
Wearing of closed work clothing is recommended.

Hygiene measures : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

## MasterSeal TC 295 charcoal gre PART A

Version 1.1      Revision Date: 01/08/2021      SDS Number: 000000894666      Date of last issue: 06/10/2020  
Date of first issue: 06/10/2020

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	:	liquid
Color	:	dark gray
Odor	:	faint odour
pH	:	No applicable information available.
Melting point	:	No applicable information available.
Freezing point	:	No applicable information available.
Boiling point	:	No applicable information available.
Flash point	:	323.60 °F / 162.00 °C  Method: Determination of flash point: Pensky-Martens closed cup method.
Evaporation rate	:	No applicable information available.
Flammability (solid, gas)	:	not flammable
Self-ignition	:	not self-igniting
Upper explosion limit / Upper flammability limit	:	No applicable information available.
Lower explosion limit / Lower flammability limit	:	No applicable information available.
Vapor pressure	:	No applicable information available.
Relative vapor density	:	No applicable information available.
Relative density	:	No applicable information available.
Density	:	1.5190 g/cm <sup>3</sup> (77.00 °F / 25.00 °C)
Solubility(ies)	:	
Water solubility	:	No applicable information available.
Solubility in other solvents	:	No applicable information available.
Partition coefficient: n-octanol/water	:	No applicable information available.
Autoignition temperature	:	No applicable information available.

## MasterSeal TC 295 charcoal gre PART A

Version	Revision Date:	SDS Number:	Date of last issue: 06/10/2020
1.1	01/08/2021	000000894666	Date of first issue: 06/10/2020

---

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity  
 Viscosity, dynamic : No applicable information available.

Viscosity, kinematic : No applicable information available.

Oxidizing properties : Based on its structural properties the product is not classified as oxidizing.

Sublimation point : No applicable information available.

Molecular weight : No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids  
 Strong bases  
 Strong oxidizing agents  
 Strong reducing agents

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Not classified based on available information.

**Product:**

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

**Skin corrosion/irritation**

Causes skin irritation.

**Product:**

Remarks : Extremely corrosive and destructive to tissue.





## MasterSeal TC 295 charcoal gre PART A

Version 1.1      Revision Date: 01/08/2021      SDS Number: 000000894666      Date of last issue: 06/10/2020  
Date of first issue: 06/10/2020

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:**

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

**Persistence and degradability**

No data available

**Bioaccumulative potential****Components:****Aspartic acid, N,N'-(methylenedi-4,1-cyclohexanediyl)bis-, 1,1',4,4'-tetraethyl ester:**

Partition coefficient: n-octanol/water : log Pow: 5.16  
Method: other (calculated)

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life.  
Harmful to aquatic life with long lasting effects.  
The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with national, state and local regulations.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

## MasterSeal TC 295 charcoal gre PART A

Version	Revision Date:	SDS Number:	Date of last issue: 06/10/2020
1.1	01/08/2021	000000894666	Date of first issue: 06/10/2020

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

Not regulated as a dangerous good

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****49 CFR**

Not regulated as a dangerous good

**SECTION 15. REGULATORY INFORMATION****US State Regulations****Pennsylvania Right To Know**

calcium oxide	1305-78-8
Limestone	1317-65-3
Titanium dioxide	13463-67-7
talc	14807-96-6

**New Jersey Right To Know**

calcium oxide	1305-78-8
Limestone	1317-65-3
Titanium dioxide	13463-67-7
talc	14807-96-6

**California Prop. 65**

WARNING: This product can expose you to chemicals including Titanium dioxide, which is/are known to the State of California to cause cancer, and methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**The ingredients of this product are reported in the following inventories:**


DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

**SECTION 16. OTHER INFORMATION****Further information**

## MasterSeal TC 295 charcoal gre PART A

Version 1.1      Revision Date: 01/08/2021      SDS Number: 000000894666      Date of last issue: 06/10/2020  
 Date of first issue: 06/10/2020

**NFPA 704:****HMIS® IV:**

<b>HEALTH</b>		
<b>FLAMMABILITY</b>		
<b>PHYSICAL HAZARD</b>		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

**Full text of other abbreviations**

29 CFR 1910.1000 (Table Z-1-A)	: OSHA - Table Z-1-A (29 CFR 1910.1000)
29 CFR 1910.1000 (Table Z-1)	: OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV	: American Conference of Governmental Industrial Hygienists - threshold limit values (US)
NIOSH	: NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA P0	: USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	: USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
29 CFR 1910.1000 (Table Z-1-A) / TWA value	: Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-1) / PEL	: Permissible exposure limit
ACGIH / TWA	: 8-hour, time-weighted average
ACGIHTLV / TWA value	: Time Weighted Average (TWA):
NIOSH / REL value	: Recommended exposure limit (REL):
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
OSHA P0 / TWA	: 8-hour time weighted average
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-3 / TWA	: 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely

## MasterSeal TC 295 charcoal gre PART A

Version	Revision Date:	SDS Number:	Date of last issue: 06/10/2020
1.1	01/08/2021	000000894666	Date of first issue: 06/10/2020

---

Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 01/08/2021

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE

**MasterSeal TC 295 charcoal gre PART A**

Version	Revision Date:	SDS Number:	Date of last issue: 06/10/2020
1.1	01/08/2021	000000894666	Date of first issue: 06/10/2020

---

ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN