



We create chemistry

Technical Bulletin

Equipment Recommendations for Application of MasterSeal® AWB 665, MasterSeal® AWB 660, MasterSeal® AWB 660 I, MasterSeal® AWB 600 FL

FORMERLY ENERSHIELD® -HP, ENERSHIELD® -I, ENERSHIELD® -FIL

DESCRIPTION

MasterSeal® AWB 665, MasterSeal® AWB 660, MasterSeal® AWB 660 I, and MasterSeal® AWB 600 FL are water-based, single component, Silica Fortified Rubber™ products designed for use with most substrates and cladding systems. MasterSeal® AWB systems can be applied with many commonly used spray equipment systems, rollers and/or brushes. The information contained within this document is designed to give the applicator a general listing of equipment that has been used successfully with MasterSeal® AWB products, and/or is generally recommended by the equipment manufacturer as acceptable. All attempts have been made to ensure the validity of the information contained within this document.

SPRAY EQUIPMENT SELECTION

Due to changes in equipment design and to the maintenance and wear involved with equipment, BASF Construction Systems does not warrant the information contained within this document. Proper equipment selection and success of the use of such equipment is the responsibility of the applicator. Equipment not listed in this bulletin may also provide acceptable performance. Please consult the equipment manufacturer for their recommendations and application guidelines. Please refer to the individual product technical data guides for additional information and application instructions.

MASTERSEAL® AWB 660, MASTERSEAL® AWB 660 I, MASTERSEAL® AWB 600 FL

Formerly Enershield® -HP, Enershield® -I, Enershield® -FIL

MODEL	GUN	TIP	PRESSURE (PSI)	HOSE LENGTH AND ID
Apla-Tech T-Series	Apla-Tech	2530 pressure washer tip	60-80	Max 100', 1/2"
Graco RTX1500	Texture Gun	#2 with B disc	20-80	Max 100', 3/4"
Graco HTX 2030 air assist	Trigger Gun	#2 with B disc	1000	Max 150', 3/4"
Graco HTX 2030 airless	HD Texture Gun (Blue)	655/665/671	1000-3300	Max 300', 1/2"
Graco GH833	HD Texture Gun (Blue)	655/665/671	500-1100	Max 300', 1/2"
Titan Hydra M 4000	M-8 Mastic Gun	SC-6 Plus 451	3100-3500	Max 300', 1/2"

MASTERSEAL® AWB 665

MODEL	GUN	TIP	PRESSURE (PSI)	HOSE LENGTH AND ID
Graco Ultra Max II 1095	Contractor/Silver Plus Gun	525/527/529	1800-2200	Max 100', 3/8"
Graco Ultra Max II 1595	Contractor/Silver Plus Gun	525/527/529	1800-2200	Max 150', 3/8"
Graco GMAX 5900	Contractor/Silver Plus Gun	525/527/529	1800-3300	Max 150', 3/8"
Graco GMAX 7900	Contractor/Silver Plus Gun	525/527/529	1800-3300	Max 150', 3/8"
Graco TexSpray Mark V	HD Texture Gun (Blue)	525/527/529	1800-2200	Max 150', 3/8"
Graco TexSpray Mark X	HD Texture Gun (Blue)	525/527/529	1800-2200	Max 150', 3/8"
Graco GH 833	HD Texture Gun (Blue)	525/527/529	500-1100	Max 300', 3/8"

MODEL	GUN	TIP	PRESSURE (PSI)	HOSE LENGTH AND ID
Graco Jet Roller System	-	525/527/529	-	-
Graco Pressure Roller	-	-	-	-
Titan Impact 1040	Rx-Pro	525/527/529	3000-3300	Max 100', 3/8"
Titan Impact 1140	Rx-Pro	525/527/529	3000-3300	Max 100', 3/8"
Titan PowrTwin 6900	Rx-Pro/LX-80II/S-5	525/527/529	3000-3600	Max 150', 3/8"
Titan PowrTwin 8900	Rx-Pro/LX-80II/S-5	525/527/529	3000-3600	Max 150', 3/8"
Titan PowrTwin 12000	Rx-Pro/LX-80II/S-5	525/527/529	3000-3600	Max 150', 3/8"
Titan Hydra M 4000	S-5	TRI HP 525	3100-3500	Max 300', 3/8"
Titan Power Roller System	-	525/527/529	-	-

*For best performance, remove filters from pump and gun. If pump filters are used, the minimum filter recommended is 60 mesh.

*A maximum 3/8" (ID) whip is recommended (airless only).

EQUIPMENT START-UP

Prior to starting up equipment, carefully read and follow the equipment manufacturer's operating and safety instructions and familiarize yourself with equipment features. If using an external air compressor, ensure that it has a capacity and pressure rating that meets the pump manufacturer's specifications. **Note: It is important to ensure that all equipment is clean prior to use.**

SPRAY APPLICATION

Verify substrate condition before spray application. Applicators should protect all surfaces that are not to be coated. Mask off sensitive areas (such as windows) and clean off any overspray before MasterSeal® AWB 665/MasterSeal® AWB 660/ MasterSeal® AWB 660 I cures.

EQUIPMENT CLEANUP

Immediately after use and before material has cured, clean equipment with warm water. Follow the spray equipment manufacturer's cleaning recommendations. Cured MasterSeal® AWB 665/ MasterSeal® AWB 660/MasterSeal® AWB 660 I is difficult to remove and may affect subsequent equipment performance.

FOR BEST PERFORMANCE

The greatest productivity gains are realized on large walls that have few areas that must be protected from overspray (e.g. windows). Small, complex walls may be more suited for roller or brush application. Note that the weather plays a role – windy days may be less than ideal for spraying material. Power Roller, Jet Roller, and Pressure Roller systems can increase productivity in these conditions, when spraying is not conducive.

TECHNICAL SUPPORT

Consult the BASF Construction Systems Technical Services Department for specific recommendations concerning all other applications. Consult the Master Builders website, www.master-builders-solutions.basf.com, for additional information about products and systems and for updated literature.

HEALTH AND SAFETY

Read, understand, and follow all Safety Data Sheets and product label information for this product prior to use. The SDS can be obtained by visiting www.master-builders-solutions.basf.us, email your request to basfbcsst.basf.com or by calling 1(800)433-9517. Use only as directed.

For medical emergencies only, call CHEMTREC at (800) 424-9300.

WARRANTY

BASF warrants this product to be free from manufacturing defects and to meet the technical properties on the current Product Bulletin, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control.

BASF MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product,

including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of BASF. In the absence of an extended warranty issued by BASF, any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. BASF WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on BASF's present knowledge and experience. However, BASF assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. BASF reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.