

MasterTop® P 160

Primer for MasterTop 110 SL underlayment

FORMERLY CHEMREX® PRIMER G

PACKAGING

– 1 gallon (3.8 L) pails

YIELD

200–400 ft²/gal (4.91–9.83 m²/L)

when diluted with 1:1 with water.

Coverage will vary based upon profile and porosity of the substrate.

STORAGE

Store in unopened containers between 60 and 80° F (16 to 27° C) in clean, dry conditions. Keep from freezing.

SHELF LIFE

12 months when properly stored

VOC CONTENT

156 g/L less water and exempt solvents

DESCRIPTION

MasterTop P 160 is a high-quality primer and bonding agent that seals concrete surfaces and provides a maximum-strength binder coat for MasterTop 110 SL underlayment.

PRODUCT HIGHLIGHTS

- Low VOC content complies with most regional regulations
- Compatibility with cured adhesive can prevent expensive floor refinishing
- Compatibility with uncured adhesive eliminates dull residue

APPLICATIONS

- Interior
- As a primer and binder coat for MasterTop 110 SL underlayment

SUBSTRATES

- Semi-porous, and porous concrete

HOW TO APPLY

BEFORE APPLYING MASTERTOP P 160, CONSULT THE TECHNICAL DATA GUIDE FOR MASTERTOP 110 SL.

SURFACE PREPARATION

1. Concrete surfaces must be fully cured, structurally sound, clean, and free of dust, oil, grease, water, curing compounds, sealers, waxes, paint, or any contaminants that might inhibit proper bond.
2. Fill and grout all cracks and drilled or sawed holes to prevent seepage of MasterTop P 160 or MasterTop 110 SL.
3. Designed joints in substrate must be carried through the application of MasterTop 110 SL.
4. The concrete surface must be roughened to a CSP of 8–9 following ICRI Guideline no. 310.2 to permit proper bond.
5. Dampen the substrate prior to application, being sure to remove any standing water.

MIXING

Stir for 1 or 2 minutes with a clean stir stick using the dilution ratios appropriate for the porosity of the substrate (see the Application section below).

APPLICATION

1. Apply MasterTop P 160 with a brush or roller, working the primer thoroughly into the substrate. Avoid leaving puddles of primer in low areas.
2. On semi-porous surfaces (including steel troweled concrete), use 1 coat of MasterTop P 160 diluted 1:1 with clean water.
3. Porous surfaces may require 2 coats of MasterTop P 160. Dilute the first coat with 2 parts clean water and 1 part primer. Dilute the second coat with 1 part primer and 1 part clean water.
4. When applying MasterTop P 160 over MasterTop P 220, let MasterTop P 220 dry a minimum of 4 hours and no more than 24 hours. MasterTop P 160 and MasterTop 110 SL must be applied in the same day.

DRYING TIME

Cure time is approximately 1–2 hours, depending on ambient temperatures and humidity. Allow MasterTop P 160 to dry 2–24 hours before applying a second coat of primer. The final coat of primer should dry to a tack-free condition before the placement of MasterTop 110 SL. MasterTop 110 SL must be applied the same day as priming or the substrate will require another application of primer diluted 1 to 1 with water.

CLEAN UP

Immediately clean equipment with soap and water.

FOR BEST PERFORMANCE

- Do not allow to freeze. If material freezes, DO NOT USE
- Test installations are encouraged. Test floors for vapor drive in accordance with ASTM D 4263. The finish used will determine the acceptable vapor drive.
- Minimum air and substrate application temperature is 40° F (4° C).
- MasterTop P 160 must be tack free during placement of MasterTop 110 SL.
- MasterTop 110 SL must be applied the same day as MasterTop P 160; otherwise, reapply primer.

- If diluting, use only clean potable water.
- For professional use only; not for sale to or use by the general public.
- Make certain the most current versions of product data sheet and SDS are being used; visit www.master-builders-solutions.com/en-us to verify the most current versions.
- Proper application is the responsibility of the user. Field visits by Master Builders Solutions personnel are for the purpose of making technical recommendations only and not for supervising or providing quality control on the jobsite.

HEALTH, SAFETY AND ENVIRONMENTAL

Read, understand and follow all Safety Data Sheets and product label information for this product prior to use. The SDS can be obtained by visiting www.master-builders-solutions.com/en-us, e-mailing your request to mbsbscst@mbcc-group.com or calling 1(800)433-9517. Use only as directed.

IN CASE OF EMERGENCY: Call CHEMTEL +1 (800) 255-3924 or if outside the US or Canada, +1 (813) 248-0585.

LIMITED WARRANTY NOTICE

Master Builders Solutions Construction Systems US, LLC ("Master Builders") warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. MASTER BUILDERS MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails

to meet this warranty, at the sole option of Master Builders. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. MASTER BUILDERS WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders' present knowledge and experience. However, Master Builders assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

FOR PROFESSIONAL USE ONLY. NOT FOR SALE TO OR USE BY THE GENERAL PUBLIC.