according to the OSHA Hazard Communication Standard



MasterTop SRS 100PAS

Version Revision Date: SDS Number: Date of last issue: 01/26/2022 2.0 10/27/2023 000000520172 Date of first issue: 08/20/2020

SECTION 1. IDENTIFICATION

Product name : MasterTop SRS 100PAS

Product code : 00000000050231291 00000000050231291

Manufacturer or supplier's details

Company name of supplier : Master Builders-Construction Systems

US, LLC

Address : 889 VALLEY PARK DR

Shakopee MN 55379-1854

Emergency telephone : ChemTel: +1-813-248-0585

National Emergency Tele-

phone Number

USA: +1-800-255-3924 ChemTel contract no. MIS9240420

Recommended use of the chemical and restrictions on use

Recommended use : Functional surface coating

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 2

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitization : Category 1

Specific target organ toxicity

- single exposure

Category 3 (Respiratory system)

Specific target organ toxicity

- repeated exposure (Oral)

: Category 2 (Kidney)

Short-term (acute) aquatic

hazard

Category 3

GHS label elements

according to the OSHA Hazard Communication Standard



MasterTop SRS 100PAS

Version Revision Date: SDS Number: Date of last issue: 01/26/2022 2.0 10/27/2023 000000520172 Date of first issue: 08/20/2020

Hazard pictograms







Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation.

H373 May cause damage to organs (Kidney) through prolonged

or repeated exposure if swallowed. H402 Harmful to aquatic life.

Precautionary Statements

Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe mist or vapors. P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of

the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P314 Get medical advice/ attention if you feel unwell.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention

P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alco-

hol-resistant foam to extinguish.

P403 + P233 Store in a well-ventilated place. Keep container

Storage:

according to the OSHA Hazard Communication Standard



MasterTop SRS 100PAS

Version Revision Date: SDS Number: Date of last issue: 01/26/2022 2.0 10/27/2023 000000520172 Date of first issue: 08/20/2020

tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : methacrylates

Components

Chemical name	CAS-No.	Concentration (% w/w)
methyl methacrylate	80-62-6	>= 15 - < 40
Dibutyl maleate	105-76-0	>= 1 - < 5
2,2'-Ethylenedioxydiethyl dimethacry-	109-16-0	>= 0.5 - < 3
late		

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.

If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).

Immediately remove contaminated clothing.

If inhaled : Keep patient calm, remove to fresh air, seek medical atten-

tion.

In case of skin contact : Wash thoroughly with soap and water

In case of eye contact : Wash affected eyes for at least 15 minutes under running

water with eyelids held open, consult an eye specialist.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention.

Most important symptoms and effects, both acute and

delayed

: Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated

exposure if swallowed.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

according to the OSHA Hazard Communication Standard



MasterTop SRS 100PAS

Version Revision Date: SDS Number: Date of last issue: 01/26/2022 2.0 10/27/2023 000000520172 Date of first issue: 08/20/2020

Suitable extinguishing media : Dry powder

Alcohol-resistant foam

Unsuitable extinguishing

media

water jet

Specific hazards during fire

fighting

Evolution of fumes/fog.

Hazardous combustion prod: :

ucts

harmful vapours

Further information : The degree of risk is governed by the burning substance and

the fire conditions.

Containers may rocket or explode in heat of fire.

Keep containers cool by spraying with water if exposed to fire. Collect contaminated extinguishing water separately, do not

allow to reach sewage or effluent systems.

Contaminated extinguishing water must be disposed of in

accordance with official regulations.

Special protective equipment:

for fire-fighters

Wear self-contained breathing apparatus and chemical-

protective clothing.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

gency procedures

Can release flammable vapours. Wind direction should be noted.

Avoid all sources of ignition: heat, sparks, open flame.

Use antistatic tools.

Breathing protection required. Use personal protective clothing.

Keep people away from and upwind of spill/leak.

Ventilate the area.

Environmental precautions : Prevent spread over a wide area (e.g. by containment or oil

barriers).

Contain contaminated water/firefighting water.

Do not discharge into drains/surface waters/groundwater.

Methods and materials for

containment and cleaning up

Pick up with suitable absorbent material.

Dispose of in accordance with national, state and local regula-

tions.

Large spills should be collected mechanically (remove by

pumping) for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Sources of ignition should be kept well clear.

Take precautionary measures against static discharges. Substance/product can form explosive mixture with air. Vapours are heavier than air and may accumulate in low are-

according to the OSHA Hazard Communication Standard



MasterTop SRS 100PAS

Version Revision Date: SDS Number: Date of last issue: 01/26/2022 2.0 10/27/2023 000000520172 Date of first issue: 08/20/2020

as and travel a considerable distance up to the source of igni-

tion.

Advice on safe handling : Take precautionary measures against static discharges.

Keep away from sources of ignition - No smoking.

Provide good room ventilation even at ground level (vapours

are heavier than air).

Conditions for safe storage : Keep containers tightly closed in a cool, well-ventilated place.

Protect from direct sunlight.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Use only explosion-proof equipment.

Materials to avoid : Segregate from strong oxidizing agents.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
methyl methacrylate	80-62-6	TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
		TWA	100 ppm	NIOSH REL
			410 mg/m3	
		TWA	100 ppm	OSHA Z-1
			410 mg/m3	
		TWA	100 ppm	OSHA P0
			410 mg/m3	

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits

may be exceeded.

Wear a NIOSH-certified (or equivalent) organic va-

pour/particulate respirator.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's

directions for use should be observed because of great di-

versity of types.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Body protection must be chosen based on level of activity

and exposure.

Protective measures : Do not inhale dust/fumes/aerosols.

Avoid contact with the skin, eyes and clothing.

according to the OSHA Hazard Communication Standard



MasterTop SRS 100PAS

Version Revision Date: SDS Number: Date of last issue: 01/26/2022 2.0 10/27/2023 000000520172 Date of first issue: 08/20/2020

Avoid exposure.

Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : Do not breathe vapors, mist or gas.

No eating, drinking, smoking or tobacco use at the place of

work.

Remove contaminated clothing and protective equipment

before entering eating areas.

Handle in accordance with good industrial hygiene and safety

practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : blue

Odor : sweet, ester-like

Odor Threshold : not determined

pH : Not applicable

Melting point/freezing point : -54 °F / -48 °C

Boiling point : 212 °F / 100 °C

Flash point : 48 °F / 9 °C

Evaporation rate : > 1

(Butyl Acetate=1.0)

Flammability (liquids) : Highly flammable liquid and vapor.

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapor pressure : 27.8 mmHg (68 °F / 20 °C)

Relative vapor density : 3.1

(Air = 1.0)

according to the OSHA Hazard Communication Standard



MasterTop SRS 100PAS

Version Revision Date: SDS Number: Date of last issue: 01/26/2022 2.0 10/27/2023 000000520172 Date of first issue: 08/20/2020

Relative density : 1.01

Density : 1.01 g/cm3 (77 °F / 25 °C)

8.44 lb/USg (77 °F / 25 °C)

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

not applicable for mixtures

Autoignition temperature : 806 °F / 430 °C

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : Not an oxidizer.

Sublimation temperature : No data available

Molecular weight : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as pre-

scribed/indicated.

Chemical stability : The product is stable if stored and handled as pre-

scribed/indicated.

Possibility of hazardous reac-

tions

: Vapors may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Electrostatic discharge

Incompatible materials : Strong bases

Acids

Oxidizing agents

Hazardous decomposition : No hazardous decomposition products if stored and handled

according to the OSHA Hazard Communication Standard



MasterTop SRS 100PAS

Version Revision Date: SDS Number: Date of last issue: 01/26/2022 2.0 10/27/2023 000000520172 Date of first issue: 08/20/2020

products as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Solvents may degrease the skin.

Remarks : Health injuries are not known or expected under normal use.

The product has not been tested. The statements on toxicology have been derived from the properties of the individual

components.

according to the OSHA Hazard Communication Standard



MasterTop SRS 100PAS

Version 2.0

Revision Date: 10/27/2023

SDS Number: 000000520172

Date of last issue: 01/26/2022 Date of first issue: 08/20/2020

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Persistence and degradability

Product:

Biodegradability

Remarks: Taking into consideration the properties of several ingredients, the product is estimated not to be readily biodegradable according to OECD classification.

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Obse

Observe national and local legal requirements.

Disposal requirements are dependent on the hazard classification and will vary by location and the type of disposal se-

lected.

The use and processing of this product, or addition of other constituents, may cause it to be considered a hazardous

waste.

Residues should be disposed of in the same manner as the

substance/product.

Contaminated packaging : Contaminated packaging should be emptied as far as possi-

ble; then it can be passed on for recycling after being thor-

oughly cleaned.

Packs that cannot be cleaned should be disposed of in the

same manner as the contents.

according to the OSHA Hazard Communication Standard



MasterTop SRS 100PAS

Version Revision Date: SDS Number: Date of last issue: 01/26/2022 2.0 10/27/2023 000000520172 Date of first issue: 08/20/2020

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1866

Proper shipping name : RESIN SOLUTION

Class : 3
Packing group : II
Labels : 3
Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 1866
Proper shipping name : Resin solution

Class : 3 Packing group : II

Labels : Flammable Liquids

364

Packing instruction (cargo

aircraft)

Packing instruction (passen: 353

ger aircraft)

IMDG-Code

UN number : UN 1866

Proper shipping name : RESIN SOLUTION

Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-E
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1866
Proper shipping name : Resin solution

Class : 3 Packing group : II

Labels : FLAMMABLE LIQUID

ERG Code : 127 Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)

according to the OSHA Hazard Communication Standard



MasterTop SRS 100PAS

Version Revision Date: SDS Number: Date of last issue: 01/26/2022 2.0 10/27/2023 000000520172 Date of first issue: 08/20/2020

methyl methacrylate 80-62-6 1000 3333

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

methyl methacry- 80-62-6 >= 30 - < 50 %

late

US State Regulations

Pennsylvania Right To Know

methyl methacrylate 80-62-6

New Jersey Right To Know

methyl methacrylate 80-62-6

The ingredients of this product are reported in the following inventories:


TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

according to the OSHA Hazard Communication Standard



MasterTop SRS 100PAS

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01/26/2022

 2.0
 10/27/2023
 000000520172
 Date of first issue: 08/20/2020

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan): ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 10/27/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN