

## MasterTop SRS 71TC

Version 2.0      Revision Date: 03/29/2021      SDS Number: 000000260447      Date of last issue: 12/04/2020  
Date of first issue: 12/04/2020

---

**SECTION 1. IDENTIFICATION**

Product name : MasterTop SRS 71TC  
Product code : 000000000055585093 000000000055585093

**Manufacturer or supplier's details**

Company name of supplier : Master Builders-Construction Systems  
US, LLC  
Address : 23700 CHAGRIN BLVD  
Beachwood OH 44122  
Emergency telephone : ChemTel: +1-813-248-0585

**Recommended use of the chemical and restrictions on use**

Recommended use : Product for construction chemicals  
Restrictions on use : Reserved for industrial and professional use.

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Flammable liquids : Category 2  
Acute toxicity (Oral) : Category 4  
Skin corrosion/irritation : Category 2  
Skin sensitization : Category 1B  
Specific target organ toxicity : Category 3 (Respiratory system)  
- single exposure  
Specific target organ toxicity : Category 2 (Kidney)  
- repeated exposure (Oral)  
Short-term (acute) aquatic : Category 2  
hazard

**GHS label elements**

Hazard pictograms : 

Signal Word : Danger

## MasterTop SRS 71TC

Version	Revision Date:	SDS Number:	Date of last issue: 12/04/2020
2.0	03/29/2021	000000260447	Date of first issue: 12/04/2020

---

Hazard Statements : H225 Highly flammable liquid and vapor.  
H315 Causes skin irritation.  
H302 Harmful if swallowed.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.  
H373 May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.  
H401 Toxic to aquatic life.

Precautionary Statements : **Prevention:**  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe dusts or mists.  
P271 Use only outdoors or in a well-ventilated area.  
P243 Take action to prevent static discharges.  
P273 Avoid release to the environment.  
P241 Use explosion-proof electrical, ventilating and lighting equipment.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P270 Do not eat, drink or smoke when using this product.  
P264 Wash face, hands and any exposed skin thoroughly after handling.  
P240 Ground and bond container and receiving equipment.  
P242 Use only non-sparking tools.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P314 Get medical advice/ attention if you feel unwell.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
Rinse mouth.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.  
P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.

**Storage:**

P233 Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents/container to appropriate hazardous waste collection point.

## MasterTop SRS 71TC

Version 2.0      Revision Date: 03/29/2021      SDS Number: 000000260447      Date of last issue: 12/04/2020  
 Date of first issue: 12/04/2020

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : acrylic polymers  
 methacrylic ester

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
methyl methacrylate	80-62-6	>= 50 - < 75
1,4-butanediol dimethacrylate	2082-81-7	>= 5 - < 10
Dibutyl maleate	105-76-0	>= 5 - < 10
2-hydroxy-4-methoxybenzophenone	131-57-7	>= 1 - < 5
1,1'-(p-tolylimino)dipropan-2-ol	38668-48-3	>= 1 - < 5

**SECTION 4. FIRST AID MEASURES**

- General advice : First aid personnel should pay attention to their own safety.  
 Remove contaminated clothing.
- If inhaled : Remove the affected individual into fresh air and keep the person calm.  
 If breathing difficulties develop, aid in breathing and seek immediate medical attention.  
 If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : Wash thoroughly with soap and water  
 Under no circumstances should organic solvent be used.  
 If irritation develops, seek medical attention.
- In case of eye contact : Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
- If swallowed : Rinse mouth and then drink 200-300 ml of water.  
 Do not induce vomiting due to aspiration hazard.  
 Do not induce vomiting unless told to by a poison control center or doctor.
- Most important symptoms and effects, both acute and delayed : Harmful if swallowed.  
 Causes skin irritation.  
 May cause an allergic skin reaction.  
 May cause respiratory irritation.  
 May cause damage to organs through prolonged or repeated exposure.
- Notes to physician : Treat symptomatically.

**SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Dry powder

## MasterTop SRS 71TC

Version	Revision Date:	SDS Number:	Date of last issue: 12/04/2020
2.0	03/29/2021	000000260447	Date of first issue: 12/04/2020

---

- Alcohol-resistant foam
- Unsuitable extinguishing media : water jet
- Hazardous combustion products : harmful vapours  
nitrogen oxides  
fumes/smoke  
carbon black  
carbon oxides
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent spread over a wide area (e.g. by containment or oil barriers).  
Contain contaminated water/firefighting water.  
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).  
Use only explosion-proof equipment.  
Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapors/dust.  
Avoid exposure - obtain special instructions before use.

## MasterTop SRS 71TC

Version 2.0      Revision Date: 03/29/2021      SDS Number: 000000260447      Date of last issue: 12/04/2020  
 Date of first issue: 12/04/2020

Avoid contact with skin and eyes.  
 For personal protection see section 8.  
 Smoking, eating and drinking should be prohibited in the application area.  
 Take precautionary measures against static discharges.  
 Provide sufficient air exchange and/or exhaust in work rooms.  
 Open drum carefully as content may be under pressure.  
 Dispose of rinse water in accordance with local and national regulations.  
 Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Conditions for safe storage : no smoking  
 Keep container tightly closed in a dry and well-ventilated place.  
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
 Observe label precautions.  
 Electrical installations / working materials must comply with the technological safety standards.

Further information on storage conditions : Keep container tightly closed and in a well-ventilated place.  
 Keep away from heat.  
 Avoid all sources of ignition: heat, sparks, open flame.

Recommended storage temperature : < 77 °F / < 25 °C

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
methyl methacrylate	80-62-6	TWA value	50 ppm	ACGIHTLV
		STEL value	100 ppm	ACGIHTLV
		REL value	100 ppm 410 mg/m3	NIOSH
		PEL	100 ppm 410 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	100 ppm 410 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
		TWA	100 ppm 410 mg/m3	NIOSH REL
		TWA	100 ppm 410 mg/m3	OSHA Z-1
		TWA	100 ppm	OSHA P0

## MasterTop SRS 71TC

Version	Revision Date:	SDS Number:	Date of last issue: 12/04/2020
2.0	03/29/2021	000000260447	Date of first issue: 12/04/2020

		410 mg/m3	
--	--	-----------	--

**Engineering measures** : Ensure adequate ventilation.

**Personal protective equipment**

Respiratory protection : Wear appropriate certified respirator when exposure limits may be exceeded.

Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Safety glasses with side-shields.

Skin and body protection : Body protection must be chosen based on level of activity and exposure.  
Antistatic apron

Protective measures : Avoid inhalation of dusts/mists/vapours.  
Avoid contact with the skin, eyes and clothing.  
Avoid prolonged and/or repeated contact with the skin.  
Handle in accordance with good building materials hygiene and safety practice.

Hygiene measures : When using, do not eat, drink or smoke.  
Hands and/or face should be washed before breaks and at the end of the shift.  
At the end of the shift the skin should be cleaned and skin-care agents applied.  
Gloves must be inspected regularly and prior to each use.  
Replace if necessary (e.g. pinhole leaks).

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Color : light blue

Odor : sweetish, ester-like

Odor Threshold : not determined

pH : Not applicable

Melting point : No data available

Boiling point/boiling range : 214 °F / 101 °C

## MasterTop SRS 71TC

Version            Revision Date:            SDS Number:            Date of last issue: 12/04/2020  
2.0                03/29/2021              000000260447        Date of first issue: 12/04/2020

---

Flash point                         : 50 °F / 10 °C

Evaporation rate                    : No data available

Flammability (liquids)              : Highly flammable liquid and vapor.

Upper explosion limit / Upper  
flammability limit                    : 12.5 %(V)

Lower explosion limit / Lower  
flammability limit                    : 2.1 %(V)

Vapor pressure                      : approx. 40 hPa (68 °F / 20 °C)

Relative vapor density              : > 1 (68 °F / 20 °C)

Relative density                     : No data available

Density                              : approx. 1.0 g/cm<sup>3</sup> (68 °F / 20 °C)

Solubility(ies)

    Water solubility                 : approx. 20 g/l (68 °F / 20 °C)

    Solubility in other solvents     : No data available

Partition coefficient: n-  
octanol/water                        : No data available

Autoignition temperature          : not determined

Decomposition temperature         : Vapors may form explosive mixture with air.  
No decomposition if stored and handled as pre-  
scribed/indicated.

Viscosity

    Viscosity, dynamic                : 30 - 60 mPa.s (73 °F / 23 °C)

    Viscosity, kinematic             : No data available

Explosive properties                : Not explosive

Oxidizing properties                : Based on its structural properties the product is not classified  
as oxidizing.

Sublimation point                    : No data available

Molecular weight                    : No data available

Metal corrosion rate                : Corrosive effects to metal are not anticipated.

## MasterTop SRS 71TC

Version	Revision Date:	SDS Number:	Date of last issue: 12/04/2020
2.0	03/29/2021	000000260447	Date of first issue: 12/04/2020

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	No hazardous reactions if stored and handled as prescribed/indicated.
Chemical stability	:	The product is stable if stored and handled as prescribed/indicated.
Possibility of hazardous reactions	:	Vapors may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products if stored and handled as prescribed/indicated.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Harmful if swallowed.

**Product:**

Acute oral toxicity : ATE: 1,880 mg/kg

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/eye irritation**

Not classified based on available information.

**Respiratory or skin sensitization****Skin sensitization**

May cause an allergic skin reaction.

**Respiratory sensitization**

Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT-single exposure**

May cause respiratory irritation.

**STOT-repeated exposure**

May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.



## MasterTop SRS 71TC

Version	Revision Date:	SDS Number:	Date of last issue: 12/04/2020
2.0	03/29/2021	000000260447	Date of first issue: 12/04/2020

---

**Aspiration toxicity**

Not classified based on available information.

**Further information****Product:**

Remarks : Solvents may degrease the skin.

Remarks : The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Product:****Ecotoxicology Assessment**

Acute aquatic toxicity : Toxic to aquatic life.

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Observe national and local legal requirements. Residues should be disposed of in the same manner as the substance/product.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

---

## MasterTop SRS 71TC

Version      Revision Date:      SDS Number:      Date of last issue: 12/04/2020  
2.0          03/29/2021          000000260447      Date of first issue: 12/04/2020

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

UN number                    : UN 1866  
Proper shipping name        : RESIN SOLUTION  
Class                         : 3  
Packing group               : II  
Labels                        : 3

**IATA-DGR**

UN/ID No.                    : UN 1866  
Proper shipping name        : RESIN SOLUTION  
Class                         : 3  
Packing group               : II  
Labels                        : Flammable Liquids  
Packing instruction (cargo aircraft) : 364  
Packing instruction (passenger aircraft) : 353

**IMDG-Code**

UN number                    : UN 1866  
Proper shipping name        : RESIN SOLUTION  
  
Class                         : 3  
Packing group               : II  
Labels                        : 3  
EmS Code                     : F-E, S-E  
Marine pollutant             : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****49 CFR**

UN/ID/NA number            : UN 1866  
Proper shipping name        : RESIN SOLUTION  
  
Class                         : 3  
Packing group               : II  
Labels                        : FLAMMABLE LIQUID  
ERG Code                     : 127  
Marine pollutant             : no

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

**SECTION 15. REGULATORY INFORMATION****CERCLA Reportable Quantity**

## MasterTop SRS 71TC

Version 2.0      Revision Date: 03/29/2021      SDS Number: 000000260447      Date of last issue: 12/04/2020  
 Date of first issue: 12/04/2020

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
methyl methacrylate	80-62-6	1000	1666

**US State Regulations****Pennsylvania Right To Know**

methyl methacrylate

80-62-6

**New Jersey Right To Know**


methyl methacrylate

80-62-6

**The ingredients of this product are reported in the following inventories:**

DSL : All components of this product are on the Canadian DSL

TSCA : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

**SECTION 16. OTHER INFORMATION****Further information****NFPA 704:****HMIS® IV:**

<b>HEALTH</b>	<input type="text"/>	<input type="text"/>
<b>FLAMMABILITY</b>	<input type="text"/>	<input type="text"/>
<b>PHYSICAL HAZARD</b>	<input type="text"/>	<input type="text"/>

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

**Full text of other abbreviations**

29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)  
 29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000  
 ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
 ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)  
 NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)  
 NIOSH REL : USA. NIOSH Recommended Exposure Limits

## MasterTop SRS 71TC

Version	Revision Date:	SDS Number:	Date of last issue: 12/04/2020
2.0	03/29/2021	000000260447	Date of first issue: 12/04/2020

OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  
 OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  
 29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):  
 29 CFR 1910.1000 (Table Z-1) / PEL : Permissible exposure limit  
 ACGIH / TWA : 8-hour, time-weighted average  
 ACGIH / STEL : Short-term exposure limit  
 ACGIHTLV / STEL value : Short Term Exposure Limit (STEL):  
 ACGIHTLV / TWA value : Time Weighted Average (TWA):  
 NIOSH / REL value : Recommended exposure limit (REL):  
 NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek  
 OSHA P0 / TWA : 8-hour time weighted average  
 OSHA Z-1 / TWA : 8-hour time weighted average

AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 03/29/2021

**MasterTop SRS 71TC**

Version	Revision Date:	SDS Number:	Date of last issue: 12/04/2020
2.0	03/29/2021	000000260447	Date of first issue: 12/04/2020

---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN