

MasterTop TC 504 light tan PART A

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/08/2020 000000260708 Date of first issue: 10/08/2020

SECTION 1. IDENTIFICATION

Product name : MasterTop TC 504 light tan PART A

Product code : 00000000051651138 00000000051651138

Manufacturer or supplier's details

Company name of supplier : Master Builders-Construction Systems

US, LLC

Address : 23700 CHAGRIN BLVD

Beachwood OH 44122

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

FLAMMABLE LIQUIDS : Category 4

Skin corrosion/irritation : Category 2

Serious eye damage/eye

irritation

Category 2A

Skin sensitization : Category 1A

Short-term (acute) aquatic

hazard

Category 2

Long-term (chronic) aquatic

hazard

Category 2

GHS label elements

Hazard pictograms





Signal Word : Warning

Hazard Statements : H227 Combustible liquid.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.



Version Revision Date: SDS Number: Date of last issue: -

1.0 10/08/2020 000000260708 Date of first issue: 10/08/2020

H401 Toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements : __

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P273 Avoid release to the environment.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P272 Contaminated work clothing should not be allowed out of the workplace.

P264 Wash face, hands and any exposed skin thoroughly after handling.

Response:

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.

P333 + P311 If skin irritation or rash occurs: Call a POISON CENTER or doctor/physician.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

P337 + P311 If eye irritation persists: Call a POISON CENTER or doctor/physician.

P370 + P378 In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish.

Storage:

P403 Store in a well-ventilated place.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

No data available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : No data available.

Components

Chemical name	CAS-No.	Concentration (% w/w)
bisphenol A-epichlorohydrin resin	25068-38-6	>= 25 - < 50
Quartz (SiO2)	14808-60-7	>= 20 - < 25
1-methoxypropan-2-ol	107-98-2	>= 3 - < 5
oxirane, mono[(C12-14-	68609-97-2	>= 0.3 - < 1



Version Revision Date: SDS Number: Date of last issue: -

1.0 10/08/2020 000000260708 Date of first issue: 10/08/2020

alkyloxy)methyl] derivs.		
1,6-hexanediol diacrylate	13048-33-4	>= 0 - < 1
Limestone	1317-65-3	>= 10 - < 25
Titanium dioxide	13463-67-7	>= 3 - < 7

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety.

If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position).

Immediately remove contaminated clothing.

Move out of dangerous area.

Show this material safety data sheet to the doctor in attend-

ance.

Do not leave the victim unattended.

If inhaled : Keep patient calm, remove to fresh air, seek medical atten-

tion.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : Immediately wash thoroughly with soap and water, seek med-

ical attention.

If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Wash affected eyes for at least 15 minutes under running

water with eyelids held open, consult an eye specialist.

Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention.

Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms

and effects, both acute and

delayed

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Notes to physician : Treat symptomatically.

Version **Revision Date:** SDS Number: Date of last issue: -

000000260708 Date of first issue: 10/08/2020 1.0 10/08/2020

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Foam Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

tive equipment and emer-

gency procedures

Personal precautions, protec- : Use personal protective equipment.

Environmental precautions Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Product is not explosive.

Do not spray on a naked flame or any incandescent material. Keep away from open flames, hot surfaces and sources of

ignition.

Advice on safe handling Avoid formation of aerosol.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/08/2020 000000260708 Date of first issue: 10/08/2020

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage : no smoking

Keep in a well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.

Protect from direct sunlight.

Materials to avoid : Observe VCI storage rules.

Further information on stor-

age stability

No data available

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1-methoxypropan-2-ol	107-98-2	TWA value	50 ppm	ACGIHTLV
		STEL value	100 ppm	ACGIHTLV
		REL value	100 ppm 360 mg/m3	NIOSH
		STEL value	150 ppm 540 mg/m3	NIOSH
		TWA value	100 ppm 360 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		STEL value	150 ppm 540 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	50 ppm	ACGIH
		STEL	100 ppm	ACGIH
		ST	150 ppm 540 mg/m3	NIOSH REL
		TWA	100 ppm 360 mg/m3	NIOSH REL



MasterTop TC 504 light tan PART A

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/08/2020 000000260708 Date of first issue: 10/08/2020

		TWA	100 ppm 360 mg/m3	OSHA P0
		STEL	150 ppm 540 mg/m3	OSHA P0
Limestone	1317-65-3	REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium car- bonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium car- bonate)	NIOSH REL
Titanium dioxide	13463-67-7	TWA value	10 mg/m3	ACGIHTLV
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (Total dust)	10 mg/m3	OSHA P0
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH
Quartz (SiO2)	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m3	ACGIHTLV
		TWA value	0.05 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050



MasterTop TC 504 light tan PART A

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/08/2020 000000260708 Date of first issue: 10/08/2020

OSHA Action level	0.025 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
REL value (Respirable dust)	0.05 mg/m3	NIOSH
TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
PEL (respir- able)	0.05 mg/m3	OSHA CARC
TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL

Engineering measures : No applicable information available.

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the occupa-

tional exposure limits they must use appropriate certified

respirators.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using do not eat or drink.

When using do not smoke.



MasterTop TC 504 light tan PART A

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/08/2020 000000260708 Date of first issue: 10/08/2020

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : pigmented

Odor : aromatic, mild

Odor Threshold : No data available

pH : neutral to slightly alkaline

Melting point : No applicable information available.

Boiling point : 325 °F / 163 °C

Flash point : 165 °F / 74 °C

Method: Standard Method of Test for Flash Point by Setaflash

Closed Tester, closed cup

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not determined

Upper explosion limit / Upper

flammability limit

No data available.

Lower explosion limit / Lower

flammability limit

No data available.

Vapor pressure : No data available.

Relative vapor density : Heavier than air.

Relative density : 1.57

Density : approx. 1.0 g/cm3 (68 °F / 20 °C)

Bulk density : not applicable

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : insoluble

Partition coefficient: n-

octanol/water

No data available.



MasterTop TC 504 light tan PART A

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/08/2020 000000260708 Date of first issue: 10/08/2020

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No data available.

Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive

Not explosive

Oxidizing properties : Based on its structural properties the product is not classified

as oxidizing.

Sublimation point : No applicable information available.

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

ions

No decomposition if stored and applied as directed.

Vapors may form explosive mixture with air.

Conditions to avoid : Avoid all sources of ignition: heat, sparks, open flame.

Heat, flames and sparks.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

Traces of the substances/groups of substances are released

as decomposition products of the dry substance.

carbon oxides nitrogen oxides Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No applicable information available.



MasterTop TC 504 light tan PART A

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/08/2020 000000260708 Date of first issue: 10/08/2020

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : May cause irreversible eye damage.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Product:

Remarks : Causes sensitization.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration hazard expected.

Further information

Product:

Remarks : No data available

MBCC GROUP

MasterTop TC 504 light tan PART A

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/08/2020 000000260708 Date of first issue: 10/08/2020

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

bisphenol A-epichlorohydrin resin:

Toxicity to fish : LC50 (Oryzias latipes): 1.41 mg/l

Exposure time: 96 h Test Type: semistatic

Method: Acute toxicity testing with Fish, semistatic procedure (Method: Japanese Industrial Standard: Testing methods for

industrial wastewater)

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (daphnia): 1 - 10 mg/l

Remarks: Information taken from reference works and the

literature.

EC50 (Daphnia magna): 12 mg/l

Exposure time: 48 h Test Type: static

Method: Daphnia test acute

Toxicity to algae/aquatic

plants

EC50 (green algae): 9.1 mg/l

Exposure time: 96 h Test Type: static

Method: Algal growth inhibition test

Toxicity to daphnia and other

aquatic invertebrates (Chron-

ic toxicity)

No observed effect concentration (Daphnia magna): 0.3 mg/l

End point: Reproduction rate

Exposure time: 21 d Test Type: semistatic

Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50 (activated sludge): > 100 mg/l

Test Type: aquatic

Remarks: Information taken from reference works and the

literature.

Persistence and degradability

Components:

bisphenol A-epichlorohydrin resin:

Biodegradability : aerobic

Inoculum: Inoculum conforming to MITI requirements (OECD

301C)

Biodegradation: 0 % Exposure time: 28 d

Method: MITI-Test (I), ready



Version Revision Date: SDS Number: Date of last issue: -

1.0 10/08/2020 000000260708 Date of first issue: 10/08/2020

Bioaccumulative potential

Components:

bisphenol A-epichlorohydrin resin:

Bioaccumulation : Remarks: Because of the n-octanol/water distribution coeffi-

cient (log Pow) accumulation in organisms is possible. Information taken from reference works and the literature.

Partition coefficient: n-

octanol/water

log Pow: > 3

Quartz (SiO2):

Partition coefficient: n-

octanol/water

Remarks: not applicable

1-methoxypropan-2-ol:

Partition coefficient: n-

octanol/water

log Pow: -0.43 (77 °F / 25 °C) Method: other (measured)

GLP: no

Remarks: Information taken from reference works and the

literature.

1,6-hexanediol diacrylate:

Partition coefficient: n-

octanol/water

log Pow: 2.81 (77 °F / 25 °C) Method: other (measured)

Titanium dioxide:

Partition coefficient: n-

octanol/water

Remarks: not applicable

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Dispose of in accordance with national, state and local regula-

tions.

Do not discharge into drains/surface waters/groundwater.



Version Revision Date: SDS Number: Date of last issue: -

1.0 10/08/2020 000000260708 Date of first issue: 10/08/2020

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

US State Regulations

Pennsylvania Right To Know

 1-methoxypropan-2-ol
 107-98-2

 Limestone
 1317-65-3

 Titanium dioxide
 13463-67-7

 Quartz (SiO2)
 14808-60-7

New Jersey Right To Know

 1-methoxypropan-2-ol
 107-98-2

 Limestone
 1317-65-3

 Titanium dioxide
 13463-67-7

California Prop. 65

WARNING: This product can expose you to chemicals including 2,3-epoxypropyl phenyl ether, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory


SECTION 16. OTHER INFORMATION

Further information

Version **Revision Date:** SDS Number: Date of last issue: -

10/08/2020 000000260708 Date of first issue: 10/08/2020 1.0

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1910.1000

29 CFR 1910.1001-1050 OSHA - Specifically Regulated Substances (29 CFR

1910.1001-1050)

ACGIH USA. ACGIH Threshold Limit Values (TLV)

ACGIHTLV American Conference of Governmental Industrial Hygienists -

threshold limit values (US)

NIOSH Pocket Guide to Chemical Hazards (US) NIOSH **NIOSH REL** USA. NIOSH Recommended Exposure Limits

OSHA CARC OSHA Specifically Regulated Chemicals/Carcinogens OSHA_{P0} USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

29 CFR 1910.1000 (Table Z- : Short Term Exposure Limit (STEL):

1-A) / STEL value

29 CFR 1910.1000 (Table Z- : Time Weighted Average (TWA):

1-A) / TWA value

Permissible exposure limit 29 CFR 1910.1000 (Table Z- :

1) / PEL

29 CFR 1910.1001-1050 / OSHA Action level:

OSHA Action level

29 CFR 1910.1001-1050 / Time Weighted Average (TWA):

TWA value ACGIH / TWA 8-hour, time-weighted average Short-term exposure limit

ACGIH / STEL ACGIHTLV / STEL value Short Term Exposure Limit (STEL): ACGIHTLV / TWA value Time Weighted Average (TWA):

Recommended exposure limit (REL): NIOSH / REL value



Version Revision Date: SDS Number: Date of last issue: -

1.0 10/08/2020 000000260708 Date of first issue: 10/08/2020

NIOSH / STEL value : Short Term Exposure Limit (STEL):

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA P0 / TWA : 8-hour time weighted average
OSHA P0 / STEL : Short-term exposure limit
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ -Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

Revision Date : 10/08/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of



Version Revision Date: SDS Number: Date of last issue: -

1.0 10/08/2020 000000260708 Date of first issue: 10/08/2020

our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN