

# **COLOR COAT TB CLEAR**

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/01/2020 000000260320 Date of first issue: 10/01/2020

**SECTION 1. IDENTIFICATION** 

Product name : COLOR COAT TB CLEAR

Product code : 00000000051666402 00000000051666402

Manufacturer or supplier's details

Company name of supplier : Master Builders-Construction Systems

US, LLC

Address : 23700 CHAGRIN BLVD

Beachwood OH 44122

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals

Restrictions on use : Reserved for industrial and professional use.

# **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with 29 CFR 1910.1200

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity

- repeated exposure

Category 2 (Kidney)

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 2 (Kidney, Immune system)

Specific target organ toxicity

- repeated exposure (Inhala-

tion)

Category 1

Short-term (acute) aquatic

Short-te hazard

Category 1

Long-term (chronic) aquatic

hazard

Category 1

**GHS** label elements

Hazard pictograms









## **COLOR COAT TB CLEAR**

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/01/2020 000000260320 Date of first issue: 10/01/2020

Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.

H350 May cause cancer.

H373 May cause damage to organs through prolonged or re-

peated exposure.

H372 Causes damage to organs through prolonged or repeated

exposure if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Precautionary Statements :

Prevention:

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

P201 Obtain special instructions before use.

P273 Avoid release to the environment.

P260 Do not breathe dust or mist.

P202 Do not handle until all safety precautions have been read

and understood.

P270 Do not eat, drink or smoke when using this product.

P264 Wash face, hands and any exposed skin thoroughly after

handling.

P272 Contaminated work clothing should not be allowed out of

the workplace.

Response:

P314 Get medical advice/ attention if you feel unwell.

P308 + P311 IF exposed or concerned: Call a POISON

CENTER/ doctor.

P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap

and water.

P391 Collect spillage.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to appropriate hazardous

waste collection point.

Other hazards

No data available.

## **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

### Components

Chemical name	CAS-No.	Concentration (% w/w)
ethyleneglycol	107-21-1	>= 1 - < 3
Quartz (SiO2)	14808-60-7	>= 1 - < 5
3-iodo-2-propynyl butylcarbamate; 3-	55406-53-6	>= 0 - < 0.1
liodoprop-2-vn-1-vl butvlcarbamate		



## **COLOR COAT TB CLEAR**

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/01/2020 000000260320 Date of first issue: 10/01/2020

**SECTION 4. FIRST AID MEASURES** 

General advice : Move out of dangerous area.

Show this material safety data sheet to the doctor in attend-

ance.

Do not leave the victim unattended.

If inhaled : Consult a physician after significant exposure.

If unconscious, place in recovery position and seek medical

advice.

In case of skin contact : If on skin, rinse well with water.

In case of eye contact : Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Induce vomiting immediately and call a physician.

Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms

and effects, both acute and

delayed

May cause an allergic skin reaction.

May cause cancer.

Causes damage to organs through prolonged or repeated

exposure if inhaled.

May cause damage to organs through prolonged or repeated

exposure.

Notes to physician : Treat symptomatically.

**SECTION 5. FIRE-FIGHTING MEASURES** 

Suitable extinguishing media : Water spray

Foam Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

## **COLOR COAT TB CLEAR**

Version **Revision Date:** SDS Number: Date of last issue: -

10/01/2020 000000260320 Date of first issue: 10/01/2020 1.0

Further information Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment :

for fire-fighters

Wear self-contained breathing apparatus for firefighting if nec-

essary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Use personal protective equipment.

Ensure adequate ventilation.

Environmental precautions Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling Avoid formation of aerosol.

Do not breathe vapors/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Conditions for safe storage Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Further information on stor-

age conditions

Keep only in the original container in a cool, dry, well-

ventilated place away from ignition sources, heat or flame.



# **COLOR COAT TB CLEAR**

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/01/2020 000000260320 Date of first issue: 10/01/2020

Protect from direct sunlight.

Materials to avoid : No applicable information available.

Recommended storage tem: :

perature

32 °F / 0 °C

Further information on stor-

age stability

Minimum storage temperature:

### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethyleneglycol	107-21-1	TWA value (Vapor frac- tion)	25 ppm	ACGIHTLV
		STEL value (Vapor frac- tion)	50 ppm	ACGIHTLV
		STEL value (Aerosol, inhalable.)	10 mg/m3	ACGIHTLV
		TWA (Vapor)	25 ppm	ACGIH
		STEL (Va- por)	50 ppm	ACGIH
		STEL (Inhalable fraction, Aerosol only)	10 mg/m3	ACGIH
		С	50 ppm 125 mg/m3	OSHA P0
Quartz (SiO2)	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m3	ACGIHTLV
		TWA value	0.05 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
		OSHA Action level	0.025 mg/m3 (Respirable dust)	29 CFR 1910.1001- 1050
		REL value (Respirable dust)	0.05 mg/m3	NIOSH
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (respir-	0.1 mg/m3	OSHA P0



# **COLOR COAT TB CLEAR**

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/01/2020 000000260320 Date of first issue: 10/01/2020

able dust fraction)		
TWA (Respirable particulate matter)	0.025 mg/m3 (Silica)	ACGIH
PEL (respir- able)	0.05 mg/m3	OSHA CARC
TWA (Respirable dust)	0.05 mg/m3 (Silica)	NIOSH REL

**Engineering measures** : No applicable information available.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits

may be exceeded.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water

Tightly fitting safety goggles

Skin and body protection : Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Color : opaque

Odor : ammonia-like

Odor Threshold : No data available

pH : slightly alkaline

# **MBCC** GROUP

# **COLOR COAT TB CLEAR**

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/01/2020 000000260320 Date of first issue: 10/01/2020

Melting point : No applicable information available.

Boiling point : 212 °F / 100 °C

Flash point : 200.01 °F / 93.34 °C

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not highly flammable

Method: derived from flash point

Upper explosion limit / Upper

flammability limit

No data available.

Lower explosion limit / Lower

flammability limit

No data available.

Vapor pressure : No data available.

Relative vapor density : No data available.

Relative density : No data available.

Density : approx. 1.0 g/cm3 (68  $^{\circ}$ F / 20  $^{\circ}$ C)

Bulk density : not applicable

Solubility(ies)

Water solubility : partly soluble

Solubility in other solvents : partly soluble

Partition coefficient: n-

octanol/water

No data available.

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as pre-

scribed/indicated.

Viscosity

Viscosity, dynamic : No data available.

Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive

Not explosive

Oxidizing properties : Based on its structural properties the product is not classified

as oxidizing.

Sublimation point : No applicable information available.



## **COLOR COAT TB CLEAR**

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/01/2020 000000260320 Date of first issue: 10/01/2020

Molecular weight : No data available

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids

Strong bases

Strong oxidizing agents Strong reducing agents

Hazardous decomposition

products

No hazardous decomposition products if stored and handled

as prescribed/indicated.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

# **Acute toxicity**

Not classified based on available information.

**Product:** 

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

## Skin corrosion/irritation

Not classified based on available information.

**Product:** 

Remarks : May cause skin irritation and/or dermatitis.

## Serious eye damage/eye irritation

Not classified based on available information.

**Product:** 

Remarks : Vapors may cause irritation to the eyes, respiratory system

and the skin.

### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.



# **COLOR COAT TB CLEAR**

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/01/2020 000000260320 Date of first issue: 10/01/2020

#### **Respiratory sensitization**

Not classified based on available information.

**Product:** 

Remarks : Causes sensitization.

### Germ cell mutagenicity

Not classified based on available information.

### Carcinogenicity

May cause cancer.

## Reproductive toxicity

Not classified based on available information.

### STOT-single exposure

Not classified based on available information.

# STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure if inhaled.

May cause damage to organs through prolonged or repeated exposure.

#### **Aspiration toxicity**

Not classified based on available information.

#### **Product:**

No aspiration hazard expected.

#### **Further information**

Product:

Remarks : No data available

### **SECTION 12. ECOLOGICAL INFORMATION**

### **Ecotoxicity**

No data available

### Persistence and degradability

No data available

Bioaccumulative potential

#### **Components:**

ethyleneglycol:

Partition coefficient: n- : log Pow: approx. -1.36 (73 °F / 23 °C) octanol/water : Method: Calculation Hansch/Leo

GLP: no data

Remarks: Information taken from reference works and the

literature.

Quartz (SiO2):

Partition coefficient: n- : Remarks: not applicable



## **COLOR COAT TB CLEAR**

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/01/2020 000000260320 Date of first issue: 10/01/2020

octanol/water

3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate:

Partition coefficient: n- : log Pow: 2.81 (77 °F / 25 °C)

octanol/water Method: Partition coefficient (n-octanol/water), Shake-flask

method GLP: yes

N'-tert-Butyl-N-cyclopropyl-6-(methylthio)-1,3,5-triazine-2,4-diamine:

Partition coefficient: n- : log Pow: 2.8 (68 °F / 20 °C)

octanol/water Method: Partition coefficient (n-octanol/water), HPLC method.

GLP: yes

2-(Hydroxymethylamino)ethanol:

Partition coefficient: n- : log Pow: -2.205

octanol/water Method: other (calculated)

GLP: no data

Mobility in soil
No data available

Other adverse effects

**Product:** 

Additional ecological infor-

mation

An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Very toxic to aquatic life.

Very toxic to aquatic life with long lasting effects.

**SECTION 13. DISPOSAL CONSIDERATIONS** 

**Disposal methods** 

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Dispose of in accordance with national, state and local regula-

tions.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the sub-

stance/product.

**SECTION 14. TRANSPORT INFORMATION** 

International Regulations

**UNRTDG** 

Not regulated as a dangerous good

IATA-DGR



# **COLOR COAT TB CLEAR**

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/01/2020 000000260320 Date of first issue: 10/01/2020

Not regulated as a dangerous good

**IMDG-Code** 

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

**Domestic regulation** 

**49 CFR** 

Not regulated as a dangerous good

#### **SECTION 15. REGULATORY INFORMATION**

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

ethyleneglycol 107-21-1

**US State Regulations** 

Pennsylvania Right To Know

ethyleneglycol 107-21-1 Quartz (SiO2) 14808-60-7

**New Jersey Right To Know** 

ethyleneglycol 107-21-1

California Prop. 65

WARNING: This product can expose you to chemicals including benzophenone, which is/are known to the State of California to cause cancer, and

ethyleneglycol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory

## **SECTION 16. OTHER INFORMATION**


## **Further information**

# **COLOR COAT TB CLEAR**

Version **Revision Date:** SDS Number: Date of last issue: -

10/01/2020 000000260320 Date of first issue: 10/01/2020 1.0

#### NFPA 704:



Special hazard

#### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

29 CFR 1910.1001-1050 OSHA - Specifically Regulated Substances (29 CFR

1910.1001-1050)

USA. ACGIH Threshold Limit Values (TLV) **ACGIH** 

American Conference of Governmental Industrial Hygienists -**ACGIHTLV** 

threshold limit values (US)

NIOSH Pocket Guide to Chemical Hazards (US) NIOSH NIOSH REL USA. NIOSH Recommended Exposure Limits

**OSHA CARC** OSHA Specifically Regulated Chemicals/Carcinogens USA. OSHA - TABLE Z-1 Limits for Air Contaminants -OSHA<sub>P0</sub>

1910.1000

OSHA Z-1 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-3 USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

Time Weighted Average (TWA):

eral Dusts OSHA Action level:

29 CFR 1910.1001-1050 / 29 CFR 1910.1001-1050 /

OSHA Action level

TWA value

ACGIH / TWA 8-hour, time-weighted average Short-term exposure limit ACGIH / STEL

Short Term Exposure Limit (STEL): ACGIHTLV / STEL value ACGIHTLV / TWA value Time Weighted Average (TWA): Recommended exposure limit (REL): NIOSH / REL value

Time-weighted average concentration for up to a 10-hour NIOSH REL / TWA

workday during a 40-hour workweek

OSHA CARC / PEL Permissible exposure limit (PEL) OSHA P0 / TWA 8-hour time weighted average

OSHA P0 / C Ceiling limit

OSHA Z-1 / TWA 8-hour time weighted average OSHA Z-3 / TWA 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensa-



# **COLOR COAT TB CLEAR**

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/01/2020 000000260320 Date of first issue: 10/01/2020

tion, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB -Very Persistent and Very Bioaccumulative

Revision Date : 10/01/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE



# **COLOR COAT TB CLEAR**

Version Revision Date: SDS Number: Date of last issue: -

1.0 10/01/2020 000000260320 Date of first issue: 10/01/2020

CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN