

EZ Grip

Fast setting dry-mix polymer adhesive

PACKAGING

22.6 kg per 19-liter pail
(50 lbs per 5-gallon pail)

COVERAGE

(Approximate) 25.5–30.1 m²
(275–325 ft²) per pail

DESCRIPTION

Water-based, non-cementitious, translucent white adhesive, ready to use directly from the pail.

USES

1. For use with the Senerflex Wall System to adhere expanded polystyrene insulation board to the following acceptable substrates: ASTM C1177 type sheathings, including DensGlass™ exterior sheathing, eXP™ sheathing, GlasRoc® sheathing, Securock™ glass-mat sheathing, Weather Defense™ Platinum sheathing, GreenGlass® sheathing, PermaBase™ cement-board by National Gypsum and other cement-boards (ASTM C1325 Type A Exterior), Untreated Exposure I or exterior plywood sheathing (grade C-D or better), Untreated Exposure I OSB, gypsum sheathing (ASTM C79/ASTM C1396), poured concrete/unit masonry.

2. Used with Pebbletex Pressure Equalized Design to coat both edges of all closure blocks.

Note: EZ Grip is not acceptable for adhering EPS to EPS in any application or for embedding mesh in any application.

MIXING

1. Mix the contents of the EZ Grip pail with a low speed drill and paddle mixer until thoroughly blended.
2. Additives are not permitted.
3. Close container when not in use.
4. Clean tools with soap and water immediately after use.

FEATURES	BENEFITS
Ready to use	No need to add cement
Butter-like consistency	Spreads with minimum effort, offers best coverage of non-cementitious adhesives
Resealable	Produces minimal waste
Excellent adhesion to wood-based sheathings	Ideal for light commercial projects using wood sheathing
Water based	Safe, non-toxic, clean up easily with soap and water

APPLICATION

Apply mixed EZ Grip to entire surface of insulation board using a stainless steel trowel with 5 mm x 5 mm (3/16"x 3/16") notches spaced 5 mm (3/16") apart. Additional EZ Grip may be required over uneven substrates to ensure proper adhesion occurs. During the application process, periodically check the EPS insulation board for proper adhesion and apply additional EZ Grip as needed.

Note: The ribbon & dab method is not an acceptable method when using EZ Grip.

LIMITATIONS

1. Protect Finestone materials during transportation and storage.
 2. Store Finestone materials in a cool, dry place protected from freezing. Store at no less than 4 °C (40 °F). Protect from extreme heat and direct sunlight. Shelf life is two years when unopened and stored as directed.
 3. Do not apply Finestone materials in ambient temperatures below 4 °C (40 °F). Provide supplementary heat during installation and drying period (at least 24 hours after installation and until dry) when temperatures less than 4 °C (40 °F) prevail.
 4. Do not apply Finestone materials to frozen surfaces.
-

HEALTH, SAFETY AND ENVIRONMENTAL

Read, understand and follow all Safety Data Sheets and product label information for this product prior to use. The SDS can be obtained by visiting finestone.master-builders-solutions.com/en, e-mailing your request to mbsbscst@mbcc-group.com or calling +1 (800) 433-9517. Use only as directed.

IN CASE OF EMERGENCY: Call CHEMTEL +1 (800) 255-3924 or if outside the US or Canada, +1 (813) 248-0585.

TECHNICAL SUPPORT

Consult Master Builders Solutions Technical Services Department at +1 (800) 589-1336 for specific recommendations concerning all other applications. Consult the Wall Systems website at finestone.master-builders-solutions.com/en, for additional information about products and systems and for updated literature.

LIMITED WARRANTY NOTICE

Master Builders Solutions Construction Systems US, LLC ("Master Builders") warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. MASTER BUILDERS MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of Master Builders. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. MASTER BUILDERS WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders' present knowledge and experience. However, Master Builders assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

FOR PROFESSIONAL USE ONLY. NOT FOR SALE TO OR USE BY THE GENERAL PUBLIC.

For the most current version of this literature, please visit our website at finestone.master-builders-solutions.com/en.