

SENERGY ASAP TB DEEP

Version 1.0 Revision Date: 10/07/2020 SDS Number: 000000260318 Date of last issue: -
Date of first issue: 10/07/2020

SECTION 1. IDENTIFICATION

Product name : SENERGY ASAP TB DEEP
Product code : 000000000051657869 000000000051657869

Manufacturer or supplier's details

Company name of supplier : Master Builders-Construction Systems
US, LLC
Address : 23700 CHAGRIN BLVD
Beachwood OH 44122
Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with 29 CFR 1910.1200**

Specific target organ toxicity : Category 2 (Kidney)
- repeated exposure

Short-term (acute) aquatic hazard : Category 3

Long-term (chronic) aquatic hazard : Category 3

GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H373 May cause damage to organs (Kidney) through prolonged or repeated exposure.
H402 Harmful to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**
P273 Avoid release to the environment.
P260 Do not breathe dust or mist.

SENERGY ASAP TB DEEP

Version 1.0 Revision Date: 10/07/2020 SDS Number: 000000260318 Date of last issue: -
 Date of first issue: 10/07/2020

Response:

P314 Get medical advice/ attention if you feel unwell.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

No data available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**Components**

Chemical name	CAS-No.	Concentration (% w/w)
ethyleneglycol	107-21-1	>= 1 - < 3
Poly(oxy-1,2-ethanediyl), .alpha.- [(1,1,3,3-tetramethylbutyl)phenyl]- .omega.-hydroxy-	9036-19-5	>= 0.1 - < 0.2
diuron	330-54-1	>= 0 - < 0.1
3-iodo-2-propynyl butylcarbamate; 3- iodoprop-2-yn-1-yl butylcarbamate	55406-53-6	>= 0 - < 0.1
Quartz (SiO ₂)	14808-60-7	>= 0 - < 1
Limestone	1317-65-3	>= 15 - < 50

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
 Show this material safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
 If symptoms persist, call a physician.
- In case of skin contact : After contact with skin, wash immediately with plenty of water and soap.
 Under no circumstances should organic solvent be used.
 If irritation develops, seek medical attention.
- In case of eye contact : Flush eyes with water as a precaution.
 Remove contact lenses.
 Protect unharmed eye.
 Keep eye wide open while rinsing.
 If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
 Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.
 Take victim immediately to hospital.

SENERGY ASAP TB DEEP

Version 1.0 Revision Date: 10/07/2020 SDS Number: 000000260318 Date of last issue: -
Date of first issue: 10/07/2020

Most important symptoms and effects, both acute and delayed : None known.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Foam
Dry powder
Carbon dioxide (CO₂)

Unsuitable extinguishing media : High volume water jet

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Do not breathe vapour/aerosol/spray mists.
Wear eye/face protection.
If exposed to high vapour concentration, leave area immediately.
Use personal protective clothing.
Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Product is not explosive.

Normal measures for preventive fire protection.

SENERGY ASAP TB DEEP

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/07/2020	000000260318	Date of first issue: 10/07/2020

- Advice on safe handling : Do not breathe vapors/dust.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
Protect from direct sunlight.
- Materials to avoid : Observe VCI storage rules.
- Recommended storage temperature : 32 °F / 0 °C
- Further information on storage stability : Minimum storage temperature:

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
ethyleneglycol	107-21-1	TWA value (Vapor fraction)	25 ppm	ACGIHTLV
		STEL value (Vapor fraction)	50 ppm	ACGIHTLV
		STEL value (Aerosol, inhalable.)	10 mg/m3	ACGIHTLV
		TWA (Vapor)	25 ppm	ACGIH
		STEL (Vapor)	50 ppm	ACGIH
		STEL (Inhalable fraction, Aerosol only)	10 mg/m3	ACGIH
		C	50 ppm 125 mg/m3	OSHA P0
diuron	330-54-1	TWA value	10 mg/m3	ACGIHTLV
		REL value	10 mg/m3	NIOSH
		TWA value	10 mg/m3	29 CFR 1910.1000

SAFETY DATA SHEET

SENERGY ASAP TB DEEP

Version 1.0 Revision Date: 10/07/2020 SDS Number: 000000260318 Date of last issue: -
 Date of first issue: 10/07/2020

				(Table Z-1-A)
		TWA	10 mg/m3	ACGIH
		TWA	10 mg/m3	NIOSH REL
		TWA	10 mg/m3	OSHA P0
Limestone	1317-65-3	REL value (Respirable)	5 mg/m3	NIOSH
		REL value (Total)	10 mg/m3	NIOSH
		PEL (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1)
		PEL (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value (Respirable fraction)	5 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA value (Total dust)	15 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable)	5 mg/m3 (Calcium carbonate)	NIOSH REL
		TWA (total)	10 mg/m3 (Calcium carbonate)	NIOSH REL
Quartz (SiO2)	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m3	ACGIHTLV
		TWA value	0.05 mg/m3 (Respirable dust)	29 CFR 1910.1001-1050
		OSHA Action level	0.025 mg/m3 (Respirable dust)	29 CFR 1910.1001-1050
		REL value (Respirable dust)	0.05 mg/m3	NIOSH
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (respir-	0.1 mg/m3	OSHA P0

SENERGY ASAP TB DEEP

Version 1.0 Revision Date: 10/07/2020 SDS Number: 000000260318 Date of last issue: -
 Date of first issue: 10/07/2020

		able dust fraction)		
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH
		PEL (respirable)	0.05 mg/m ³	OSHA CARC
		TWA (Respirable dust)	0.05 mg/m ³ (Silica)	NIOSH REL
crystalline silica	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m ³	ACGIHTLV
		REL value (Respirable dust)	0.05 mg/m ³	NIOSH
		TWA value	0.05 mg/m ³ (Respirable dust)	29 CFR 1910.1001-1050
		OSHA Action level	0.025 mg/m ³ (Respirable dust)	29 CFR 1910.1001-1050
		TWA (Respirable dust)	0.05 mg/m ³	OSHA Z-1
		TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m ³	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH
		PEL (respirable)	0.05 mg/m ³	OSHA CARC
		TWA (Respirable dust)	0.05 mg/m ³ (Silica)	NIOSH REL

Engineering measures : No applicable information available.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits may be exceeded.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

SENERGY ASAP TB DEEP

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/07/2020	000000260318	Date of first issue: 10/07/2020

- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Protective measures : Do not inhale gases/vapours/aerosols.
Avoid contact with the skin, eyes and clothing.
Avoid exposure - obtain special instructions before use.
Handle in accordance with good building materials hygiene and safety practice.
Wearing of closed work clothing is recommended.
- Hygiene measures : Wash hands before breaks and at the end of workday.
-

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Color : opaque
- Odor : ammonia-like
- Odor Threshold : No data available
- pH : slightly alkaline
- Melting point : No applicable information available.
- Boiling point : 212 °F / 100 °C
- Flash point : 392 °F / 200 °C
- Evaporation rate : No applicable information available.
- Flammability (solid, gas) : No applicable information available.
- Upper explosion limit / Upper flammability limit : No data available.
- Lower explosion limit / Lower flammability limit : No data available.
- Vapor pressure : No data available.
- Relative vapor density : No data available.
- Relative density : No data available.
- Density : approx. 1.0 g/cm³ (68 °F / 20 °C)
- Bulk density : not applicable
-

SENERGY ASAP TB DEEP

Version 1.0 Revision Date: 10/07/2020 SDS Number: 000000260318 Date of last issue: -
Date of first issue: 10/07/2020

Solubility(ies)
Water solubility : partly soluble

Solubility in other solvents : partly soluble

Partition coefficient: n-octanol/water : No data available.

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity
Viscosity, dynamic : No data available.

Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive
Not explosive

Oxidizing properties : Based on its structural properties the product is not classified as oxidizing.

Sublimation point : No applicable information available.

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids
Strong bases
Strong oxidizing agents
Strong reducing agents

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

SENERGY ASAP TB DEEP

Version 1.0 Revision Date: 10/07/2020 SDS Number: 000000260318 Date of last issue: -
Date of first issue: 10/07/2020

Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration hazard expected.

Further information**Product:**

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

SENERGY ASAP TB DEEP

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/07/2020	000000260318	Date of first issue: 10/07/2020

Persistence and degradability**Components:****Poly(oxy-1,2-ethanediyl), .alpha.-[(1,1,3,3-tetramethylbutyl)phenyl]- .omega.-hydroxy-:**

Biodegradability : aerobic
 Inoculum: activated sludge, domestic, non-adapted
 Result: Readily biodegradable.
 Biodegradation: 90 %
 Exposure time: 28 d
 Method: Modified OECD-Screening-Test.

Bioaccumulative potential**Components:****ethyleneglycol:**

Partition coefficient: n-octanol/water : log Pow: approx. -1.36 (73 °F / 23 °C)
 Method: Calculation Hansch/Leo
 GLP: no data
 Remarks: Information taken from reference works and the literature.

Poly(oxy-1,2-ethanediyl), .alpha.-[(1,1,3,3-tetramethylbutyl)phenyl]- .omega.-hydroxy-:

Bioaccumulation : Remarks: Accumulation in organisms is not to be expected.

3-iodo-2-propynyl butylcarbamate; 3-iodoprop-2-yn-1-yl butylcarbamate:

Partition coefficient: n-octanol/water : log Pow: 2.81 (77 °F / 25 °C)
 Method: Partition coefficient (n-octanol/water), Shake-flask method
 GLP: yes

Quartz (SiO₂):

Partition coefficient: n-octanol/water : Remarks: not applicable

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
 Harmful to aquatic life.
 Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Do not contaminate ponds, waterways or ditches with chemi-

SENERGY ASAP TB DEEP

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/07/2020	000000260318	Date of first issue: 10/07/2020

cal or used container.
 Dispose of in accordance with national, state and local regulations.
 Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations**UNRTDG**

Not permitted for transport

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

SARA 311/312 Hazards : Acute
 Chronic

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

ethyleneglycol 107-21-1

US State Regulations**Pennsylvania Right To Know**

ethyleneglycol	107-21-1
Limestone	1317-65-3
crystalline silica	14808-60-7

New Jersey Right To Know

ethyleneglycol	107-21-1
Limestone	1317-65-3
crystalline silica	14808-60-7

SENERGY ASAP TB DEEP


Version 1.0 Revision Date: 10/07/2020 SDS Number: 000000260318 Date of last issue: -
Date of first issue: 10/07/2020

California Prop. 65

WARNING: This product can expose you to chemicals including 1,3-dichloropropene, which is/are known to the State of California to cause cancer, and ethyleneglycol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION**Further information****NFPA 704:****HMIS® IV:**

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z-1-A) : OSHA - Table Z-1-A (29 CFR 1910.1000)
 29 CFR 1910.1000 (Table Z-1) : OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
 29 CFR 1910.1001-1050 : OSHA - Specifically Regulated Substances (29 CFR 1910.1001-1050)
 ACGIH : USA. ACGIH Threshold Limit Values (TLV)
 ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
 NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
 NIOSH REL : USA. NIOSH Recommended Exposure Limits
 OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens
 OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
 OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants

SENERGY ASAP TB DEEP

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/07/2020	000000260318	Date of first issue: 10/07/2020

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
 29 CFR 1910.1000 (Table Z-1-A) / TWA value : Time Weighted Average (TWA):
 29 CFR 1910.1000 (Table Z-1) / PEL : Permissible exposure limit
 29 CFR 1910.1001-1050 / OSHA Action level : OSHA Action level:
 29 CFR 1910.1001-1050 / TWA value : Time Weighted Average (TWA):
 ACGIH / TWA : 8-hour, time-weighted average
 ACGIH / STEL : Short-term exposure limit
 ACGIHTLV / STEL value : Short Term Exposure Limit (STEL):
 ACGIHTLV / TWA value : Time Weighted Average (TWA):
 NIOSH / REL value : Recommended exposure limit (REL):
 NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
 OSHA CARC / PEL : Permissible exposure limit (PEL)
 OSHA P0 / TWA : 8-hour time weighted average
 OSHA P0 / C : Ceiling limit
 OSHA Z-1 / TWA : 8-hour time weighted average
 OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

SENERGY ASAP TB DEEP

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/07/2020	000000260318	Date of first issue: 10/07/2020

Revision Date : 10/07/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN