

SENERLASTIC SAHARA COLOR MEDIUM

Version 1.0 Revision Date: 09/18/2020 SDS Number: 000000260670 Date of last issue: -
Date of first issue: 09/18/2020

SECTION 1. IDENTIFICATION

Product name : SENERLASTIC SAHARA COLOR MEDIUM
Product code : 000000000051699898 000000000051699898

Manufacturer or supplier's details

Company name of supplier : Master Builders-Construction Systems
US, LLC
Address : 23700 CHAGRIN BLVD
Beachwood OH 44122
Emergency telephone : ChemTel: +1-813-248-0585


Recommended use of the chemical and restrictions on use

Recommended use : Product for construction chemicals
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with 29 CFR 1910.1200**

Skin sensitization : Category 1
Specific target organ toxicity : Category 1 (Lung)
- repeated exposure (Inhalation)

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H317 May cause an allergic skin reaction.
H372 Causes damage to organs (Lung) through prolonged or repeated exposure if inhaled.

Precautionary Statements : **Prevention:**
P280 Wear protective gloves.
P260 Do not breathe dust or mist.
P270 Do not eat, drink or smoke when using this product.
P264 Wash face, hands and any exposed skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.

SENERLASTIC SAHARA COLOR MEDIUM

Version 1.0 Revision Date: 09/18/2020 SDS Number: 000000260670 Date of last issue: -
 Date of first issue: 09/18/2020

Response:

P314 Get medical advice/ attention if you feel unwell.
 P303 + P352 IF ON SKIN (or hair): Wash with plenty of soap and water.
 P333 + P311 If skin irritation or rash occurs: Call a POISON CENTER or doctor/physician.
 P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

No data available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Quartz (SiO ₂)	14808-60-7	>= 50 - < 75
Kieselguhr, soda ash flux-calcined	68855-54-9	>= 1 - < 3
Titanium dioxide	13463-67-7	>= 1 - < 3
2-(Hydroxymethylamino)ethanol	34375-28-5	>= 0.1 - < 0.2

SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.
- If inhaled : If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.
- In case of skin contact : After contact with skin, wash immediately with plenty of water and soap.
Under no circumstances should organic solvent be used.
If irritation develops, seek medical attention.
- In case of eye contact : Hold eyes open and rinse slowly and gently with water for 15 to 20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.
Do NOT induce vomiting.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
Causes damage to organs through prolonged or repeated exposure if inhaled.

SECTION 5. FIRE-FIGHTING MEASURES

SENERLASTIC SAHARA COLOR MEDIUM

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/18/2020	000000260670	Date of first issue: 09/18/2020

- Suitable extinguishing media : Water spray
Foam
Dry powder
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : See SDS section 10 - Stability and reactivity.
- Hazardous combustion products : harmful vapours
nitrogen oxides
fumes/smoke
carbon black
carbon oxides
- Further information : The degree of risk is governed by the burning substance and the fire conditions.
If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.
- Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Do not breathe vapour/aerosol/spray mists.
Wear eye/face protection.
If exposed to high vapour concentration, leave area immediately.
Use personal protective clothing.
Handle in accordance with good building materials hygiene and safety practice.
- Environmental precautions : Contain contaminated water/firefighting water.
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Large spills should be collected mechanically (remove by pumping) for disposal.
Pick up with inert absorbent material (e.g. sand, earth etc.).
Spilled product should be disposed in accordance with all applicable government regulations.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid aerosol formation.
Avoid inhalation of mists/vapours.
Avoid skin contact.
Avoid contact with eyes.

SENERLASTIC SAHARA COLOR MEDIUM

Version 1.0 Revision Date: 09/18/2020 SDS Number: 000000260670 Date of last issue: -
 Date of first issue: 09/18/2020

Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.

Materials to avoid : No applicable information available.

Recommended storage temperature : 32 °F / 0 °C

Further information on storage stability : Minimum storage temperature:

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Titanium dioxide	13463-67-7	TWA value	10 mg/m ³	ACGIHTLV
		PEL (Total dust)	15 mg/m ³	29 CFR 1910.1000 (Table Z-1)
		TWA value (Total dust)	10 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		TWA (total dust)	15 mg/m ³	OSHA Z-1
		TWA (Total dust)	10 mg/m ³	OSHA P0
		TWA	10 mg/m ³ (Titanium dioxide)	ACGIH
Quartz (SiO ₂)	14808-60-7	TWA value (Respirable fraction)	0.025 mg/m ³	ACGIHTLV
		TWA value	0.05 mg/m ³ (Respirable dust)	29 CFR 1910.1001-1050
		OSHA Action level	0.025 mg/m ³ (Respirable dust)	29 CFR 1910.1001-1050
		REL value (Respirable dust)	0.05 mg/m ³	NIOSH
		TWA (Respirable dust)	0.05 mg/m ³	OSHA Z-1
		TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (respirable dust)	0.1 mg/m ³	OSHA P0

SENERLASTIC SAHARA COLOR MEDIUM

Version 1.0 Revision Date: 09/18/2020 SDS Number: 000000260670 Date of last issue: -
Date of first issue: 09/18/2020

		fraction)		
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH
		PEL (respirable)	0.05 mg/m ³	OSHA CARC
		TWA (Respirable dust)	0.05 mg/m ³ (Silica)	NIOSH REL
Kieselguhr, soda ash flux-calcined	68855-54-9	REL value	6 mg/m ³	NIOSH
		TWA value	20 millions of particles per cubic foot of air	29 CFR 1910.1000 (Table Z-3)
		TWA value	0.8 mg/m ³	29 CFR 1910.1000 (Table Z-3)
		OSHA Action level	0.025 mg/m ³ (Respirable dust)	29 CFR 1910.1001-1050
		TWA value	0.05 mg/m ³ (Respirable dust)	29 CFR 1910.1001-1050
		TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m ³ / %SiO ₂ (Silica)	OSHA Z-3
		TWA	6 mg/m ³ (Silica)	NIOSH REL

Engineering measures : No applicable information available.

Personal protective equipment

Respiratory protection : Wear appropriate certified respirator when exposure limits may be exceeded.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Safety glasses with side-shields.

Skin and body protection : Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

Protective measures : Do not inhale gases/vapours/aerosols.
Avoid contact with the skin, eyes and clothing.
Avoid exposure - obtain special instructions before use.

SENERLASTIC SAHARA COLOR MEDIUM

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/18/2020	000000260670	Date of first issue: 09/18/2020

Handle in accordance with good building materials hygiene and safety practice.
Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.
Hands and/or face should be washed before breaks and at the end of the shift.
At the end of the shift the skin should be cleaned and skin-care agents applied.
Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.
Gloves must be inspected regularly and prior to each use.
Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous

Color : white to light beige

Odor : like acrylic

Odor Threshold : No data available

pH : 8.5 - 10.5 (73 °F / 23 °C)
9

Melting point : No applicable information available.

Flash point : > 200 °F / > 93 °C
Method: Standard Method of Test for Flash Point by Setaflash Closed Tester, closed cup
> 199.99 °F / > 93.33 °C
Method: Standard Method of Test for Flash Point by Setaflash Closed Tester, closed cup

Evaporation rate : No applicable information available.

Flammability (solid, gas) : not determined

Upper explosion limit / Upper flammability limit : No applicable information available.

Lower explosion limit / Lower flammability limit : No applicable information available.

Vapor pressure : No applicable information available.

SENERLASTIC SAHARA COLOR MEDIUM

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/18/2020	000000260670	Date of first issue: 09/18/2020

Relative vapor density : Heavier than air.

Relative density : No applicable information available.

Density : 15 lb/USg (73 °F / 23 °C)

Solubility(ies)

Water solubility : partly miscible (59 °F / 15 °C)

Solubility in other solvents : No applicable information available.

Autoignition temperature : Based on the water content the product does not ignite.

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity

Viscosity, dynamic : No applicable information available.

Viscosity, kinematic : No applicable information available.

Explosive properties : Not explosive
Not explosive

Sublimation point : No applicable information available.

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability : The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions : The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid : See SDS section 7 - Handling and storage.

Incompatible materials : Strong acids
Strong bases
Strong oxidizing agents
Strong reducing agents

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

SENERLASTIC SAHARA COLOR MEDIUM

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/18/2020	000000260670	Date of first issue: 09/18/2020

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Product:

Acute oral toxicity : Remarks: No applicable information available.

Acute inhalation toxicity : Remarks: No applicable information available.

Acute dermal toxicity : Remarks: No applicable information available.

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Causes damage to organs (Lung) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

SENERLASTIC SAHARA COLOR MEDIUM

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/18/2020	000000260670	Date of first issue: 09/18/2020

Bioaccumulative potential**Components:****Quartz (SiO₂):**

Partition coefficient: n-octanol/water : Remarks: not applicable

Kieselguhr, soda ash flux-calcined:

Partition coefficient: n-octanol/water : Remarks: not applicable

Titanium dioxide:

Partition coefficient: n-octanol/water : Remarks: not applicable

2-(Hydroxymethylamino)ethanol:

Partition coefficient: n-octanol/water : log Pow: -2.205
Method: other (calculated)
GLP: no data

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information : There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with national, state and local regulations. Do not discharge into drains/surface waters/groundwater. Residues should be disposed of in the same manner as the substance/product.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION**International Regulations**

SENERLASTIC SAHARA COLOR MEDIUM

Version 1.0 Revision Date: 09/18/2020 SDS Number: 000000260670 Date of last issue: -
Date of first issue: 09/18/2020

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**US State Regulations****Pennsylvania Right To Know**

Kieselguhr, soda ash flux-calcined	68855-54-9
Titanium dioxide	13463-67-7
Quartz (SiO ₂) listed	14808-60-7

New Jersey Right To Know

Titanium dioxide	13463-67-7
Quartz (SiO ₂) listedSpecial Hazard.	14808-60-7

California Prop. 65

WARNING: This product can expose you to chemicals including acrylonitrile, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.


The ingredients of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION**Further information**

SENERLASTIC SAHARA COLOR MEDIUM

Version 1.0 Revision Date: 09/18/2020 SDS Number: 000000260670 Date of last issue: -
 Date of first issue: 09/18/2020

NFPA 704:**HMIS® IV:**

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z-1-A)	: OSHA - Table Z-1-A (29 CFR 1910.1000)
29 CFR 1910.1000 (Table Z-1)	: OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
29 CFR 1910.1000 (Table Z-3)	: OSHA Table Z-3 (Mineral Dusts) 29 CFR 1910.1000
29 CFR 1910.1001-1050	: OSHA - Specifically Regulated Substances (29 CFR 1910.1001-1050)
ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV	: American Conference of Governmental Industrial Hygienists - threshold limit values (US)
NIOSH	: NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA CARC	: OSHA Specifically Regulated Chemicals/Carcinogens
OSHA P0	: USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	: USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
29 CFR 1910.1000 (Table Z-1-A) / TWA value	: Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-1) / PEL	: Permissible exposure limit
29 CFR 1910.1000 (Table Z-3) / TWA value	: Time Weighted Average (TWA):
29 CFR 1910.1001-1050 / OSHA Action level	: OSHA Action level:
29 CFR 1910.1001-1050 / TWA value	: Time Weighted Average (TWA):
ACGIH / TWA	: 8-hour, time-weighted average
ACGIHTLV / TWA value	: Time Weighted Average (TWA):
NIOSH / REL value	: Recommended exposure limit (REL):

SENERLASTIC SAHARA COLOR MEDIUM

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/18/2020	000000260670	Date of first issue: 09/18/2020

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek

OSHA CARC / PEL : Permissible exposure limit (PEL)

OSHA P0 / TWA : 8-hour time weighted average

OSHA Z-1 / TWA : 8-hour time weighted average

OSHA Z-3 / TWA : 8-hour time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 09/18/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE

SENERLASTIC SAHARA COLOR MEDIUM

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	09/18/2020	000000260670	Date of first issue: 09/18/2020

, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN