

WS FLASHING PRIMER

Version Revision Date: SDS Number: Date of last issue: 08/04/2020
2.0 11/04/2020 000000315677 Date of first issue: 08/04/2020

SECTION 1. IDENTIFICATION

Product name : WS FLASHING PRIMER
Product code : 000000000057341271 000000000057341271

Manufacturer or supplier's details

Company name of supplier : Master Builders-Construction Systems
US, LLC
Address : 23700 CHAGRIN BLVD
Beachwood OH 44122
Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Adhesives and/or sealants
Product for construction chemicals
Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with 29 CFR 1910.1200**

Reproductive toxicity : Category 2
Short-term (acute) aquatic : Category 3
hazard
Long-term (chronic) aquatic : Category 3
hazard

GHS label elements

Hazard pictograms :



Signal Word : Warning
Hazard Statements : H361d Suspected of damaging the unborn child.
H402 Harmful to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read
and understood.
P273 Avoid release to the environment.

WS FLASHING PRIMER

Version 2.0 Revision Date: 11/04/2020 SDS Number: 000000315677 Date of last issue: 08/04/2020
 Date of first issue: 08/04/2020

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Aqueous solution based on:
polymers

Components

Chemical name	CAS-No.	Concentration (% w/w)
toluene	108-88-3	$\geq 0.1 - < 1$
ammonia	7664-41-7	$\geq 0.1 - < 1$
ammonia, aqueous solution	1336-21-6	$\geq 0.1 - < 1$
diuron	330-54-1	$\geq 0 - < 0.1$

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.
- If inhaled : If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.
- In case of skin contact : After contact with skin, wash immediately with plenty of water and soap.
Under no circumstances should organic solvent be used.
If irritation develops, seek medical attention.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.
Do NOT induce vomiting.

WS FLASHING PRIMER

Version 2.0 Revision Date: 11/04/2020 SDS Number: 000000315677 Date of last issue: 08/04/2020
Date of first issue: 08/04/2020

Most important symptoms and effects, both acute and delayed : Suspected of damaging the unborn child.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Foam
Water spray
Dry powder
Carbon dioxide (CO₂)

Unsuitable extinguishing media : water jet

Specific hazards during fire fighting : See SDS section 10 - Stability and reactivity.

Hazardous combustion products : harmful vapours
nitrogen oxides
fumes/smoke
carbon black
carbon oxides

Further information : The degree of risk is governed by the burning substance and the fire conditions.
If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.
Contaminated extinguishing water must be disposed of in accordance with official regulations.

Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Do not breathe vapour/aerosol/spray mists.
Wear eye/face protection.
If exposed to high vapour concentration, leave area immediately.
Use personal protective clothing.
Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions : Contain contaminated water/firefighting water.
Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up : Large spills should be collected mechanically (remove by pumping) for disposal.
Pick up with inert absorbent material (e.g. sand, earth etc.).
Spilled product should be disposed in accordance with all

WS FLASHING PRIMER

Version Revision Date: SDS Number: Date of last issue: 08/04/2020
 2.0 11/04/2020 000000315677 Date of first issue: 08/04/2020

applicable government regulations.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid formation of aerosol.
 Do not breathe vapors/dust.
 Avoid exposure - obtain special instructions before use.
 Avoid contact with skin and eyes.
 For personal protection see section 8.
 Smoking, eating and drinking should be prohibited in the application area.
 Provide sufficient air exchange and/or exhaust in work rooms.
 Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Store in original container.
 Keep cool. Protect from sunlight.
 Keep container tightly closed in a dry and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
- Further information on storage conditions : Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame.
 Protect from direct sunlight.
- Materials to avoid : Segregate from oxidizing agents.
- Further information on storage stability : The product is chemically stable.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
toluene	108-88-3	TWA value	20 ppm	ACGIHTLV
		REL value	100 ppm 375 mg/m ³	NIOSH
		STEL value	150 ppm 560 mg/m ³	NIOSH
		TWA value	100 ppm 375 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		STEL value	150 ppm 560 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		max. conc.	500 ppm	29 CFR

WS FLASHING PRIMER

Version 2.0 Revision Date: 11/04/2020 SDS Number: 000000315677 Date of last issue: 08/04/2020
 Date of first issue: 08/04/2020

				1910.1000 (Table Z-2)
		CLV	300 ppm	29 CFR 1910.1000 (Table Z-2)
		TWA value	200 ppm	29 CFR 1910.1000 (Table Z-2)
		TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m3	NIOSH REL
		ST	150 ppm 560 mg/m3	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm (10 minutes)	OSHA Z-2
		TWA	100 ppm 375 mg/m3	OSHA P0
		STEL	150 ppm 560 mg/m3	OSHA P0
ammonia	7664-41-7	STEL value	35 ppm	ACGIHTLV
		TWA value	25 ppm	ACGIHTLV
		REL value	25 ppm 18 mg/m3	NIOSH
		STEL value	35 ppm 27 mg/m3	NIOSH
		PEL	50 ppm 35 mg/m3	29 CFR 1910.1000 (Table Z-1)
		STEL value	35 ppm 27 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	50 ppm 35 mg/m3	OSHA Z-1
		STEL	35 ppm 27 mg/m3	OSHA P0
		TWA	25 ppm (Ammonia)	ACGIH
		STEL	35 ppm (Ammonia)	ACGIH
		TWA	25 ppm 18 mg/m3 (Ammonia)	NIOSH REL
		ST	35 ppm 27 mg/m3 (Ammonia)	NIOSH REL
ammonia, aqueous solution	1336-21-6	STEL value	35 ppm	ACGIHTLV
		TWA value	25 ppm	ACGIHTLV
		REL value	25 ppm 18 mg/m3	NIOSH
		STEL value	35 ppm 27 mg/m3	NIOSH

WS FLASHING PRIMER

Version 2.0 Revision Date: 11/04/2020 SDS Number: 000000315677 Date of last issue: 08/04/2020
 Date of first issue: 08/04/2020

		PEL	50 ppm 35 mg/m ³	29 CFR 1910.1000 (Table Z-1)
		STEL value	35 ppm 27 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		TWA	25 ppm (Ammonia)	ACGIH
		STEL	35 ppm (Ammonia)	ACGIH
		TWA	25 ppm 18 mg/m ³ (Ammonia)	NIOSH REL
		ST	35 ppm 27 mg/m ³ (Ammonia)	NIOSH REL
diuron	330-54-1	TWA value	10 mg/m ³	ACGIHTLV
		REL value	10 mg/m ³	NIOSH
		TWA value	10 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		TWA	10 mg/m ³	ACGIH
		TWA	10 mg/m ³	NIOSH REL
		TWA	10 mg/m ³	OSHA P0

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : Wear respiratory protection if ventilation is inadequate.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Safety glasses with side-shields.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures : Do not inhale gases/vapours/aerosols.
Avoid contact with the skin, eyes and clothing.
Avoid exposure - obtain special instructions before use.
Handle in accordance with good building materials hygiene and safety practice.
Wearing of closed work clothing is recommended.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

WS FLASHING PRIMER

Version Revision Date: SDS Number: Date of last issue: 08/04/2020
2.0 11/04/2020 000000315677 Date of first issue: 08/04/2020

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : orange, pink

Odor : slight odour, ammonia-like

Odor Threshold : not determined

pH : 7 - 10

Melting point : No data available

Boiling point : 212 °F / 100 °C

Flash point : No data available

Evaporation rate : No data available

Flammability (liquids) : Not classified as a flammability hazard

Upper explosion limit / Upper
flammability limit : No data available

Lower explosion limit / Lower
flammability limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : 0.99

Density : 0.99 g/cm³

Solubility(ies)
 Water solubility : soluble

 Solubility in other solvents : No data available

Partition coefficient: n-
octanol/water : No data available

Autoignition temperature : No data available

Decomposition temperature : No decomposition if stored and handled as pre-
scribed/indicated.

Viscosity
 Viscosity, dynamic : No data available

WS FLASHING PRIMER

Version	Revision Date:	SDS Number:	Date of last issue: 08/04/2020
2.0	11/04/2020	000000315677	Date of first issue: 08/04/2020

Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Sublimation point	:	No data available
Molecular weight	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No hazardous reactions if stored and handled as prescribed/indicated.
Chemical stability	:	The product is stable if stored and handled as prescribed/indicated.
Possibility of hazardous reactions	:	The product is stable if stored and handled as prescribed/indicated.
Conditions to avoid	:	See SDS section 7 - Handling and storage.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products if stored and handled as prescribed/indicated.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Product:

Acute inhalation toxicity	:	Acute toxicity estimate: > 200 mg/l Exposure time: 4 h Test atmosphere: vapor Method: Calculation method
---------------------------	---	---

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

WS FLASHING PRIMER

Version 2.0 Revision Date: 11/04/2020 SDS Number: 000000315677 Date of last issue: 08/04/2020
Date of first issue: 08/04/2020

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging the unborn child.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information**Product:**

Remarks : Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:****Ecotoxicology Assessment**

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Components:**ammonia:**

M-Factor (Acute aquatic toxicity) : 1

diuron:

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 10

Persistence and degradability

No data available

WS FLASHING PRIMER

Version 2.0 Revision Date: 11/04/2020 SDS Number: 000000315677 Date of last issue: 08/04/2020
Date of first issue: 08/04/2020

Bioaccumulative potential**Components:****toluene:**

Partition coefficient: n-octanol/water : log Pow: 2.73 (68 °F / 20 °C)
pH: 7
Method: other (measured)
GLP: no data
Remarks: Information taken from reference works and the literature.

ammonia:

Partition coefficient: n-octanol/water : log Pow: 0.23 (68 °F / 20 °C)
Method: other (calculated)
Remarks: The value has not been determined because the substance is inorganic.

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with national, state and local regulations.
Residues should be disposed of in the same manner as the substance/product.
Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

Packs that cannot be cleaned should be disposed of in the same manner as the contents.

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

WS FLASHING PRIMER

Version	Revision Date:	SDS Number:	Date of last issue: 08/04/2020
2.0	11/04/2020	000000315677	Date of first issue: 08/04/2020

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**US State Regulations****Pennsylvania Right To Know**

toluene	108-88-3
ammonia	7664-41-7
ammonia, aqueous solution	1336-21-6
diuron	330-54-1

New Jersey Right To Know

toluene	108-88-3
---------	----------

California Prop. 65

WARNING: This product can expose you to chemicals including diuron, which is/are known to the State of California to cause cancer, and toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL

TSCA list

The following substance(s) is/are subject to a Significant New Use Rule:

Alkanes, C14-16, chloro	1372804-76-6
-------------------------	--------------

The following substance(s) is/are subject to TSCA 12(b) export notification requirements:


Alkanes, C14-16, chloro	1372804-76-6
-------------------------	--------------

SECTION 16. OTHER INFORMATION**Further information**

WS FLASHING PRIMER

Version
2.0Revision Date:
11/04/2020SDS Number:
000000315677Date of last issue: 08/04/2020
Date of first issue: 08/04/2020

NFPA 704:



HMIS® IV:

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z-1-A)	: OSHA - Table Z-1-A (29 CFR 1910.1000)
29 CFR 1910.1000 (Table Z-1)	: OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
29 CFR 1910.1000 (Table Z-2)	: OSHA Table Z-2 (Toxic and Hazardous Substances) 29 CFR 1910.1000
ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV	: American Conference of Governmental Industrial Hygienists - threshold limit values (US)
NIOSH	: NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA P0	: USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	: USA. Occupational Exposure Limits (OSHA) - Table Z-2
29 CFR 1910.1000 (Table Z-1-A) / STEL value	: Short Term Exposure Limit (STEL):
29 CFR 1910.1000 (Table Z-1-A) / TWA value	: Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-1) / PEL	: Permissible exposure limit
29 CFR 1910.1000 (Table Z-2) / CLV	: Ceiling Limit Value:
29 CFR 1910.1000 (Table Z-2) / TWA value	: Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-2) / max. conc.	: Maximum concentration:
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
ACGIHTLV / STEL value	: Short Term Exposure Limit (STEL):
ACGIHTLV / TWA value	: Time Weighted Average (TWA):
NIOSH / REL value	: Recommended exposure limit (REL):

WS FLASHING PRIMER

Version	Revision Date:	SDS Number:	Date of last issue: 08/04/2020
2.0	11/04/2020	000000315677	Date of first issue: 08/04/2020

NIOSH / STEL value	:	Short Term Exposure Limit (STEL):
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / STEL	:	Short-term exposure limit
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-2 / TWA	:	8-hour time weighted average
OSHA Z-2 / CEIL	:	Acceptable ceiling concentration
OSHA Z-2 / Peak	:	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 11/04/2020

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensur-

WS FLASHING PRIMER

Version	Revision Date:	SDS Number:	Date of last issue: 08/04/2020
2.0	11/04/2020	000000315677	Date of first issue: 08/04/2020

ing the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

US / EN