

SRT Mesh (Stucco Reinforcing **Treatment Mesh**)

Glass fiber mesh for use with Stucco

DESCRIPTION

SRT Mesh is a woven fiber glass mesh with high mechanical strength and dimensional stability.

PACKAGING

Sold by the pallet. 33 rolls per pallet. 39.4" x 164' (100 cm x 50 m)

COLOR

White, printed "Not for use with EIFS"

WEIGHT

4.3 oz/yd2 (145 g/m2)

USES

Resurfacing Systems for improved crack resistance.

ADVANTAGES

Alkali resistant, compatible with all Base Coats; high tensile strength and flexibility for long-term durability.

Increased flexural & tensile strength at ultimate load compared to stucco without SRT Mesh/ Base Coat.

APPLICATION

Note: Allow stucco to cure a minimum of 6 days prior to application of Base Coat / SRT Mesh.

- 1. All surfaces to receive Base Coat and SRT Mesh must be clean, dry and free of contaminants.
- 2. Apply mixed Base Coat to entire surface of stucco with a stainless steel trowel.
- 3. Immediately place SRT Mesh against wet Base Coat and embed SRT Mesh into the Base Coat by troweling from center to the edges.
- 4. Lap SRT Mesh 64mm (2 1/2") minimum at edges.
- 5. Ensure SRT Mesh is continuous, void of wrinkles and embedded in Base Coat so that no SRT Mesh is visible.
- 6. If required, apply a second layer of Base Coat to achieve total nominal Base Coat / SRT Mesh thickness of 1.6 mm (1/16").
- 7. Allow Base Coat with embedded SRT Mesh to dry hard (normally 8 to 10 hours) prior to finish coat application.

LIMITATIONS

- For use with Wall Systems Stucco, and Stucco 1. For Stucco Wall Systems only. Not for use in Exterior Insulation and Finish Systems (EIFS) or Cement Board Stucco Systems.
 - 2. Store SRT Mesh in a cool, dry place protected from exposure to moisture.
 - 3. See specifications and details for complete information on installation of Wall Systems.
 - 4. Apply in temperatures of 4 °C (40 °F) and higher.
 - 5. Protect SRT Mesh during transportation and installation to avoid physical damage.

TECHNICAL SUPPORT

Consult Master Builders Solutions Technical Services Department at (800) 589-1336 for specific recommendations concerning all other applications. Consult the Wall Systems website at www.master-builders-solutions.com/en-us, for additional information about products and systems and for updated literature.

WARRANTY

Master Builders Solutions warrants this product to be free from manufacturing defects and to meet the technical properties on the current Product Bulletin, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. MASTER BUILDERS SOLUTIONS MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS. The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of Master Builders Solutions. In the absence of an extended warranty issued by Master Builders Solutions, any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. MASTER BUILDERS SOLUTIONS WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on Master Builders Solutions present knowledge and experience. However, Master Builders Solutions assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. Master Builders Solutions reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

For the most current version of this literature, please visit our website at www.master-builders-solutions.com/en-us.

Master Builders Solutions US 889 Valley Park Drive, Shakopee, MN 55379, USA www.master-builders-solutions.com/en-us

 Customer Service
 +1 (800) 433-9517

 Technical Service
 +1 (800) 589-1336