

MasterCast 726

New generation of PCE based plasticizer for Manufactured Concrete Products, specially engineered for use in production hollow-core slabs, masonry and paving blocks.

MATERIAL DESCRIPTION

MasterCast 726 is an innovative multipurpose plasticizer based polycarboxylic ether polymers specially developed for semi-dry concrete mixes. The product is suitable for the production of hollow-core slabs, masonry, and paving blocks. At the same time, **MasterCast 726** accelerates the strength development and reduces the cycle time whilst the appearance is maintained or even improved.

Due to its unique principle of action on the cement grain, **MasterCast 726** fully exploits the hydration potential of cement resulting in higher early strengths and shorter curing times.

APPLICATIONS

MasterCast 726 is suitable for manufacturing concrete products, especially:

- Pavers
- Blocks
- Hollow-core Slabs

FEATURES AND BENEFITS

MasterCast 726 offers the following benefits for the MCP industry to:

- Optimised mix design.
- · Enhanced productivity due to shorter cycle time.
- Higher early strength.
- Optimised curing cycles due to shorter curing times.

PACKAGING

MasterCast 726 is available in 20L & 1000 litre IBCs.

APPLICATION PROCEDURE

MasterCast 726 is a liquid ready-to-use admixture to be added to the concrete during the mixing process. The best results are obtained when the admixture is added after all the other components are already in the mixer and after the addition of at least 80% of the total water. The water content is adjusted to obtain the desired consistency or workability.

TYPICAL PROPERTIES*

Properties listed are for guidance and are not a guarantee of performance.

Appearance	Whitish to light brownish coloured liquid
Specific gravity @25°C	1.020 -1.040
pH value	5.0 - 7.0

DOSAGE

The normally recommended dosage rate is 0.4 to 1.2 litres per 100kg of cementitious material.

Other dosages may be used in special cases according to specific job site conditions. In this case, please consult our Technical Services Department.

COMPATIBILITY

MasterCast 726 is not compatible with MasterRheobuild superplasticizers.

STORAGE

MasterCast 726 must be stored in a place where the temperature does not drop below 5°C.

If stored in unopened containers according to manufacturer's instructions, the shelf life is 1 year.

HANDLING AND TRANSPORTATION

No special requirements must be observed while the product is used. Protection gloves and glasses are recommended. Do not eat, drink or smoke during the application. **MasterCast 726** is non-flammable, non-toxic or irritant and is not subject to special transport requirements.



MasterCast 726

New generation of PCE based plasticizer for Manufactured Concrete Products, specially engineered for use in production hollow-core slabs, masonry and paving blocks.

NOTE

Technical support, where provided, does not constitute supervisory responsibility. For additional information contact your local MB Construction Chemicals Solutions South Africa (Pty) Ltd representative. MB Construction Chemicals Solutions South Africa (Pty) Ltd shall not be liable for technical advice provided.

MB Construction Chemicals Solutions South Africa (Pty) Ltd reserves the right to have the true cause of any difficulty determined by accepted test methods. Undertaking such tests is not, and shall not be deemed to be, an admission of liability or an assumption of any risk, loss, damage or liability.

QUALITY AND RESPONSIBLE CARE

All products originating from MB Construction Chemicals Solutions South Africa (Pty) Ltd are manufactured under a management system independently certified to conform to the requirements of the quality standards ISO 9001, environmental and occupational health and safety standards.

* Properties listed are based on laboratory controlled tests.

DISCLAIMER

The technical information and application advice given in this MB Construction Chemicals Solutions South Africa (Pty) Ltd publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.