

MasterFinish 302

High performance chemical and physical mould release agent

MATERIAL DESCRIPTION

MasterFinish 302 is a multi-purpose chemical release agent for all types of shutters. It is mineral oil based and will produce satisfactory results on concrete surfaces under all construction and manufacturing conditions. Application by spray is recommended.

TYPICAL USES

MasterFinish 302 may be used for all general applications and is especially reliable for achieving high quality off-shutter finishes.

The use of specific mould releasing aids should always be determined by site trials. Oils should not be used on rubber or plastic moulds. Waxes are especially suited for non-absorbing shutters as a base preparation and chemical sensitive moulding materials such as plastic and rubber.

TYPICAL PROPERTIES*

Properties listed are for guidance and are not a guarantee of performance.

Appearance	Brownish liquid
Specific gravity @25°C	0.90
Coverage m ³ /l	25 - 35

DIRECTIONS FOR USE

Apply before the first casting and thereafter reapply immediately after stripping and cleaning the mould. Lightweight horticultural sprayers are ideal as **MasterFinish 302** is finely atomized to give a uniform coating. Excessive application should be avoided. Alternatively, application may be made by a fine haired brush, only a very thin coating should be made, and any excess removed.

PACKAGING

MasterFinish 302 is available in 20 litre or 210 litre drums.

STORAGE

Store under cover, out of direct sunlight and protect from extremes of temperatures. Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. **MasterFinish 302** has a shelf life of 12 months from date of manufacture when stored in undamaged, unopened packaging.

SAFETY PRECAUTIONS

As with all chemical products, care should be taken during use and storage to avoid contact with eyes mouth, skin and foodstuffs (which can also be tainted with vapour until product fully cured or dried). Treat splashes to eyes and skin immediately. If accidentally ingested, seek immediate medical attention. Keep away from children and animals. Reseal containers after use.

MasterFinish 302

High performance chemical and physical mould release agent

NOTE

Technical support, where provided, does not constitute supervisory responsibility. For additional information contact your local MB Construction Chemicals Solutions South Africa (Pty) Ltd representative MB Construction Chemicals Solutions South Africa (Pty) Ltd shall not be liable for technical advice provided. MB Construction Chemicals Solutions South Africa (Pty) Ltd reserves the right to have the true cause of any difficulty determined by accepted test methods. Undertaking such tests is not, and shall not be deemed to be, an admission of liability or an assumption of any risk, loss, damage or liability.

QUALITY AND RESPONSIBLE CARE

All products originating from MB Construction Chemicals Solutions South Africa (Pty) Ltd are manufactured under a management system independently certified to conform to the requirements of the quality standards ISO 9001, environmental and occupational health and safety standards.

* Properties listed are based on laboratory-controlled tests.

DISCLAIMER

The technical information and application advice given in this MB Construction Chemicals Solutions South Africa (Pty) Ltd publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.