

MasterSeal 934

Waterproofing tape for MasterSeal 754 application

MATERIAL DESCRIPTION

MasterSeal 934 is a butyl rubber coated tape. The butyl rubber tape has release liner with overlaps for easy removal.

FIELDS OF APPLICATIONS

MasterSeal 934 is self-adhesive tape which is used with **MasterSeal 754** pre-applied waterproofing applications at overlapping and damaged areas.

FEATURES AND BENEFITS

- Provides easy application at end points of membrane.
- It is used for damaged areas on membrane.
- Combines perfectly with **MasterSeal 754** membrane.

PACKAGING AND ROLL SIZES

MasterSeal 934 is supplied as 0.9mm thick, width of 200mm and length of 20 meters.

COLOUR

Grey

APPLICATION PROCEDURE

In **MasterSeal 754** pre-applied membrane applications, **MasterSeal 934** is placed to the edges, end points and damaged areas. Protection foil is removed from the accessory. **MasterSeal 754** is combined with self-adhesive surface of **MasterSeal 934**.

COVERAGE

Application requirements can vary according to the total consumption of the project.

STORAGE AND SHELF LIFE

MasterSeal 934 has a shelf-life of 12 months from date of production if stored properly in unopened, undamaged, original packaging in dry conditions and at temperatures between +5°C and +30°C.

NOTE

Technical support, where provided, does not constitute supervisory responsibility. For additional information contact your local MB Construction Chemicals Solutions South Africa (Pty) Ltd representative. MB Construction Chemicals Solutions South Africa (Pty) Ltd shall not be liable for technical advice provided.

MB Construction Chemicals Solutions South Africa (Pty) Ltd reserves the right to have the true cause of any difficulty determined by accepted test methods. Undertaking such tests is not, and shall not be deemed to be, an admission of liability or an assumption of any risk, loss, damage or liability.

QUALITY AND RESPONSIBLE CARE

All products originating from MB Construction Chemicals Solutions South Africa (Pty) Ltd are manufactured under a management system independently certified to conform to the requirements of the quality standards ISO 9001, environmental and occupational health and safety standards.

* Properties listed are based on laboratory controlled tests.

MasterSeal 934

Waterproofing tape for MasterSeal 754 application

TECHNICAL DATA*

Material composition	Substrate: Polypropylene foil Coating: Self-adhesive butyl rubber, high elastic, resistant to ageing Protection: Release foil
Total width	200mm
Total thickness	1.2mm (without release liner) 1.0mm (with release liner)
Length per roll	20 meters
Material weight	1270g/m ² (with release liner) 1180g/m ² (without release liner)
Resistance to temperature	-30°C to 60°C
Burst pressure: max.	2.4 bar
Breaking load longitudinal DIN EN ISO 527-3	105N / 15mm
Breaking load lateral DIN EN ISO 527-3	82N / 15mm
Extension break longitudinal DIN EN ISO 527-3	448%
Extension break lateral DIN EN ISO 527-3	805%
Peel test on neutral PVC carrier	>13N / 20mm
Chemical properties	Resistance to wide range of chemical liquids

DISCLAIMER

The technical information and application advice given in this MB Construction Chemicals Solutions South Africa (Pty) Ltd publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.