

MasterTop SR 1, 3 & 5

Silica aggregates for use in conjunction with MasterTop and MasterProtect systems

MATERIAL DESCRIPTION

MasterTop SR aggregates are used with various resin products to produce industrial floors filled coatings and slip-resistant profiles.

MasterTop SR 1: 0.3-0.65mm

MasterTop SR 3: 0.4-0.85mm

MasterTop SR 5: 0.8-1.2mm

PRIMARY USES

MasterTop SR aggregates are designed to increase the impact and slip resistance of industrial coatings and flooring systems. Also used to increase the bond between concrete substrates and multi-layer systems and to provide a mechanical key for overlay systems.

PACKAGING

MasterTop SR aggregates are available in 25kg triple ply sacks.

TYPICAL APPLICATIONS

MasterTop SR aggregates when used as per the relevant method statements for Master Builders Solutions products can be used in locations such as:

- Car Park Decks
- Kitchens
- Engineering Workshops
- Garages
- Warehouses
- Power Stations
- Agricultural Buildings
- Aircraft Hangars
- Abattoirs
- Loading Bays
- Factories

COVERAGE

As per the relevant Master Builders Solutions Product Method Statements.

EQUIPMENT AND CARE

Clean all equipment with water immediately after use.

STORAGE

Store out of direct sunlight, clear of the ground on pallets protected from rainfall. Avoid excessive compaction.

SAFETY PRECAUTIONS

MasterTop SR aggregates are inert and harmless, however, as with other products containing Portland cement and resins, **MasterTop SR** aggregates mixes may cause irritation. In case of contact with eyes, immediately flush with plenty of water for at least 15 minutes. Call a physician. In case of contact with skin, wash skin thoroughly. For further information refer to the material safety data sheet.

ADVANTAGES

- Economical
- High impact
- Wear resistant
- Non-oxidising
- Slip resistant
- Improves bond
- Reduces dusting

MasterTop SR 1, 3 & 5

Silica aggregates for use in conjunction with MasterTop and MasterProtect systems

NOTE

Technical support, where provided, does not constitute supervisory responsibility. For additional information contact your local MB Construction Chemicals Solutions South Africa (Pty) Ltd representative. MB Construction Chemicals Solutions South Africa (Pty) Ltd shall not be liable for technical advice provided.

MB Construction Chemicals Solutions South Africa (Pty) Ltd reserves the right to have the true cause of any difficulty determined by accepted test methods. Undertaking such tests is not, and shall not be deemed to be, an admission of liability or an assumption of any risk, loss, damage or liability.

QUALITY AND RESPONSIBLE CARE

All products originating from MB Construction Chemicals Solutions South Africa (Pty) Ltd are manufactured under a management system independently certified to conform to the requirements of the quality standards ISO 9001, environmental and occupational health and safety standards.

* Properties listed are based on laboratory controlled tests.

DISCLAIMER

The technical information and application advice given in this MB Construction Chemicals Solutions South Africa (Pty) Ltd publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.