

Pecitape WS

Self-adhesive waterproofing tape for waterproof corner and perimeter joints

MATERIAL DESCRIPTION

Self-adhesive, fleece-lined butyl rubber tape with cover foil on the adhesive side.



AREAS OF APPLICATION

- For indoor and outdoor use.
- For walls and floors.
- For wet areas with non-pressurised water such as showers in residential buildings, hotels, senior citizen homes and hospitals.
- For outer areas, e.g. balconies and terraces.



Pecitape WS can be rapidly and reliably applied also to unusual shapes (here round shower).

FEATURES AND BENEFITS

- Base material butyl rubber, therefore ductile.
- Self-adhesive, therefore simple and reliable working.
- High bond to clean substrates.
- Immediately functional, therefore rapid workflow.

SURFACE PREPARATION

The substrate must be sound, dry, clean, practically level and free of oil, grease and other residues which could impair adhesion. Clean relevant area and remove any residues in the transition area wall/floor. Sweep off with a fine broom.

APPLICATION

In combination with the bonded waterproofing to be applied in liquid form:

1. Unroll **Pecitape WS** to required length.
2. Remove protective foil and press **Pecitape WS** to the substrate applying positive pressure but without stretching the tape. Ensure accurate application of the tape in corners.
3. Apply waterproofing material over **Pecitape WS** and make sure that it is fully covered.

In combination with waterproofing membranes:

1. Affix waterproofing membrane in accordance with the respective technical data sheet; butt-joint membranes contrary to the usual method (**Pecitape WS** is not laid over wall/floor junctions and butt joints until the waterproofing membranes are installed).
2. Unroll **Pecitape WS** to required length.
3. Remove protective foil and press **Pecitape WS** to the substrate applying positive pressure but without stretching the tape. Ensure accurate application of the tape in corners.

Pecitape WS

Self-adhesive waterproofing tape for waterproof corner and perimeter joints

Subsequent work:

1. Tile laying can continue immediately.



Remove protective foil and press **Pecitape WS** to the substrate applying positive pressure but without stretching the tape.

COLOUR

Blue-Grey

NOTE

The substrate must be clean, sound and able to bear weight. Install **Pecitape WS** without stretching it. Once installed the tape cannot be removed without being damaged. The application of **Pecitape WS** is only allowed in areas where water is not subject to hydrostatic pressure.

DISCLAIMER

The technical information and application advice given in this MB Construction Chemicals Solutions South Africa (Pty) Ltd publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

STORAGE AND SHELF LIFE

Store under cover out of direct sunlight and protect from extremes of temperature. Shelf life is 24 months from date of manufacture when stored as above. Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage and disposal instructions refer to the Material Safety Data Sheet.

NOTE

Technical support, where provided, does not constitute supervisory responsibility. For additional information contact your local MB Construction Chemicals Solutions South Africa (Pty) Ltd representative. MB Construction Chemicals Solutions South Africa (Pty) Ltd shall not be liable for technical advice provided.

MB Construction Chemicals Solutions South Africa (Pty) Ltd reserves the right to have the true cause of any difficulty determined by accepted test methods. Undertaking such tests is not, and shall not be deemed to be, an admission of liability or an assumption of any risk, loss, damage or liability.

QUALITY AND RESPONSIBLE CARE

All products originating from MB Construction Chemicals Solutions South Africa (Pty) Ltd are manufactured under a management system independently certified to conform to the requirements of the quality standards ISO 9001, environmental and occupational health and safety standards.

* Properties listed are based on laboratory controlled tests.