

## **DECLARATION OF PERFORMANCE**

according Annex III of the Regulation (EU) No 305/2011  
amended by Commissions delegated Regulation (EU) No 574/2014

---

**No 850002**

---

Unique identification code of the product-type: **MasterProtect 8500 CI**

---

Intended use/es:

**EN 1504-2**  
**Principles 1.1/2.1/8.1**  
Surface protection product/hydrophobic impregnation

---

Manufacturer:

**Master Builders Solutions Deutschland GmbH**  
**Donnerschweer Str. 372**  
**D-26123 Oldenburg**

---

System/s of AVCP:

**EN 1504-2: System 2+ (for uses in buildings and civil engineering works)**

---

Harmonised standard:

**EN 1504-2:2004**

---

Notified body/ies:

**KIWA Polymer Institut**  
**D-65439 Flörsheim-Wicker**  
**(CE identification number: 1119)**

---

Declared performance/s:

**EN 1504-2:**

**Table 1: Performance of MasterProtect 8500 CI:**

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Depth of penetration	Class II (> 10mm)	System 2+	EN 1504-2:2004
Water absorption and resistance to alkali	Absorption ratio < 7,5% compared with the untreated specimen < 10% after immersion in alkali solution		
Drying rate for hydrophobic impregnation	Class I (> 30%)		
Loss of mass after freeze-thaw salt stress	at least 20 cycles later than that of the not impregnated specimen		
Dangerous substances	Comply with 5.3 (EN 1504-2)		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Klaus Claassen  
 Product Manager Waterproofing Resins Europe

Oldenburg, 04.01.2021

**Annex:**

Technical data sheets for use in buildings (system build-ups according to respective technical data sheets)