## **DECLARATION OF PERFORMANCE**

DE0251/05 (1/2) 04.01.2021



Unique identification code of the product-type:

MasterSeal NP 474 (DE0251/05)

Intended use/es:

Sealants for non-structural use in joints in buildings and pedestrian walkways

EN 15651-1 Type F EXT-INT-CC
Sealants for facade elements, Class 25 HM
Conditioning: Method A
Substrate: Mortar M1 without primer

EN 15651-4 Type PW EXT-INT-CC
Sealants for pedestrian walkways, Class 25 HM
Conditioning: Method A
Substrate: Mortar M1 without primer

Manufacturer:

Master Builders Solutions Deutschland GmbH, Donnerschweer Str. 372, D-26123 Oldenburg

System/s of AVCP:

System 3, System 3 (Reaction to fire)

Harmonised standard / Notified body/ies:

EN 15651-1:2012 EN 15651-4:2012 GINGER CEBTP (NB 0074)

## **DECLARATION OF PERFORMANCE**

DE0251/05 (2/2) 04.01.2021



Unique identification code of the product-type:

## MasterSeal NP 474 (DE0251/05)

Declared performance/s:

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	Class E	System 3	EN 15651-1:2012 EN 15651-4:2012
Release of chemicals dangerous to the environment and health	Evaluated	System 3	EN 15651-1:2012 EN 15651-4:2012
Tensile properties at maintained extension	Pass		EN 15651-4:2012
Tear resistance	Pass		LIN 13031-4.2012
Resistance to flow	≤ 3 mm		EN 15651-1:2012
Loss of volume	≤ 10 %		EN 15651-1:2012 EN 15651-4:2012
Tensile properties at maintained extension after immersion in water at 23 °C	Pass		EN 15651-1:2012
Adhesion/cohesion properties at maintained extension after 28 days water immersion	Pass		EN 15651-4:2012
Adhesion/cohesion properties at maintained extension after 28 days salt water immersion	Pass		EN 15651-4:2012
Tensile properties at -30 °C	≤ 0,9 MPa		
Tensile properties at maintained extension at -30 °C	Pass		EN 15651-1:2012 EN 15651-4:2012
Durability	Pass		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) No 305/2011 and No 574/2014, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Jürgen Baumann

Volker Schwarz

