

DECLARATION OF PERFORMANCE

n° IT0093/02

MasterSeal P385 comp D

1) Unique identification code of the product-type

EN 1504-3: Methods 3.1/3.2/4.4/7.1/7.2 EN 1504-02: Methods 5.1

2) Intended use or uses

Fast drying cement-based mortar

3) Manufacturer

Master Builders Solutions Italia SpA, via Vicinale delle Corti 21, 31100 Treviso

4) System or systems of assessment and verification of constancy of performance (AVCP)

System 2+

5) Harmonized standard:

EN 1504-3: 2005; EN 1504-2: 2005

6) Notified body

ICMQ SpA, identification n° 1305

7) Declared performances

Essential characteristics	Performance	Harmonized technical specification
Compressive strength	Class R4	EN 1504-3: 2005
Chloride ion content	≤ 0,05%	
Adhesive bond	≥ 2,0 MPa	EN 1504-3: 2005; EN 1504-2: 2005
Capillary absorption	≤ 0,5 kg/m ² .h ^{0,5}	
Carbonation resistance	Pass	EN 1504-3: 2005
Elastic modulus	≥ 20 GPa	
Thermal compatibility: freeze-thaw, thunder shower, dry cycling	≥ 2,0 MPa	
Abrasion resistance	< 1050 mg	EN 1504-2: 2005
Impact resistance	Class III	
Reaction to fire	Class A1	EN 1504-3: 2005; EN 1504-2: 2005
Dangerous substances	See SDS	

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dario Micheletto

Resp. Quality Control

Treviso, 01 January 2021

