

MasterTop F

Fillers for MasterTop, MasterSeal and Ucrete systems.

MATERIAL DESCRIPTION

MasterTop F is a family of fillers to be used as part of MasterTop and Ucrete flooring system and for MasterSeal waterproofing systems.

Product	Description
MasterTop F1	Quartz filler 0,1 - 0,3 mm
MasterTop F1X	Mix of Quartz filler 0,1- 0,4 mm, france quartz and glass microspheres
MasterTop F1W E	Mix of quartz filler 0,1- 0,4 mm, france quartz and barite filler
MasterTop F18	Quartz filler 0,2 - 0,5 mm
MasterTop F340	Quartz filler 0,2 - 1 mm
MasterTop F5	Quartz filler 0,3 - 0,8 mm
MasterTop F5 AS	Conductive filler 0,3 - 0,8 mm
MasterTop TIX 9	Tixotropic filler agent
MasterTop F11	Coloured quartz 0,4 - 0,8 mm
MasterTop F11 AS	Coloured conductive filler 0,4 - 0,8 mm
MasterTop F5 per Ucrete	High shore filler 0,3 - 0,8 mm
Ucrete F20	High shore filler 0,8 - 1,2 mm
Ucrete F20 AS	High shore conductive Filler 0,8 - 1,2 mm
Ucrete F25	High shore filler 1,2 - 1,8 mm

MAIN APPLICATIONS

MasterTop F vengono utilizzati nei sistemi MasterTop, Ucrete e MasterSeal.

FEATURES AND BENEFITS

Basic part of MasterTop, Ucrete and MasterSeal systems.

CONSUMPTION

Refer to the individual data sheets of each specific MasterTop, Ucrete and MasterSeal systems.

PACKAGING

Product	Pack
MasterTop F1	25 kg bag
MasterTop F1X	15 kg bag
MasterTop F1W E	21 kg bag
MasterTop F18	25 kg bag
MasterTop F340	25 kg bag
MasterTop F5	25 kg bag
MasterTop F5 per Ucrete	25 kg bag
MasterTop F5 AS	25 kg bag
MasterTop TIX 9	1 kg bag
MasterTop F11	25 kg bag
MasterTop F11 AS	25 kg bag
Ucrete F20	25 kg bag
Ucrete F20 AS	25 kg bag
Ucrete F25	25 kg bag

STORAGE

Store the product in a sheltered, dry place at a temperature between +5°C and +25°C.

APPLICATION SHEET

Refer to the individual data sheets of each specific MasterTop, Ucrete and MasterSeal systems.

DECLARATION OF PERFORMAN (DoP) and CE marking

According to the European Regulation (EU No 305/2011 and EU No. 574/2014) the materials have their own CE marking EN 13139 and DoP (Declaration of Performance).

SAFETY INSTRUCTION

For information on the correct and safe use, transport, storage and disposal of the product, consult the most recent Safety Data Sheet.

MasterTop F

Fillers for MasterTop, MasterSeal and Ucrete systems.

OTHER SERVICES

For price analysis, specifications, supplementary brochures, references, reports and technical assistance, visit the website www.master-builders-solutions.com/it-it or contact infomac@mbcc-group.com.

Since 16/12/1992, Master Builders Solutions Italia Spa has been operating under a Certified Quality System compliant with the UNI EN ISO 9001 Standard. Furthermore, the Environmental Management System is certified according to the UNI EN ISO 14001 Standard and the Safety Management System is certified according to the UNI ISO 45001 Standard.

Master Builders Solutions Italia Spa

Via Vicinale delle Corti, 21 – 31100 Treviso – Italia

T +39 0422 429200 F +39 0422 421802

www.master-builders-solutions.com/it-it

e-mail: infomac@mbcc-group.com

For further information, please consult the local Technician of Master Builders Solutions. The technical advice on how to use our products, either written or verbally given, are based on the current state of our scientific and practical expertise, and does not imply the assumption of any guarantee and/or responsibility for the final results of works executed using our products.

Therefore, the customer is not exempted from the exclusive task and responsibility of verifying the suitability of our products for the intended use and purposes.

This version supersedes all the previous ones.