

## **DECLARATION OF PERFORMANCE**

according Annex III of the regulation (EU) No 305/2011 amended by Commissions delegated Regulation (EU) No. 574/2014

For the system "MasterTop 1324 R"

	No. <b>132403</b>			
1.	Unique identification code of the product-type: EN 13813: 2002: SR-B1.5-AR1-IR4			
2.	Intended use/es: Synthetic resin screed for internal uses			
3.	Manufacturer: Master Builders Solutions Deutschland GmbH Donnerschweer Str. 372 D-26123 Oldenburg			
4.	System/s of assessment and verification of constancy of performance (AVCP): System 4 for internal uses System 3 for reaction to fire			
5.	Harmonised standard: EN 13813: 2002			
6.	Notified body/ies: For the reaction to fire: MPA Universität Stuttgart (0672) Prüfinstitut Hoch (1508) MPA Dresden (0767)			





7. Declared performances determined in System build-up MasterTop 1324 R:

Performance	System of assessment and verification of constancy of performance	Harmonisierte technische Spezifikation
Bfl-s1	System 3	
SR		
NPD		
≤ AR1		
≥ B1,5		EN 13813:2002
≥ IR4	System 4	
NPD		
NPD		
NPD		
NPD	1	
	BfI-s1 SR NPD ≤ AR1 ≥ B1,5 ≥ IR4 NPD NPD NPD	Performanceand verification of constancy of performanceBfl-s1System 3SR

NPD: No Performance Determined

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

Appropriate Technical Documentation to reaction to fire: No. 9026244000-61 / 9026244000-71 / 9026244000-81 No. PB-Hoch-130297, 130298, KB-Hoch-130299 No. PB-Hoch-120258, 120259, KB-Hoch-120260

Fulfilled requirements: Bfl-s1 Thickness max. of the flooring system: 3 mm

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Henrik Willem Vetter European Marketing Manager Performance Flooring

Oldenburg, 04.01.2021 <u>Annex:</u> Technical data sheets for use in buildings (system build-ups according to respective technical data sheets)