

## **DECLARATION OF PERFORMANCE**

according Annex III of the regulation (EU) No 305/2011 amended by Commissions delegated Regulation (EU) No. 574/2014

For the system "MasterTop 1324 N&B"

| No. <b>132405</b> |  |  |  |  |
|-------------------|--|--|--|--|
| 1.                | Unique identification code of the product-type:<br>EN 13813: 2002: SR-B1.5-AR1-IR4   |  |  |  |
| 2.                | Intended use/es:<br>Synthetic resin screed for internal uses   |  |  |  |
| 3.                | Manufacturer:<br>Master Builders Solutions Deutschland GmbH<br>Donnerschweer Str. 372<br>D-26123 Oldenburg                                 |  |  |  |
| 4.                | System/s of assessment and verification of constancy of performance (AVCP):<br>System 4 for internal uses<br>System 3 for reaction to fire |  |  |  |
| 5.                | Harmonised standard:<br>EN 13813: 2002   |  |  |  |
| 6.                | Notified body/ies:<br>For the reaction to fire:<br>MPA Universität Stuttgart (0672)  |  |  |  |





7. Declared performances determined in System build-up MasterTop 1324 N&B:

| Essential characteristics       | Performance | System of assessment<br>and verification of<br>constancy of<br>performance | Harmonisierte<br>technische<br>Spezifikation |
|---------------------------------|-------------|--|--|
| Reaction to fire                | Bfl-s1      | System 3   |  |
| Release of corrosive substances | SR          | System 4   | EN 13813:2002                                |
| Water permeability              | NPD         |  |  |
| Wear resistance                 | ≤ AR1       |  |  |
| Bond strength                   | ≥ B1,5      |  |  |
| Impact resistance               | ≥ IR4       |  | 211 100 10.2002                              |
| Sound insulation                | NPD         |  |  |
| Sound absorption                | NPD         |  |  |
| Thermal resistance              | NPD         |  |  |
| Chemical resistance             | NPD         |  |  |
|                                 |             |  |  |

NPD: No Performance Determined

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

Appropriate Technical Documentation to reaction to fire: No. 9026244000-61 / 9026244000-71 / 9026244000-81

Fulfilled requirements: Bfl-s1 Thickness max. of the flooring system: 3 mm

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Vitte

Henrik Willem Vetter European Marketing Manager Performance Flooring

Oldenburg, 04.01.2021

<u>Annex:</u> Technical data sheets for use in buildings (system build-ups according to respective technical data sheets)